

Data Dictionary



Spitfire Management, LLC
84 Business Park Drive
Suite 111
Armonk, NY 10504
www.spitfiremanagement.com

Revision Number: 4.3.06.24.2013

© Copyright 2004-2013 Spitfire Management, LLC. All Rights Reserved.
No part of this document may be reproduced, stored in a retrieval system, or transmitted, in any form or by any means electronic or mechanical, photocopying, recording, or otherwise without written permission of Spitfire Management, LLC.

© 2002-2013 Microsoft, Microsoft Business Solutions (MBS), and Solomon are either registered trademarks or trademarks of Microsoft Corporation, Great Plains Software, Inc. or Microsoft Business Solutions Corporation in the United States and/or other countries. FRx are either trademarks or registered trademarks of FRx Software Corporation. Microsoft Business Solutions Corporation is a wholly-owned subsidiaries of Microsoft Corporation.

The names of actual companies and products mentioned herein may be the trademarks of their respective owners.

Spitfire Management, LLC.
84 Business Park Drive
Armonk, NY 10504
ph. 914.273.0809
fax: 914.273.4208
www.spitfiremanagement.com

SPM

xsfAlert**User Alerts List**

Contains a row for each Spitfire alert; Rows are removed from this table when alerts are discarded

AlertKey	Guid Default(newid())	Primary Key:1
UserKey	Guid	In Index IX_xsfaAlert:1 References xsfUser.UserKey
Status	Char(1) Default('N')	New; Saved In Index IX_xsfaAlert:2
NotificationType	Char(1) Default('N')	None; eMail; future: IM
Created	Datetime(23,3) Default(getdate())	In Index IX_xsfaAlert:3
Notified	Datetime(23,3) NULL	When notification sent (by sfATC)
Viewed	Datetime(23,3) NULL	When viewed from dashboard
Description	Varchar(50)	
AlertText	Varchar(2000)	Length of PJCOMMUN in Solomon is 254
DocMasterKey	Guid NULL	Weak link to corresponding Spitfire Document
Project	Char(16) NULL	
Source	Varchar(30) NULL	
SourceKey	Varchar(50) NULL	
Info1	Varchar(50) NULL	
Info2	Varchar(50) NULL	
UpdateTS	Timestamp(8) NULL	

Fields: 16

SPM

xsfAlertSubscription**Alert Subscriptions**

Each row describes a subscription to alerts

AlertSubscriptionKey	Guid Default(newid())	Primary Key:1
AlertDefKey	Guid	Link to xsfAlertType or xsfComplianceType
UserKey	Guid NULL	Either UserKey or UCRoleKey References xsfUser.UserKey
UCRoleKey	Guid NULL	Subscription applies to all role members References xsfUCRole.UCRoleKey
DocTypeKey	Guid NULL	For subscriptions to all Document that match the specified doc type References xsfDocType.DocTypeKey
Subtype	Varchar(8) NULL	
Description	Varchar(2000) Default("")	Free form; Inactive subscriptions still receive from existing documents unless the description includes SUSPEND
DivisionID	Char(10) NULL	
Project	Char(16) NULL	For subscriptions to all Document that match the specified project
Recurs	Char(2) Default('NA')	
LeadTime	Smallint(5) Default((0))	
IncludeRoutees	Bit(1) Default((1))	Provides xsfDocAlert default
RemoteNotify	Bit(1) Default((0))	When TRUE, alerts associated with this subscription are also sent remotely
Suspend	Bit(1) Default((0))	When TRUE, alerts will not be delivered
Active	Bit(1) Default((1))	When FALSE, does not create alerts tracking on new documents
UpdateTS	Timestamp(8) NULL	

Fields: 16

SPM

xsfAlertType

Alert Types

Each row defines a particular type of alert

Field Name	Field Type	Description
AlertTypeKey	Guid Default(newid())	Primary Key:1
AlertName	Varchar(50)	Display name for the alert. In Index IX_xsfAlertType:2
Recurs	Char(2) Default('NA')	Default recurrence for this alert
LeadTime	Smallint(5) Default((0))	Default lead time in days
Sequence	Smallint(5) Default((1000))	Display sequence (by name withing sequence) In Index IX_xsfAlertType:1
WorkflowScript	Varchar(-1) NULL	
EditName	Bit(1) Default((0))	When true, user can rename this alert on a document
ShowDate	Bit(1) Default((1))	When true, the alert date is available on the document alert grid
AllowsRecur	Bit(1) Default((1))	When true, the recurrence for this alert on a document can be changed
AllowsLeadTime	Bit(1) Default((1))	When true, the lead time for this alert on a document can be changed
Active	Bit(1) Default((1))	
BuiltIn	Bit(1) Default((0))	TRUE for Spitfire distributed alerts
UpdateTS	Timestamp(8)	

Fields: 13

SPM

xsfAllocation

Allocations and Markups

Each row defines an allocation or markup based upon coding of project, task and category

Field Name	Field Type	Description
AllocationKey	Guid Default(newid())	Primary Key:1
EntryType	Char(1) Default('A')	
ContractType	Varchar(8) NULL	
Project	Char(16) NULL	
SourceProjEntity	Char(32) NULL	
SourceAcctCategory	Char(16)	
TargetAcctCategory	Char(16)	
TargetProjEntity	Char(32) NULL	
PrintAs	Varchar(50) NULL	
Sequence	Smallint(5) Default(0)	
ThresholdAmount	Money(19,4) NULL	
AllocationPct	Numeric(7,3) NULL	
AllocationAmount	Money(19,4) NULL	
MarkupPct	Numeric(7,3) NULL	
MarkupAmount	Money(19,4) NULL	
Active	Bit(1)	
UpdateTS	Timestamp(8)	

Fields: 17

SPM

xsfAPInfo

AP Doc Summary by Project

Each row defines the AP amount allocated to the project with keys to link back to the original AP Doc

Project	Char(16)	Primary Key:1
BatNbr	Char(10)	Primary Key:2
RefNbr	Char(10)	Primary Key:3
Acct	Char(10)	
SubAcct	Char(24)	
DocType	Char(2)	
DocBal	Money(19,4)	
OrigAmt	Money(19,4)	
PC_Status	Char(1)	
Rlsed	Bit(1) Default(0)	
OpenDoc	Bit(1) Default(1)	
UpdateTS	Timestamp(8) NULL	

Fields: 12

SPM

xsfArchiveDB

Archive Databases for static catalog content

Each row identifies another DBN to which catalog data has been migrated for long term storage

ArchiveDBKey	Guid Default(newid())	Primary Key:1
ArchiveDBN	Varchar(50)	In Index AK_xsfArchiveDB (Unique):1
Created	Datetime(23,3) Default(getdate())	
UpdateTS	Timestamp(8)	

Fields: 4

SPM

xsfAttribute

Document Attributes

Enumerates the Attributes, including instructions for a document or contact (possible values are in xsfDocTypeSubcodes)

DocAttributeKey	Guid Default(newid())	Primary Key:1
AttrOwnerKey	Guid	Link to document or contact company In Index AK_xsfAttribute (Unique):1
AttrType	Varchar(8) Default('IN')	Indicates the set of attributes from which this row was derived In Index AK_xsfAttribute (Unique):2
AttrValue	Varchar(8)	Specifies the specific attribute of the set In Index AK_xsfAttribute (Unique):3
Paragraph	Varchar(16) NULL	
Specification	Varchar(16) NULL	
Amount	Money(19,4) NULL	Can be used for amount or percent
Quantity	Money(19,4) NULL	
Value	Money(19,4) NULL	
Description	Varchar(1024) NULL	
Note	Varchar(-1) NULL	
Recorded	Datetime(23,3) Default(getdate())	
Reviewed	Datetime(23,3) NULL	
UpdateTS	Timestamp(8)	

Fields: 14

SPM

xsfChgMarkup

Change Order Markup

Each row defines a markup percent for a Project, Task and Category

ChgMarkupKey	Guid Default(newid())	Primary Key:1
Project	Char(16)	In Index AK_Markup (Unique):1
ProjEntity	Char(32)	In Index AK_Markup (Unique):2
AccountCategory	Char(16)	In Index AK_Markup (Unique):3
MarkupPct	Numeric(7,3) Default(0)	

Fields: 5

SPM

xsfCodeList

Coded Choices

Lists of choices for drop downs

CodeValueKey	Guid Default(newid())	Primary Key:1
SetName	Varchar(16)	In Index AK_CodeList (Unique):1
Code	Varchar(16)	In Index AK_CodeList (Unique):2
Descript	Nvarchar(50)	
Active	Bit(1) Default((1))	
OnAdd	Bit(1) Default((1))	
UpdateTS	Timestamp(8)	

Fields: 7

SPM

xsfCodeListHistory

History of Codes

Each row preserves the value of a customization setting at a point in time

CfgHistoryKey	Guid	Primary Key:1 References xsfCustomizationHistory.CfgHistoryKey
CodeValueKey	Guid	Primary Key:2
SetName	Varchar(16)	
Code	Varchar(16)	
Descript	Nvarchar(50)	
Active	Bit(1)	
OnAdd	Bit(1)	
UpdateTS	Timestamp(8)	

Fields: 8

SPM

xsfCodeSet

Code Sets

Each row defines a set of codes and descriptions

CodeSetKey	Guid Default(newid())	Primary Key:1
SetName	Varchar(16)	In Index IX_xsfCodeSet (Unique):1
SetType	Varchar(24)	
ShowName	Varchar(24) NULL	
CodeFlagLabel	Varchar(24) NULL	
AllowEdit	Bit(1) Default(1)	
AllowAdd	Bit(1) Default(1)	
AllowNextSet	Bit(1) Default(0)	
CodeSize	Smallint(5) Default(8)	Check ([CodeSize]>=(1) AND [CodeSize]<=(16))
UpdateTS	Timestamp(8)	

Fields: 10

SPM

xsfCodeSetHistory

History of Code Sets

Each row preserves the value of a customization setting at a point in time

Field Name	Field Type	Field Description
CfgHistoryKey	Guid	Primary Key:1 References xsfCustomizationHistory.CfgHistoryKey
CodeSetKey	Guid	Primary Key:2
SetName	Varchar(16)	
SetType	Varchar(24)	
ShowName	Varchar(24) NULL	
CodeFlagLabel	Varchar(24) NULL	
AllowEdit	Bit(1)	
AllowAdd	Bit(1)	
AllowNextSet	Bit(1)	
CodeSize	Smallint(5)	Check ([CodeSize]>=(1) AND [CodeSize]<=(12))
UpdateTS	Timestamp(8)	

Fields: 11

SPM

xsfComment

Comment

Topic content against xsfDocItem

Field Name	Field Type	Field Description
DocCommentKey	Guid Default(newid())	In Index IX_xsfDocContent (Unique):2
TopicKey	Guid	In Index IX_xsfDocContent (Unique):1
FromUser	Guid	Identifies users who added this content References xsfUser.UserKey
Note	Varchar(-1)	
Cost	Money(19,4) NULL	
Stage	Smallint(5) Default((0))	Initialized to stage when created
Created	Datetime(23,3) Default(getdate())	
UpdateTS	Timestamp(8) NULL	

Fields: 8

SPM

xsfCompanyCSIMap

Company CSI Map

Each row associates a company with a CSI

Field Name	Field Type	Field Description
CSIMapKey	Guid Default(newid())	Primary Key:1
ContactCompanyKey	Guid	In Index IX_xsfCompanyCSIMap (Unique):1
CSICode	Varchar(6)	In Index IX_xsfCompanyCSIMap (Unique):2 References xsfCSI.CSICode
Created	Datetime(23,3) Default(getdate())	
Active	Bit(1) Default((1))	
UpdateTS	Timestamp(8)	

Fields: 6

SPM

xsfCompliance

Vendor Subcontract Compliance Items

Each row details a requirement and records compliance data

ComplianceItemKey	Guid Default(newid())	Primary Key:1
DocMasterKey	Guid	In Index IX_xsfCompliance:1 References xsfDocHeader.DocMasterKey
ComplianceTypeKey	Guid	References xsfComplianceType.ComplianceTypeKey
LastReleasedBy	Guid NULL	Weak reference xsfUser; set by data layer each time a user changes the Released column value
NotificationDocKey	Guid NULL	
Description	Varchar(50)	Only editable if type has AllowDescription set true
Carrier	Varchar(50)	Informational
LastReason	Varchar(64) Default('not yet evalua	
Recurs	Char(2) Default('NA')	
PayControl	Char(2) Default('A')	When Block, this item is manually out of compliance (unless also Released)
CertificateReqd	Bit(1) Default((0))	No longer used
Complied	Bit(1) Default((0))	OUTPUT of compliance engine. When true, this item was deemed in compliance at last evaluation Use by Compliance exception reports
Alerts	Bit(1) Default((1))	
Active	Bit(1) Default((1))	
LeadDays	Smallint(5) Default((0))	
Amount	Money(19,4) NULL	Informational
Effective	Datetime(23,3) NULL	Out of compliance when this date is compared to the Subcontract Current Start Date
Expiration	Datetime(23,3) NULL	Out of compliance when this date is compared to the Subcontract Current Finish Date
RequiredBy	Datetime(23,3) NULL	Only editable if type has AllowProof set true. When NULL, defaults to the parent document due date
Received	Datetime(23,3) NULL	Only editable if type has AllowProof set true
Released	Datetime(23,3) NULL	When this field is set, the item is in compliance. Period!
LastAlertWas	Datetime(23,3) NULL	Same as xsfDocAlert
NextAlertAfter	Datetime(23,3) Default(getdate())	Same as xsfDocAlert
UpdateTS	Timestamp(8) NULL	

Fields: 24

SPM

xsfComplianceType

Compliance Type

Each row defines a compliance item

Field Name	Field Type	Field Description
ComplianceTypeKey	Guid Default(newid())	Primary Key:1
ComplianceName	Varchar(50)	In Index AK_xsfComplianceType (Unique):1
Recurs	Char(2) Default('NA')	Code List "Recur"
LeadDays	Smallint(5) Default((0))	
PayPercent	Smallint(5) NULL	Check ([PayPercent]>=(0) AND [PayPercent]<=(100))
WorkflowScript	Varchar(-1) NULL	
AutoControl	Bit(1) Default((1))	When true, this compliance item is dynamically evaluated by the system
PayControl	Bit(1) Default((0))	Compliance Items will default to AUTO unless this is T and AutoControl is F, which then uses WARN as the default
Alert	Bit(1) Default((1))	When true, this compliance item can generate alerts
AllowDescription	Bit(1) Default((1))	When true, the description field is editable
AllowCarrier	Bit(1) Default((1))	
AllowProof	Bit(1) Default((1))	When true, the RequiredBy and Received compliance fields are editable
AllowAmount	Bit(1) Default((1))	
AllowEffective	Bit(1) Default((0))	
AllowExpiration	Bit(1) Default((1))	
AllowLeadDays	Bit(1) Default((1))	
AllowRecurs	Bit(1) Default((0))	
AllowMultiple	Bit(1) Default((1))	
CheckAmount	Bit(1) Default((0))	When true, this compliance item amount must be greater than the subcontract amount; requires AllowAmount and AutoControl
Active	Bit(1) Default((1))	
UpdateTS	Timestamp(8) NULL	

Fields: 21

SPM

xsfComplianceTypeMap

Maps Compliance Type to Vendor and Commitments

Each row associates a compliance type with a vendor or commitment document and possible subtype

Field Name	Field Type	Field Description
CompTypeMapKey	Guid Default(newid())	Primary Key:1
ComplianceTypeKey	Guid	In Index AK_xsfComplianceTypeMap (Unique) References xsfComplianceType.ComplianceTypeKey
DocTypeKey	Guid	In Index AK_xsfComplianceTypeMap (Unique) References xsfDocType.DocTypeKey
ForSubtype	Varchar(8) NULL	In Index AK_xsfComplianceTypeMap (Unique)
IsRequired	Bit(1) Default((0))	
Active	Bit(1) Default((1))	
UpdateTS	Timestamp(8)	

Fields: 7

SPM

xsfContactCompany

Contact Company

Each row defines a company for one or more customer or vendor contacts

ContactCompanyKey	Guid Default(newid())	Primary Key:1
MaintenanceDocKey	Guid NULL	Weak link to xsfDocHeader References xsfDocHeader.DocMasterKey
PrimaryContactKey	Guid NULL	Link to main xsfUser References xsfUser.UserKey
CompanyName	Varchar(60)	
UnionCode	Varchar(8) NULL	
ExternalType	Char(1) Default('0')	(C)ustomer, (V)endor or (O)ther In Index IX_xsfContactCompany:2
ExternalID	Char(16) NULL	Typically vendor or customer ID, often from external source In Index IX_xsfContactCompany:1
IsPreliminary	Bit(1) Default((0))	Future - this contact is being created (not yet in external system)
IsQualified	Bit(1) Default((0))	Informational - meant to imply the contact has passed whatever checks are run
ProjectPurchasing	Bit(1) Default((0))	Designates vendors that should be When true, vendor will be included in commitment lookups
Created	Datetime(23,3) Default(getdate())	
UpdateTS	Timestamp(8)	

Fields: 12

SPM

xsfContainerPermitCache

Preresolved Container Permissions by User

Each row describes a users access to a container

UserKey	Guid	In Index AK_xsfContainerPermitCache (Uniq
ContainerKey	Guid	In Index AK_xsfContainerPermitCache (Uniq
Project	Char(16) NULL	In Index AK_xsfContainerPermitCache (Uniq
DocType	Guid NULL	In Index AK_xsfContainerPermitCache (Uniq
DocReference	Guid NULL	In Index AK_xsfContainerPermitCache (Uniq
ListOK	Bit(1)	
ReadOK	Bit(1)	
InsOK	Bit(1)	

Fields: 8

SPM

xsfContentHistory

Detailed History of Table Content

Each row describes the data in a table at a point in time

ContentAsOf	Datetime(23,3)	Primary Key:1 References xsfContentHistoryList.ContentAsOf
ObjectID	Int(10)	Primary Key:2
Rows	Int(10)	
BCS	Int(10)	
MaxTS	Bigint(19)	

Fields: 5

SPM

xsfContentHistoryList

Index of Content History Snapshots

Each row describes when a content snapshot was created

Field Name	Field Type	Field Properties
ContentAsOf	Datetime(23,3)	Primary Key:1
Comment	Varchar(128)	
UpdateTS	Timestamp(8)	

Fields: 3

SPM

xsfCSI

CSI Definition

Each row defines a CSI

Field Name	Field Type	Field Properties
CSIKey	Guid Default(newid())	Primary Key:1
CSICode	Varchar(6)	In Index AK_CSI (Unique):1
CSIDescription	Varchar(64)	
ExtendedDescription	Varchar(4096) NULL	
Created	Datetime(23,3) Default(getdate())	
AutoAdd	Bit(1) Default((0))	
Active	Bit(1) Default((1))	
UpdateTS	Timestamp(8)	

Fields: 8

SPM

xsfCustomizationHistory

Customization History Snapshot Header

Each row identifies a snapshot of customization settings at a point in time

Field Name	Field Type	Field Properties
CfgHistoryKey	Guid	Primary Key:1
WhenTaken	Datetime(23,3) Default(getdate())	
sfVersion	Varchar(32)	
Note	Varchar(99)	
TakenBy	Guid	
UnchangedAsOf	Datetime(23,3)	
LastCfgChangeWas	Bigint(19) Default((0))	
UpdateTS	Timestamp(8)	

Fields: 8

SPM

xsfDashboardMenu

Spitfire Dashboard Menu

Each row identifies a choice within the Spitfire Menu

MenuItemKey	Guid Default(newid())	Primary Key:1
DocTypeKey	Guid NULL	When set, the corresponding DocType must be active
ContainerKey	Guid NULL	Default container is the Project Management menu In Index AK_xsfDashboardMenu (Unique):1
MenuPath	Varchar(64) Default('\')	Path within container In Index AK_xsfDashboardMenu (Unique):2
MenuItemID	Int(10)	In Index AK_xsfDashboardMenu (Unique):5
MenuSeq	Int(10) Default((100))	Controls order of choices within a folder In Index AK_xsfDashboardMenu (Unique):3
ItemText	Varchar(64)	The label on the menu In Index AK_xsfDashboardMenu (Unique):4
TipText	Varchar(64) NULL	Tool tip when the menu item is pointed to
ActionText	Varchar(128) NULL	The command that is run
UCModule	Char(4) NULL	When null, access is not permission based
UCFunction	Varchar(50) NULL	The function within the specified module
RequiredPermit	Int(10) Default((1))	Bit flag of permission required (1=Read;2=Insert, etc)
Active	Bit(1) Default((1))	When false, this row is ignored
SiteActive	Bit(1) Default((1))	Allows the site to disable the row
UpdateTS	Timestamp(8) NULL	

Fields: 15

SPM

xsfDivision

Company Division List

Each row defines a company/division

DivisionKey	Guid Default(newid())	Primary Key:1
DivisionID	Char(10)	In Index AK_xsfCompany (Unique):1
DivisionName	Varchar(60)	
Addr1	Varchar(60) Default("")	
Addr2	Varchar(60) Default("")	
City	Varchar(30) Default("")	
State	Char(2) Default("")	
Zip	Char(10) Default("")	
Country	Char(3) Default("")	
Phone	Varchar(20) Default("")	
Fax	Varchar(20) Default("")	
Website	Varchar(196) NULL	
IsPrimary	Bit(1) Default(0)	
Active	Bit(1) Default(1)	
UpdateTS	Timestamp(8)	

Fields: 15

SPM

xsfDocAddr

Address

To/From Address for Document

DocAddrKey	Guid Default(newid())	Primary Key:1
DocMasterKey	Guid	In Index IX_xsfDocAddr (Unique):1 References xsfDocHeader.DocMasterKey
AddrType	Char(1)	To or From In Index IX_xsfDocAddr (Unique):2
SourceType	Char(1) Default('U')	User/Contact(Customer, Vendor), or Manual Check (charindex([SourceType], 'UM') > 0)
UserKey	Guid NULL	Identifies user/contact
Person	Varchar(60) Default("")	
Company	Varchar(60) Default("")	
Addr1	Varchar(60) Default("")	
Addr2	Varchar(60) Default("")	
City	Varchar(30) Default("")	
State	Char(2) Default("")	
Zip	Char(10) Default("")	
Phone	Varchar(30) NULL Default("")	
Fax	Varchar(30) Default("")	
Email	Varchar(80) Default("")	
UpdateTS	Timestamp(8) NULL	

Fields: 16

SPM

xsfDocAlert

Document Alert

Each row holds status for a particular document alert

DocAlertKey	Guid Default(newid())	Primary Key:1
DocMasterKey	Guid	In Index IX_xsfDocAlert:1 References xsfDocHeader.DocMasterKey
AlertTypeKey	Guid	References xsfAlertType.AlertTypeKey
AlertToRole	Guid NULL	Limits this alert to subscriptions matching this role
AlertName	Varchar(50)	Defaults from Alert Type definition In Index IX_xsfDocAlert:2
Recurs	Char(10) Default('NA')	Defaults from Alert Type definition
LeadTime	Smallint(5) Default(0)	in Days, Defaults from Alert Type definition
AlertDate	Datetime(23,3) NULL	base date for this alert
LastAlertWas	Datetime(23,3) NULL	set when alerts are generated
NextAlertAfter	Datetime(23,3) Default(getdate())	For recurring alerts this value is set to indicate the next point in time that alerts will be considered In Index IX_xsfDocAlert_Soon:2
AsSubscribed	Bit(1) Default(0)	When TRUE, this row was created by a subscription
IncludeRoutees	Bit(1) Default(1)	When TRUE, this row generates alerts to flagged doc route parties
Active	Bit(1) Default(1)	When TRUE, this row can generate alerts.
UpdateTS	Timestamp(8) NULL	

Fields: 14

SPM

xsfDocDates

Document Dates

Each row stores the values for a specific document and a specific date type

DocDateRowKey	Guid Default(newid())	Primary Key:1
DocMasterKey	Guid	In Index IX_xsfDocDates:1 References xsfDocHeader.DocMasterKey
DocDateTypeKey	Guid	References xsfDocDateType.DocDateTypeKey
LeadTime	Smallint(5) Default((0))	
SchedStart	Datetime(23,3) NULL	
SchedFinish	Datetime(23,3) NULL	
ActStart	Datetime(23,3) NULL	
ActFinish	Datetime(23,3) NULL	
Note	Varchar(-1) NULL	
UpdateTS	Timestamp(8) NULL	

Fields: 10

SPM

xsfDocDateType

Date Types

Enumerates dates/events that can be tracked

DocDateTypeKey	Guid Default(newid())	Primary Key:1
DocTypeKey	Guid Default('00000000-0000-	When not null, this type Applies only to the specified document type In Index AK_xsfDocDateType (Unique):1
DocDateName	Varchar(50)	In Index AK_xsfDocDateType (Unique):2
Sequence	Smallint(5)	
IncludeStart	Bit(1) Default((1))	
IncludeFinish	Bit(1) Default((1))	
IsRequired	Bit(1) Default((0))	When true, this date type is automatically added to any document to which it applies
Active	Bit(1) Default((1))	
Alert	Bit(1) Default((0))	
UpdateTS	Timestamp(8) NULL	

Fields: 10

SPM

xsfDocHeader

Document Header

The header of a routed document

DocMasterKey	Guid Default(newid())	Primary Key:1
DocTypeKey	Guid	In Index IX_DocList:2 References xsfDocType.DocTypeKey
DocReference	Guid NULL	In Index IX_DocOCD:0 References xsfDocReference.DocReferenceKey
DocDate	Datetime(23,3) Default(getdate())	Updatable; see also xsfDocRevision.Created In Index IX_DocOCD:1
DocNo	Char(16) NULL	References base document, based upon DocType In Index IX_DocList:3
SourceDocNo	Varchar(30) NULL	OwnChgOrd when combined with PCO Line Item # In Index IX_DocSourceNo:1 (limit (char(16) pjbillcn.change_order_num)
ExternalDocNo	Varchar(30) NULL	
DocBatchNo	Varchar(16) NULL	With DocNo, references base document Added for AP Vouchers

Title	Field Type	Short description
Source	Varchar(60) NULL	In Index IX_DocOCD:0
Priority	Varchar(8) NULL	via xsfDocTypeSubcodes - user-defined (Source)
NumToSend	Smallint(5) Default((5))	1 is highest, increasing value decreases priority
NumToForward	Smallint(5) NULL	
Probability	Smallint(5) NULL Default((0))	Check ([Probability]>=(-900) AND [Probability]<=(999))
AutoTitled	Bit(1) Default((1))	When TRUE, Spitfire can replace the title automatically
Confidential	Bit(1) Default((0))	When false, document can be forwarded
DocEdit	Bit(1) Default((0))	When TRUE, those with permission can edit the document Only originator can edit this value
Final	Bit(1) Default((0))	
DocFlag	Bit(1) Default((0))	Used on Vendor Maintenance documents
Due	Datetime(23,3) NULL	Loosly coordinated with last routing due date In Index IX_DocOCD:0
Closed	Datetime(23,3) NULL	When NULL, this document is open; date is set when document status is set to a status enumerated in the DocStatusIsClosed rule In Index IX_DocByType:0
Signoff	Datetime(23,3) NULL	Own Signature Date or Manager's Approved Date
SourceDate	Datetime(23,3) NULL	For example, invoice date of pay request
LinkedDocKey	Guid NULL	Weak link to another Spitfire Document.
UniReferenceKey	Guid NULL	In Index IX_DocOCD:0 References xsfReference.UniReferenceKey
ResponsibleParty	Guid NULL	In Index IX_DocOCD:0 References xsfUser.UserKey
SourceContact	Guid NULL	Validated in Contact Table; indicates Requestor for PCO, vendor for AP Voucher, etc In Index IX_DocByType:0
OwnerApprover	Guid NULL	Validated in Contact Table
LastStatusBy	Guid NULL	References xsfUser; Set by data layer each time a user changes the status column
LastRouteKey	Guid NULL	Predefined route last resolved
Status	Char(2) Default("")	via xsfDocTypeSubcodes In Index IX_DocSourceContact:0 Agenda/Bid/Etc
Subtype	Varchar(8) NULL	xsfDocTypeSubcodes - user-defined (Category) In Index IX_DocByType:0
ContractType	Varchar(8) NULL	FP/TM etc as site defined in xsfDocTypeSubcodes
Reason	Varchar(8) NULL	xsfDocTypeSubcodes - user-defined; Formerly RejectCode
Area	Int(10) NULL	
Duration	Int(10) Default((0))	
UpdateMask	Int(10) NULL	Bit Mask:Orig/Bid(1); EAC(2); FAC(4)
RouteFlags	Int(10) Default((0))	0=off;1=retry;2=refreshing
Location	Varchar(130) Default("")	
PayItemNumber	Varchar(30) NULL	External payment authorization number
DivisionID	Char(10) NULL Default("")	References Solomon Company
Project	Char(16) Default("")	References PJProject In Index IX_DocList:1
ProjEntity	Char(32) NULL	Used for either the cost or revenue (eg PCO) code In Index IX_DocOCD:0
BudgetRevFlag	Char(4) NULL	Was weak link to DSL pjrevhdr.revid

SOVItemNumber	Char(6) NULL	Dynamics: weak link to pjbillcn.itemnbr
Section	Char(16) NULL	freeform
SubContract	Char(16) NULL	References PJSubCon In Index IX_DocOCD:0
PayControl	Char(2) NULL	Block for hard block; Warn for alerts only; Auto for Compliance driven blocking In Index IX_DocByType:0
UpdateTS	Timestamp(8) NULL	Internal In Index IX_DocByType:0

Fields: 49

SPM

xsfdocItem

Document Item List

Topics associated with a routed document

DocItemKey	Guid Default(newid())	Primary Key:1
ResponsibleParty	Guid NULL	In Index IX_xsfdocItem_Responsible:1
LinkedDocKey	Guid NULL	Weak link to another Spitfire Document In Index IX_xsfdocItem_LinkedDoc:1
LinkedItemKey	Guid NULL	Weak Link to another item Use by CORs to point to project contract line
UniReferenceKey	Guid NULL	References xsfReference.UniReferenceKey
LastStatusBy	Guid NULL	Set by the data layer each time ItemStatus changes
Description	Varchar(-1)	
DrawingNumber	Varchar(20) NULL	
RevisionNumber	Varchar(16) NULL	
Paragraph	Varchar(16) NULL	
Specification	Varchar(16) NULL	
ItemStatus	Varchar(8) NULL	Validated against xsfDocTypeSubcodes. Checked against rule DocItemStatusIsClosed.
ItemSource	Varchar(8) NULL	
ItemType	Varchar(8) NULL	
ItemSubtype	Varchar(8) NULL	
Drawings	Varchar(8) NULL	
Samples	Varchar(8) NULL	
ProductData	Varchar(8) NULL	
TestReport	Varchar(8) NULL	
MixDesign	Varchar(8) NULL	
Schedule	Varchar(8) NULL	
FieldMockup	Varchar(8) NULL	
Guarantee	Varchar(8) NULL	
Certification	Varchar(8) NULL	
Evaluation	Varchar(8) NULL	
Shop	Varchar(8) NULL	
SourceItemNumber	Varchar(30) NULL	External reference number of this item.
SourceInitialNumber	Varchar(30) NULL	
ArchitectInitialNumber	Varchar(30) NULL	
ArchitectItemNumber	Varchar(30) NULL	
SOVLineNumber	Varchar(32) NULL	weak link to SOV Line
Manufacturer	Varchar(40) NULL	
Supplier	Varchar(40) NULL	
RevenueEntity	Char(32) NULL	Cost Code to which revenue is posted. Used by billable CORs

Stage	Smallint(5) Default((0))	Initialized to current stage when item added Not currently used for any purpose
CWRetention	Money(19,4) NULL	Check ([CWRetention]>=(0) AND [CWRetention]<=(100))
SMRetentio	Money(19,4) NULL	Check ([SMRetentio]>=(0) AND [SMRetentio]<=(100))
OriginalEstimate	Money(19,4) NULL	
OriginalQuote	Money(19,4) NULL	
ItemQuantity	Numeric(16,3) NULL	
Billable	Bit(1) Default((0))	
Started	Datetime(23,3) NULL	
Submitted	Datetime(23,3) NULL Default(getdate())	
Requested	Datetime(23,3) NULL	
Received	Datetime(23,3) NULL	
Reviewed	Datetime(23,3) NULL	Set by the data layer each time ItemStatus changes
Due	Datetime(23,3) NULL	
Completed	Datetime(23,3) NULL	Not tied to status at all
UpdateTS	Timestamp(8) NULL	

Fields: 49

SPM

xsfDocItemTask

Revenue and Expense Details for an Item

Each row identifies the tasks and account categories that are effected by an item

ItemTaskKey	Guid Default(newid())	When ItemTaskKey = DocItemKey, this is the primary (or single) extension to the corresponding item Primary Key:1
DocItemKey	Guid	In Index IX_xsfDocItemTask:1 References xsfDocItem.DocItemKey
LinkedLineKey	Guid NULL	
LinkedRFQKey	Guid NULL	Weak link to RFQ
LinkedCCCKey	Guid NULL	Links this line to its commitment cost changes (a CCO or Commitment document) In Index IX_xsfDocItemTask_LinkedCCC:1
ProjEntity	Char(32) NULL	TaskID Flexkey In Index IX_xsfDocItemTask:2
AccountCategory	Char(16) NULL	pjacct.acct In Index IX_xsfDocItemTask:3
Subcontract	Char(16) NULL	SubcontractID Flexkey In Index IX_xsfDocItemTask:4
SubChangeOrder	Char(10) NULL	Subcontract Change Order system assigned - Unique by Subcontract
CostType	Char(2) Default('SP')	Via xsfCodeList, set TaskCostType - Self Perform, SCO, etc
GLAcct	Char(10) NULL	Weak link to Solomon GL Account
GLSub	Char(24) NULL	Weak link to Solomon GL Subaccount
LaborClass	Char(4) NULL	Lookup on Solomon labor class
UOM	Char(4) NULL	from Code List, set UOM
RetentionMethod	Char(2) NULL	None or % of Total(TL)
Vendor	Char(16) NULL	Weak link to Solomon Vendor; Primarily used for splitting SPR payments amounts
ProjectReference	Char(16) NULL	Used for documents that distribute across projects In Index IX_xsfDocItemTask_ProjectCharge:
ItemPercent	Smallint(5) NULL Default((0))	Used for Retention Percent if RetentionMethod is TL Check ([ItemPercent]>=(0) AND [ItemPercent]<=(100))

Quantity	Numeric(16,3) NULL	pjcosubd.change_units
RevenueAmount	Money(19,4) NULL	Calculated, but editable
Rate	Money(19,4) NULL	
ExpenseAmount	Money(19,4) NULL	defaults to Amount, but is editable In Index IX_xsfDocItemTask_ProjectCharge:
StoredAmount	Money(19,4) NULL	Material part of RevenueAmount
WorkAmount	Money(19,4) NULL	Labor part of RevenueAmount
RetentionAmount	Money(19,4) NULL	Amount of total that goes to retention; Note that only the primary vendor on a subcontract has retention
SMRetentionAmount	Money(19,4) NULL	
SOVWork	Money(19,4) NULL	62 SOVMaterials 54 Total labor value on SOV; SOVMaterials == RevenueAmount on SOV
SOVMaterials	Money(19,4) NULL	Total material value on SOV
MarkupRate	Money(19,4) NULL	
csAmount	Money(19,4) NULL	for custom use
MarkupControl	Bit(1) Default((0))	When true, auto markup calculation for RevenueAmount is suppressed Originally intended for PCO auto split of expense and revenue onto two AIA lines
csCheck	Bit(1) Default((0))	for custom use
Note	Varchar(-1) NULL	
csString016	Varchar(16) NULL	for custom use
csString030	Varchar(30) NULL	for custom use
csString060	Varchar(60) NULL	for custom use
csDate	Datetime(23,3) NULL	for custom use
Created	Datetime(23,3) Default(getdate())	
UpdateTS	Timestamp(8) NULL	

Fields: 39

SPM

xsfDocPosting

Document Posting

Each row defines when a document posted a type of revision

DocPostingKey	Guid Default(newid())	Primary Key:1
DocMasterKey	Guid	In Index AK_xsfDocPosting (Unique):1 References xsfDocHeader.DocMasterKey
PostingType	Char(2)	In Index AK_xsfDocPosting (Unique):2
UserKey	Guid	References xsfUser.UserKey
Posted	Datetime(23,3) NULL	
UpdateTS	Timestamp(8)	

Fields: 6

SPM

xsfDocReference

Document Catagorical Reference

The reference catagories with which documents can be associated

Field Name	Field Type	Index
DocReferenceKey	Guid Default(newid())	In Index IX_xsfDocReference:1
DocTypeKey	Guid NULL	The document type with which this Reference is associated
Description	Varchar(50)	
Future	Char(2) NULL	
Rollup	Char(10) NULL	
Active	Bit(1) Default(1)	
UpdateTS	Timestamp(8) NULL	

Fields: 7

SPM

xsfDocRevision**Document Revision**

Each row defines a document revision

Field Name	Field Type	Description
DocRevKey	Guid Default(newid())	In Index AK_DocRevision (Unique):3
DocMasterKey	Guid	In Index AK_DocRevision (Unique):1
RevNo	Smallint(5) Default((0))	Revision Number - System Generated In Index AK_DocRevision (Unique):2
Description	Varchar(50)	Revision Description
DaysRequested	Smallint(5) NULL Default((0))	Scheduled Impact Requested in Days
DaysApproved	Smallint(5) NULL Default((0))	Scheduled Impact Approved
CWRetention	Money(19,4) NULL	Check ([CWRetention]>=(0) AND [CWRetention]<=(100))
SMRetention	Money(19,4) NULL	Check ([SMRetention]>=(0) AND [SMRetention]<=(100))
CostImpact	Money(19,4) NULL	
RangeFrom	Money(19,4) NULL	
RangeThru	Money(19,4) NULL	
Bond	Money(19,4) NULL	
BondRate	Decimal(9,6) NULL	
TaxRate	Decimal(9,6) NULL	
Segment	Varchar(8) NULL	
Subsegment	Varchar(8) NULL	
DraftNumber	Char(10) NULL	
ArchProject	Char(16) NULL	Architect's Project (External Reference)
TaxID	Char(10) NULL	
TaxHandling	Varchar(8) NULL	Codes assigned by Spitfire with special handling for Tax Included, Tax Added, No Tax
InPeriod	Char(6) NULL	YYYYMM
Notes	Varchar(-1) NULL	Free format notes; included in full text searches
NoteA	Varchar(-1) NULL	
NoteB	Varchar(-1) NULL	
NoteEML	Varchar(-1) NULL	
EmailSubject	Varchar(80) NULL	
csAmount	Money(19,4) NULL	for custom use
csDate	Datetime(23,3) NULL	for custom use
csString016	Varchar(16) NULL	for custom use
csString030	Varchar(30) NULL	for custom use
csString060	Varchar(60) NULL	for custom use
csCheck	Bit(1) Default((0))	
sfVersion	Smallmoney(10,4) NULL Default((4.3))	Version of SFPMS when revision created (4.1 and later)
Created	Datetime(23,3) Default(getdate())	System Timestamp
FromUser	Guid	Indicates User that created this revision
UpdateTS	Timestamp(8)	Internal

Fields: 36

SPM

xsfDocRevItem

Document Revision Items

Each row Connects Document Revisions with Items

DocRevItemKey	Guid Default(newid())	When DocRevItemKey = DocItemKey, this is the doc revision that created the item Primary Key:1
DocRevKey	Guid	Links to document revision In Index IX_xsfDocRevItem:1 References xsfDocRevision.DocRevKey
DocItemKey	Guid	Links to item In Index IX_xsfDocItemOn:1 References xsfDocItem.DocItemKey
ContainerKey	Guid NULL	Weak link to xsfItemContainer; Indicates the folder which contains this item
FromUser	Guid	Indicates User that added this item
ItemNumber	Varchar(32) NULL	Read only in UI; Automatically populated, w/docno prefix. Note that items might have been copied from prior doc In Index IX_xsfDocRevItem:2
ItemSeq	Int(10) Default((0))	
Created	Datetime(23,3) Default(getdate())	
UpdateTS	Timestamp(8)	

Fields: 9

SPM

xsfDocSession

User Document Sessions

Each row represents a user opening a document

DocSessionKey	Guid Default(newid())	Primary Key:1
DocMasterKey	Guid	In Index AK_xsfDocSession (Unique):1 References xsfDocHeader.DocMasterKey
UserSessionKey	Guid	In Index AK_xsfDocSession (Unique):3 References xsfUserSession.UserSessionKey
SessionStart	Datetime(23,3) Default(getdate())	In Index AK_xsfDocSession (Unique):2
SessionEnd	Datetime(23,3) NULL	
LastSave	Datetime(23,3) NULL	
ApproxDeltas	Int(10) Default((0))	
ApproxSaveTx	Int(10) Default((0))	
IsExclusive	Bit(1) Default((0))	
WantsExclusive	Bit(1) Default((0))	
Active	Bit(1) Default((1))	
UpdateTS	Timestamp(8)	

Fields: 12

SPM

xsfDocSingleUser

Document Exclusive User Reservation

Each row defines when a document is help for exclusive update access by a user

DocMasterKey	Guid	Primary Key:1 References xsfDocHeader.DocMasterKey
UserKey	Guid	In Index IX_xsfDocSingleUser_User:1 References xsfUser.UserKey
UserSessionKey	Guid NULL	In Index IX_xsfDocSingleUser_UserSession: References xsfUserSession.UserSessionKey
DocSessionKey	Guid NULL	In Index IX_xsfDocSingleUser_DocSession: References xsfDocSession.DocSessionKey
IsExclusive	Bit(1) Default((1))	In Index IX_xsfDocSingleUser_Expiration:1
Effective	Datetime(23,3) Default(getdate())	
Expires	Datetime(23,3)	In Index IX_xsfDocSingleUser_Expiration:2
UpdateTS	Timestamp(8)	

Fields: 8

SPM

xsfDocTemplate

Word Document Template

Each row defines a template that can be used to create the word document associated with a routed document

TemplateKey	Guid Default(newid())	Primary Key:1
DocTypeKey	Guid	The document type with which this template is associated In Index AK_xsfDocTemplateByType (Unique) References xsfDocType.DocTypeKey
FromUser	Guid	References xsfUser.UserKey
TemplateName	Varchar(80)	In Index AK_xsfDocTemplateByType (Unique)
Description	Varchar(200) NULL	
DivisionID	Char(10) Default("")	When set, limits the template to the specified company
CustomerID	Char(16) NULL	
TemplateType	Char(2) Default('B')	
DefaultInclude	Char(1) NULL Default('0')	
Subtype	Varchar(8) NULL	
ProjectSubtype	Varchar(8) NULL	
SourceID	Varchar(16) NULL	
DocReference	Guid NULL	
binType	Varchar(8) Default('doc')	
binData	Varbinary(-1) NULL	Binary contents of Microsoft Word document
Created	Datetime(23,3) Default(getdate())	
Updated	Datetime(23,3) NULL	
HasBookmarks	Bit(1) NULL Default((0))	
Active	Bit(1) Default((1))	
UpdateTS	Timestamp(8)	

Fields: 20

SPM

xsfDocType Routable Document Types

DocTypeKey	Guid Default(newid())	Primary Key:1
DocType	Varchar(50)	Descriptive Type Name In Index AK_Table1 (Unique):1
SiteName	Varchar(50) NULL	Site specific name formerly ShortName
Product	Char(1) Default('S')	Spitfire; MBS or Both
OnDashboard	Char(2) Default('')	
OpenVia	Varchar(128) NULL	indicates external resource used for document, including parameters
CheckCompliance	Bit(1) Default((0))	When TRUE, reevaluate compliance each time the document is opened or saved
ProjectDashboard	Bit(1) Default((0))	When TRUE, shows in Document Summary of Project Dashboard p_getProjectDocSummary
NewFromDashboard	Bit(1) Default((1))	
PlanRoom	Bit(1) Default((0))	When TRUE, doc type can appear in plan room
Active	Bit(1) Default((1))	
SiteActive	Bit(1) Default((1))	
ParentType	Guid NULL	Link to another DocType Record
UpdateTS	Timestamp(8) NULL	

Fields: 14

SPM

xsfDocTypeSubcodes Type Dependant Codes
Code and Descriptions that depend on DocType

DocSubtypeKey	Guid Default(newid())	Primary Key:1
DocTypeKey	Guid	In Index AK_xsfDocSubtype (Unique):1 References xsfDocType.DocTypeKey
SetName	Varchar(16) Default('Subtype')	Segregates codes into sets In Index AK_xsfDocSubtype (Unique):2
Code	Varchar(8)	In Index AK_xsfDocSubtype (Unique):3
Description	Varchar(62)	
NextSet	Varchar(16) NULL	Specifies another set of codes Currently used only by AttrType
CodeFlag	Bit(1) Default(0)	Relevance varies by SetName
Active	Bit(1) Default(1)	
UpdateTS	Timestamp(8)	

Fields: 9

SPM

xsfDocTypeSubcodesHistory History of Doc Type Specific Codes

Each row preserves the value of a customization setting at a point in time

CfgHistoryKey	Guid	Primary Key:1 References xsfCustomizationHistory.CfgHistoryKey
DocSubtypeKey	Guid	Primary Key:2
DocTypeKey	Guid	References xsfDocType.DocTypeKey
SetName	Varchar(16)	
Code	Varchar(8)	
Description	Varchar(62)	
NextSet	Varchar(16) NULL	
CodeFlag	Bit(1)	
Active	Bit(1)	
UpdateTS	Timestamp(8)	

Fields: 10

SPM

xsfDocWorkflow Document Workflow Events

Each row defines a triggering event for which the indicated workflow script will be run

DocWorkflowKey	Guid Default(newid())	Primary Key:1
DocTypeKey	Guid	In Index AK_xsfDocWorkflow (Unique):1
TriggerWhen	Smallint(5) Default((0))	In Index AK_xsfDocWorkflow (Unique):2
Sequence	Smallint(5) Default((0))	In Index AK_xsfDocWorkflow (Unique):3
TriggerWhere	Varchar(200) Default('%')	
WorkflowScriptKey	Guid	References xsfWorkflowLib.WorkflowScriptKey
StopCascade	Bit(1) Default((0))	
IsDistributed	Bit(1) Default((0))	
Active	Bit(1) Default((1))	
UpdateTS	Timestamp(8)	

Fields: 10

SPM

xsfDocWriteTx Document Save Transaction Header

Each row defines a save transaction

DocWriteKey	Guid Default(newid())	Primary Key:1
DocMasterKey	Guid	In Index AK_xsfDocWriteTx (Unique):1 References xsfDocHeader.DocMasterKey
ChangeWhen	Datetime(23,3)	In Index AK_xsfDocWriteTx (Unique):2
HSSeq	Smallint(5)	In Index AK_xsfDocWriteTxHs (Unique):2
HSDepth	Smallint(5)	
ApproxDeltas	Int(10) Default((0))	
IISMS	Int(10) NULL	
TotalMS	Int(10) NULL	
KindFlags	Int(10) NULL	
UpdateTS	Timestamp(8)	

Fields: 10

SPM

xsfDocWriteTxFact

Document Save Facts

Each row defines a fact about a save transaction

DocWriteFactKey	Guid Default(newid())	Primary Key:1
DocWriteKey	Guid	
Sequence	Smallint(5)	
Depth	Tinyint(3)	
FactFlags	Tinyint(3)	
Info	Varchar(128)	
UpdateTS	Timestamp(8)	

Fields: 7

SPM

xsfEventAgent

Event Notification Consumer Agents

Each row describes an agent that processes event notifications generated by event subscriptions

EventAgentKey	Guid Default(newid())	Primary Key:1
AgentName	Varchar(32)	informational name In Index AK_xsfEventAgent (Unique):1
AgentType	Char(2) Default('EI')	EI-Spitfire.EventNotificationInterface at AgentURI; SF-Internal
AgentURI	Varchar(300)	eg: tcp://SVRNAME:PORT/ISpitfireEventInterface
UserSelectable	Bit(1) Default(0)	When true, users can create subscriptions that are processed by this agent
Active	Bit(1) Default(1)	When false, any subscriptions that use this agent are disabled
UpdateTS	Timestamp(8) NULL	

Fields: 7

SPM

xsfEventSubscription

Event Subscriptions

Each row describes a subscription to event notifications.

Field Name	Field Type	Description
SubscriptionKey	Guid Default(newid())	Primary Key:1
EventAgentKey	Guid	References xsfEventAgent.EventAgentKey
UserKey	Guid NULL	Either UserKey or UCRoleKey, but not both References xsfUser.UserKey
UCRoleKey	Guid NULL	For Spitfire agents only: EI agents do not support role based subscriptions References xsfUCRole.UCRoleKey
DocTypeKey	Guid NULL	For subscriptions to all files and documents that match the specified doc type
FileKey	Guid NULL	For subscription to a specific file
ContainerKey	Guid NULL	For subscription to a specific folder, can yield both file and folder events
DocMasterKey	Guid NULL	For subscription to a specific document
FromUser	Guid NULL	For subscriptions to all events caused by the specified user
Project	Char(16) NULL	For subscriptions to all files and documents that match the specified project
FileType	Char(4) NULL	For subscriptions to all files that match the specified extension. Use * for all files.
Description	Varchar(200) NULL	Optional, free form description of this subscription
EventFlags	Int(10) Default(0)	Bit Coded, See Event Interface Enumeration
ItemTypes	Int(10) Default((-1))	Bit Coded, -1 for all; 1=File;2=Folder;8=Document
Active	Bit(1) NULL Default(1)	When false, subscription is suspended. When TRUE, agent must also be active for the subscription to be considered.
UpdateTS	Timestamp(8) NULL	

Fields: 16

SPM

xsfFile	Stored File	
	Binary documents controlled by document management	
DocKey	Guid Default(newid())	Primary Key:1
DocReference	Guid NULL	References xsfDocReference.DocReferenceKey
CatType	Guid NULL	Category (Scanned Invoice;Site Photo)
ContainerKey	Guid NULL	Indicates the "folder" where the file resides In Index AK_xsfFile:1
SourceContact	Guid NULL	Indicates the file source, leads to vendor/employee/customer In Index AK_xsfFile:3
AltFileContact	Guid NULL	Weak link to xsfUser; indicates the contact associated with this file
ByDocMasterKey	Guid NULL	weak link to Spitfire Document that generated (and owns) this file If the Spitfire Document is deleted, the corresponding files are removed from the catalog
FileName	Varchar(80) NULL	free form; Text Indexed In Index AK_xsfFile:4
keyword	Varchar(2000) NULL	Free form; text indexed
Other	Varchar(200) NULL	
SourceDocNo	Varchar(30) NULL	External reference number; text indexed
SourceBatchNo	Varchar(16) NULL	Optional; Text Indexed
ReferenceDate	Datetime(23,3) NULL	
FileType	Varchar(8)	TIF/DOC/JPG etc
Project	Char(16) NULL	Optional; References Solomon; text indexed In Index AK_xsfFile:2
DivisionID	Char(10) NULL	Company Division
GeoLat	Decimal(9,6) NULL	
GeoLng	Decimal(9,6) NULL	
sfGenerated	Bit(1) Default((0))	Internal document, output of a routed document
RefreshBookmarks	Bit(1) Default((1))	If sfGenerated and current document is ByDocMaster and this field is true, bookmarks are refreshed
RoutedContent	Bit(1) Default((0))	When true, this catalog entry is associated with route output and is hidden from normal catalog searches
UpdateTS	Timestamp(8) NULL	

Fields: 22

SPM

xsfFileAccess	File Access Log	
	Each row describes a user accessing a file version	
FileAccessKey	Guid Default(newid())	Primary Key:1
DocKey	Guid	In Index AK_xsfFileAccess_ByFile (Unique) References xsfFileVersionInfo.DocKey
RevID	Smallint(5)	In Index AK_xsfFileAccess_ByFile (Unique) References xsfFileVersionInfo.RevID
UserKey	Guid	In Index IX_xsfFileAccess_byUser:1 References xsfUser.UserKey
Reason	Varchar(50)	
Accessed	Datetime(23,3) Default(getdate())	In Index AK_xsfFileAccess_ByFile (Unique)
completed	Datetime(23,3) NULL	
UpdateTS	Timestamp(8) NULL	

Fields: 8

SPM

xsfFileAttach

Document Attachment List

Enumerates documents attached to a routed item

DocAttachKey	Guid Default(newid())	Primary Key:1
DocMasterKey	Guid	In Index IX_xsfDocAttach:1
DockKey	Guid NULL	In Index IX_xsfFileAttachFile:1 References xsfFile.DockKey
AttachedDocMaster	Guid NULL	Optional: references another routed document In Index IX_xsfFileAttachDoc:1 Attached documents are reciprocal, the reciprocal relation is accomplished via a UNION in the p_GetDocMaster stored procedure
LinkedItemKey	Guid NULL	In Index IX_xsfFileAttachedItem:1
Note	Varchar(-1) NULL	
FromUser	Guid	Indicates who attached this to the document References xsfUser.UserKey
Created	Datetime(23,3) Default(getdate())	
AttachedRevID	Smallint(5) Default((1))	Current Revision Number when attached This is used to filter attachments when looking at prior revisions
AttachSeq	Smallint(5) Default((100))	Controls order of attachments in merges and emails, etc
AccessLevel	Char(1) Default('V')	View or Update
MailRoute	Char(1) Default('0')	Indicates how this attachment is sent to non-web route parties, eg: 0=never;1=always;M=Assembled;P=PDF (see code set!)
UpdateTS	Timestamp(8) NULL	

Fields: 13

SPM

xsfFileCheckout

File Checkout Information

Describes file checkout and revision locking

CheckoutKey	Guid Default(newid())	Primary Key:1
FileDockKey	Guid	In Index AK_xsfFileCheckout (Unique):1 References xsfFileVersionInfo.DockKey
RevID	Smallint(5)	References xsfFileVersionInfo.RevID
UserKey	Guid	References xsfUser.UserKey
Status	Char(1) Default('L')	Locked; Out; Unlocked; In; Canceled Check (charindex([status], 'LOUIX') > 0) H is used internally to HIDE the Checkin/Checkout options; H should never be stored
CheckedOut	Datetime(23,3) Default(getdate())	
CheckedIn	Datetime(23,3) NULL	
Expires	Datetime(23,3) NULL	
UpdateTS	Timestamp(8) NULL	

Fields: 9

SPM

xsfFileMarkup**File Version Markups and Resources**

Each row defines a markup or similar jVue resource

FileMarkupKey	Guid Default(newid())	Primary Key:1
FileVerKey	Guid	In Index IX_xsfFileMarkup:1 References xsfFileVersionInfo.FileVerKey
FromUser	Guid NULL	References xsfUser.UserKey
LastUser	Guid NULL	References xsfUser.UserKey
LockUser	Guid NULL	References xsfUser.UserKey
Folder	Guid NULL	
Created	Datetime(23,3) Default(getdate())	In Index IX_xsfFileMarkup:3
LastSaved	Datetime(23,3) NULL	
Locked	Datetime(23,3) NULL	
ReferenceDate	Datetime(23,3) NULL	
DataMethod	Char(4) Default('BIN')	
DMSType	Varchar(16)	In Index IX_xsfFileMarkup:2
Subtype	Varchar(16) NULL	
MarkupName	Varchar(80) NULL	
Other	Varchar(200) NULL	
txtData	Varchar(-1) NULL	
binData	Varbinary(-1) NULL	
UpdateTS	Timestamp(8) NULL	

Fields: 18

SPM

xsfFileRStatus**Store File Content Recognition Status**

Contains information about status of file recognition, per client

RSysName	Varchar(64)	Primary Key:1
DockKey	Guid	Primary Key:2
RevID	Smallint(5)	Primary Key:3
State	Char(1) Default('I')	In Index IX_FileStatus:1
Started	Datetime(23,3) Default(getdate())	
AsOf	Datetime(23,3) Default(getdate())	In Index IX_FileStatus:2
Details	Varchar(-1) NULL	
UpdateTS	Timestamp(8) NULL	

Fields: 8

SPM

xsfFileVersion**Stored File Version**

Enumerates the versions of a binary document

FileBinKey	Guid Default(newid())	Primary Key:1
Cataloged	Datetime(23,3) Default(getdate())	
BinSize	Int(10) Default((0))	Size of native binary data, regardless of current Data storage Method
DataMethod	Char(4) Default('BIN')	
Extension	Varchar(8) NULL	Copied from xsfFile.FileType for use by SQL Full Text engine
BinData	Varbinary(-1)	Binary version of actual file
PDFData	Varbinary(-1) NULL	
UpdateTS	Timestamp(8) NULL	

Fields: 8

SPM

xsfFileVersionInfo

Stored File Version Attributes

Enumerates the attributes of a binary document

FileVerKey	Guid	Primary Key:1
FileBinKey	Guid	In Index IX_xsfFileVersionInfo:1
DockKey	Guid	In Index AK_xsfFileVersionInfo (Unique):1 References xsfFile.DockKey
RevID	Smallint(5) Default((0))	In Index AK_xsfFileVersionInfo (Unique):2
BinSize	Int(10) Default((0))	
DataHash	Char(32) Default("")	In Index IX_xsfFileVersionHash:1
SourceRevision	Varchar(16) NULL	
Cataloged	Datetime(23,3) Default(getdate())	
Approved	Datetime(23,3) NULL	
ApprovedBy	Guid NULL	In Index IX_xsfFileVersionInfo_Approver:1
FromUser	Guid	In Index IX_xsfFileVersionInfo_FromUser:1 References xsfUser.UserKey
ArchiveDBKey	Guid NULL	
TxtData	Varchar(-1) NULL	
UpdateTS	Timestamp(8) NULL	

Fields: 14

SPM

xsfFlexKeySegments

Flex Key Segment Definition

Each row describes a segment of a flex key

FlexSegmentKey	Guid Default(newid())	Primary Key:1
FlexName	Char(30)	In Index AK_xsfFlexKeySegments (Unique):1
SegNumber	Smallint(5)	In Index AK_xsfFlexKeySegments (Unique):2
SegLen	Smallint(5)	
SegName	Varchar(16)	
SegMaskType	Char(1) Default((9))	U=Char;9=Numeric;W=AlphaNumericV=Lookup;
SegLookup	Varchar(32) NULL	#-Solomon Field Class; Solomon PJCODE; Spitfire Lookup Name
SegValues	Varchar(128) NULL	Comma separated list of drop down values
SegBreakFlag	Char(1) NULL	
SegRollupFlag	Char(1) NULL	
AllowTitles	Bit(1) Default((0))	
UpdateTS	Timestamp(8) NULL	

Fields: 12

SPM

xsfForecast

Forecast

Each row carries historical cost code/account data with forecast or budget adjustments

ForecastRowKey	Guid Default(newid())	Primary Key:1
DocRevKey	Guid	In Index AK_xsfForecast (Unique):1
RowType	Char(1)	Check ([RowType]='A' OR [RowType]='T')
ProjEntity	Char(32)	AKA CostCost In Index AK_xsfForecast (Unique):2
AccountCategory	Char(16)	In Index AK_xsfForecast (Unique):3
UOM	Char(30)	Unit of Measure
CostingMethod	Char(2)	CP, FP or UP - Default from PJPENT.User1

Projected	Bit(1) Default((1))	When true, the entry is projected. Once set, carries forward. Default is inferred. In Index IX_xsfForecast_AcctTasks (Unique
Threshold	Smallint(5) Default((15))	15=15% Initialized from xsfProject.ForecastThreshold or xsfConfig In Index IX_xsfForecast_AcctTasks (Unique
BudgetedRevenue	Money(19,4) NULL	Last Posted EAC Revenue
OriginalRevenue	Money(19,4) NULL	v4.1
CurrentBudget	Money(19,4) NULL	
OriginalBudget	Money(19,4) NULL	
BudgetRevision	Money(19,4) NULL	EAC - Approved PCOs - Original Budget = net other revisions
ApprovedCO	Money(19,4) NULL	Expenses from Approved PCOs
VerbalCO	Money(19,4) NULL	Includes PCOs that are committed but without final approval
PendingCo	Money(19,4) NULL	Includes Pending PCOs with probability over PCO threshold
ApprovedCORevenue	Money(19,4) NULL	Revenue from PCOs that are approved; formerly VerbalCORevenue
PendingCORevenue	Money(19,4) NULL	Includes Pending PCOs with probability over PCO threshold and all committed PCOs
PendingBudgetRevision	Money(19,4) NULL	
PriorFACRevenue	Money(19,4) NULL	Last posted FAC revenue; repurposed from PendingFACAmount
OriginalUnits	Numeric(17,5) NULL	
RevisionUnits	Numeric(17,5) NULL	
ActualUnits	Numeric(17,5) NULL	
PendingBudgetUnits	Numeric(17,5) NULL	
ActualToDate	Money(19,4) NULL	
CommittedToDate	Money(19,4) NULL	
ActualPY	Money(19,4) NULL	
ActualPP	Money(19,4) NULL	
ActualCY	Money(19,4) NULL	
ActualCP	Money(19,4) NULL	
ActualUnitsPY	Money(19,4) NULL	
ActualUnitsPP	Money(19,4) NULL	
ActualUnitsCY	Money(19,4) NULL	
ActualUnitsCP	Money(19,4) NULL	
ChargesToDate	Money(19,4) NULL	non integrated only, not currently displayed
OriginalSC	Money(19,4) NULL	Original Commitments (subcontracts)
ApprovedSCO	Money(19,4) NULL	
PendingSCO	Money(19,4) NULL	SC Pending Change Order
PotentialSCO	Money(19,4) NULL	
SCPayReqRetention	Money(19,4) NULL	SC Pay Req Retention
SCPayReqTotal	Money(19,4) NULL	SC Pay Req Total
SCPayReqPaid	Money(19,4) NULL	SC Pay Req Amount paid
SCPPRRetention	Money(19,4) NULL	SC Pending Pay Req Retention
PendingPayAmount	Money(19,4) NULL	SC Pending Pay Req Amount
SCRemainingPay	Money(19,4) NULL	SC Amount remaining to pay; balance excludes completed commitments, final paid commitments and overpaid lines
PriorFAC	Money(19,4) NULL	Last Posted FAC expense amount
PriorFACUnits	Money(19,4) NULL	

BTDRRevenue	Money(19,4) NULL	Billed to Date
VendorName	Varchar(60) NULL	Vendor name from commitment or Multiple
Notes	Varchar(2048) NULL	Free form notes
TrackingNotes	Varchar(2048) NULL	
czUDSText1	Varchar(255) NULL	
czUDSText2	Varchar(255) NULL	
czUDSAmt1	Money(19,4) NULL	
czUDSAmt2	Money(19,4) NULL	
czUDSAmt3	Money(19,4) NULL	
DeclaredUnits	Money(19,4) NULL	
DeclaredPercentComplete	Money(19,4) NULL	
ChangeFACorFTC	Smallint(5) Default((0))	Change code In Index IX_xsfForecast_Chain:6
ChangePercentComplete	Numeric(5,2) NULL	
ChangeTaskProductionUnits	Money(19,4) NULL	The new amount of production units for a forecast task
ChangeAmount	Money(19,4) NULL	
ChangeProductionRate	Money(19,4) NULL	
ChangeAccountProductionUnits	Money(19,4) NULL	The new amount of units for a forecast account category
ChangeDollarsPerUnit	Money(19,4) NULL	
ChangeHrsPerUnit	Money(19,4) NULL	
ChangeUnitsPerHr	Money(19,4) NULL	
ChangeProductivityFactor	Money(19,4) NULL	
ChangeWorkingFAC	Money(19,4) NULL	
ChangeWorkingFACUnits	Money(19,4) NULL	Internal use
ChangeWorkingPercentComplete	Money(19,4) NULL	
ChangeWorkingAmountGL	Money(19,4) NULL	
ChangeWorkingProdUnitGL	Money(19,4) NULL	
ChangeWorkingUnitGL	Money(19,4) NULL	
ChangeBudgetType	Smallint(5) Default((0))	In Index IX_xsfForecast_Chain:5
ChangeBudgetAmount	Money(19,4) NULL	
ChangeBudgetUnit	Money(19,4) NULL	
ChangeByUserKey	Guid NULL	When set, indicates this entry has been modified in this forecast revision In Index IX_xsfForecast_Chain:4 When NULL, this row has not been modified in this forecast
PriorChangeKey	Guid NULL	Indicates the prior forecast (if any) that changed the same costcode and account
PriorBudgetChangeKey	Guid NULL	Indicates the prior budget (if any) that changed the same costcode and account
UpdateTS	Timestamp(8) NULL	In Index IX_xsfForecast_AcctTasks (Unique)

Fields: 82

SPM

xsfSnapshotByPeriod

Project Budget by Period Snapshot

Each row carries historical cost code/account data by period

PBDistribKey	Guid Default(newid())	Primary Key:1
ForecastRowKey	Guid	In Index AK_xsfSnapshotByPeriod (Unique) References xsfForecast.ForecastRowKey
FiscalPeriod	Char(6)	In Index AK_xsfSnapshotByPeriod (Unique)
ActAmount	Money(19,4) NULL	
EACAmount	Money(19,4) NULL	
FACAmount	Money(19,4) NULL	
ORGAmount	Money(19,4) NULL	
ChangeType	Smallint(5) Default(0)	
ChangeAmountNet	Money(19,4) NULL	
UpdateTS	Timestamp(8) NULL	

Fields: 10

SPM

xsflInclusion

Include and Exclusion Items

Each row holds an inclusion or exclusion item for a contract

InclusionKey	Guid Default(newid())	Primary Key:1
DocRevKey	Guid	In Index IX_xsflInclusion (Unique):1 References xsfDocRevision.DocRevKey
ItemType	Char(1) Default('I')	In Index IX_xsflInclusion (Unique):2
ItemNumber	Varchar(32)	In Index IX_xsflInclusion (Unique):3
Paragraph	Varchar(30) NULL	
csString016	Varchar(16) NULL	
csString030	Varchar(30) NULL	
csString060	Varchar(60) NULL	
csAmount	Money(19,4) NULL	
csDate	Datetime(23,3) NULL	
csCheck	Bit(1) Default((0))	
ItemText	Varchar(-1) NULL	
UpdateTS	Timestamp(8) NULL	

Fields: 13

SPM

xsflInclusionStock

Source list of stock inclusion entries

Each row stores a stock inclusion entry

InclusionStockKey	Guid Default(newid())	Primary Key:1
ItemType	Char(1) Default('I')	
Paragraph	Varchar(30)	
ItemText	Varchar(-1)	
UpdateTS	Timestamp(8)	

Fields: 5

SPM

xsfltemContainer

Heirachical Container

Each row identifies a container (folder) for items (files)

ItemContainerKey	Guid Default(newid())	Primary Key:1
ParentKey	Guid	In Index AK_xsfltemContainer (Unique):1
Label	Varchar(64)	The name of this container In Index AK_xsfltemContainer (Unique):2
Source	Char(2) Default('C')	
Created	Datetime(23,3) Default(getdate())	
UpdateTS	Timestamp(8) NULL	

Fields: 6

SPM

xsfltemPermit

Item Permission settings

Permissions assigned to roles for various folders and files

ItemPermitKey	Guid Default(newid())	Primary Key:1
ItemKey	Guid	Weak link to resource, see ItemType In Index AK_xsfltemPermit (Unique):2
UCRoleKey	Guid	In Index AK_xsfltemPermit (Unique):1 References xsfUCRole.UCRoleKey
ItemType	Char(1) Default('C')	
ListOK	Bit(1) Default(1)	
ReadOK	Bit(1) Default(1)	
InsOK	Bit(1) Default(0)	
UpdOk	Bit(1) Default(0)	
DelOK	Bit(1) Default(0)	
BlanketOK	Bit(1) Default(0)	
UpdateTS	Timestamp(8) NULL	

Fields: 11

SPM

xsfMeetingAttendee

Meeting Attendee

List of attendees

AttendeeKey	Guid Default(newid())	Primary Key:1
DocMasterKey	Guid	In Index IX_xsfMeetingAttendee:1 References xsfDocHeader.DocMasterKey
UserKey	Guid NULL	
LinkedItemKey	Guid NULL	References xsfDocItem.DocItemKey
AttendeeName	Varchar(50) NULL	In Index IX_xsfMeetingAttendee:2
Reference	Varchar(30) NULL	
Purpose	Varchar(8) NULL	
Amount	Money(19,4) NULL	
csAmount	Money(19,4) NULL	
Resolved	Datetime(23,3) NULL	
csDate	Datetime(23,3) NULL	
csString016	Varchar(16) NULL	
csString030	Varchar(30) NULL	
csString060	Varchar(60) NULL	
Present	Bit(1) Default((0))	
IsRegular	Bit(1) Default((1))	When TRUE, auto copied to next meeting
csCheck	Bit(1) Default((0))	
Note	Varchar(-1) NULL	
UpdateTS	Timestamp(8) NULL	

Fields: 19

SPM

xsfNodeParentCache

Preresolved lineage

A set of rows for each leaf

LeafNodeKey	Guid	Primary Key:1
LevelNum	Smallint(5)	Primary Key:2
ItemContainerKey	Guid	
ParentKey	Guid NULL	

Fields: 4

SPM

xsfPartConfig

User Interface Part Customization

Each row applies a change in label or visibility to a user interface item

Field Name	Field Type	Description
PartConfigKey	Guid Default(newid())	Primary Key:1
PartName	Varchar(64)	One of the UI Part names listed in Page.Config In Index IX_xsfPartConfig:1 References xsfUIPartItem.PartName
ItemName	Varchar(64) NULL	One of the UI item names listed in Page.Config (PartCfgltem) In Index IX_xsfPartConfig:2 References xsfUIPartItem.ItemName
DocTypeKey	Guid NULL	Associates this customization with a specific document type; leave null for all In Index IX_xsfPartConfig:3 References xsfDocType.DocTypeKey
UCFunctionKey	Guid NULL	Associates this customization with a specific capability; leave null for all References xsfUCFunction.UCFunctionKey
Container	Varchar(50) NULL	V3.0 In Index IX_xsfPartConfig:4
Filter	Varchar(64) NULL	Unused filter In Index IX_xsfPartConfig:5
Label	Varchar(64) NULL	When specified, overrides the default label (or sets a text value for this item)
LookupName	Varchar(32) NULL	weak reference to xsfLookup
DisplayFormat	Varchar(16) NULL	
AuxData	Varchar(250) NULL	see KBA-01336
TipText	Varchar(100) NULL	Used to set UI tool tip text
HelpText	Varchar(200) NULL	For quick help
LimitTo	Smallint(5) NULL	For overriding length
SeqData	Smallint(5) NULL	For controlling tab order
RequiredBefore	Smallint(5) Default((0))	see KBA-01434
IsReadOnly	Bit(1) Default((0))	When TRUE, UI will be read only
Active	Bit(1) Default((1))	When false, this row is ignored
Visible	Bit(1) Default((1))	Controls the visible attribute (or sets a boolean value)
IsDistributed	Bit(1) Default((0))	When true, this row is distributed default In Index IX_xsfPartConfig:6
UpdateTS	Timestamp(8)	

Fields: 21

SPM

xsfPartConfigHistory

History of UI Part customizations

Each row preserves the value of a customization setting at a point in time

CfgHistoryKey	Guid	Primary Key:1 References xsfCustomizationHistory.CfgHistoryKey
PartConfigKey	Guid	Primary Key:2
PartName	Varchar(64)	References xsfUIPartItem.PartName
ItemName	Varchar(64) NULL	References xsfUIPartItem.ItemName
DocTypeKey	Guid NULL	References xsfDocType.DocTypeKey
UCFunctionKey	Guid NULL	References xsfUCFunction.UCFunctionKey
Container	Varchar(50) NULL	
Filter	Varchar(64) NULL	
Label	Varchar(64) NULL	
LookupName	Varchar(32) NULL	
DisplayFormat	Varchar(16) NULL	
AuxData	Varchar(250) NULL	
TipText	Varchar(100) NULL	
HelpText	Varchar(200) NULL	
LimitTo	Smallint(5) NULL	
SeqData	Smallint(5) NULL	
RequiredBefore	Smallint(5)	
IsReadOnly	Bit(1)	
Active	Bit(1)	
Visible	Bit(1)	
IsDistributed	Bit(1)	
UpdateTS	Timestamp(8)	

Fields: 22

SPM

xsfPersistedData

Transient System Data

Each row stores data for the system. Most commonly used for user state and preferences

PersistedDataKey	Char(160)	Primary Key:1
UserKey	Guid Default('00000000-0000-	Allows storage to be grouped by user In Index IX_xsfPersistedData_ByUser:1
MasterSession	Char(64) Default('')	Allows storage to be grouped by session. In Index IX_xsfPersistedData_BySession:1 This is not exactly an IIS session. In fact, many IIS sessions will map to a single value, but generally a MasterSession will belong to a single user
Boundary	Datetime(23,3) Default(getdate())	Rows (with a MasterSession) can be removed at any point 48 hours after this date and time In Index IX_xsfPersistedData_ByBoundary:1
Created	Datetime(23,3) Default(getdate())	Informational
BinType	Char(8) Default('')	Unused at this time
DataMethod	Char(4) Default('BIN')	Normally BIN or GZ
BinData	Varbinary(-1)	
UpdateTS	Timestamp(8) NULL	

Fields: 9

SPM

xsfPjPeriodRev

Project Budget by Period Revision Header

Each row defines a period based revision to the project budget

PeriodRevKey	Guid Default(newid())	Primary Key:1
DocRevKey	Guid	References xsfDocRevision.DocRevKey
Project	Char(16)	In Index AK_xsfPjPeriodRev (Unique):1
RevisionID	Int(10)	In Index AK_xsfPjPeriodRev (Unique):2
ProjectRevID	Int(10) NULL	
UpdateMask	Int(10)	
InPeriod	Char(6)	
RevSource	Char(1)	
Created	Datetime(23,3) Default(getdate())	
Posted	Datetime(23,3) NULL	
UpdateTS	Timestamp(8)	

Fields: 11

SPM

xsfPjPeriodRevBD

Project Budget by Period Revision Detail

Each row describes the change to a specific line

PBDRevKey	Guid Default(newid())	Primary Key:1
PeriodRevKey	Guid	In Index AK_xsfPjPeriodRevBD (Unique):1 References xsfPjPeriodRev.PeriodRevKey
ProjectWBSKey	Guid	In Index AK_xsfPjPeriodRevBD (Unique):2 References xsfProjectWBS.ProjectWBSKey
WbPart	Char(16)	In Index AK_xsfPjPeriodRevBD (Unique):3
FiscalPeriod	Char(6)	In Index AK_xsfPjPeriodRevBD (Unique):4
Quantity	Money(19,4) NULL	
Amount	Money(19,4) NULL	
UpdateTS	Timestamp(8)	

Fields: 8

SPM

xsfProgram

Project Programs

Each row defines a collection of multiple projects

ProgramKey	Guid Default(newid())	Primary Key:1
ProgramID	Varchar(24)	In Index AK_xsfProgram (Unique):1
ProgramTitle	Varchar(60)	
Logo	Guid NULL	
Active	Bit(1) Default((1))	
UpdateTS	Timestamp(8)	

Fields: 6

SPM

xsfProgramProjectMap

Program Project List

Each row defines a project in a program

PgmPjtMapKey	Guid Default(newid())	Primary Key:1
ProgramKey	Guid	In Index AK_xsfProgramProjectMap:1 References xsfProgram.ProgramKey
ProjectKey	Guid	In Index AK_xsfProgramProjectMap:2 References xsfProject.ProjectKey
Created	Datetime(23,3) Default(getdate())	
Active	Bit(1) Default((1))	
UpdateTS	Timestamp(8)	

Fields: 6

SPM

xsfProject

Project Information

Each row provides additional data describing a project

ProjectKey	Guid Default(newid())	Primary Key:1
Project	Char(16)	In Index AK_xsfProject (Unique):1
ProjectType	Char(2) Default('P')	P,E,D
SetupDocKey	Guid NULL	weak link to project setup document
SiteAddrKey	Guid NULL	weak link to xsfDocAddr row with site address
Person	Varchar(60) Default("")	
Company	Varchar(60)	
Addr1	Varchar(60)	
Addr2	Varchar(60)	
City	Varchar(30)	
State	Char(2)	
Zip	Char(10)	
County	Varchar(40) Default("")	
Phone	Varchar(20) NULL	
Fax	Varchar(20)	
ExternalStatus	Varchar(8) NULL	for customer dashboard
ExternalSchedule	Varchar(8) NULL	for customer dashboard
SCBudgetMode	Varchar(8) Default('N')	Controls how Commitment Documents initialize budget target UpdateMask
PlanRoomMode	Varchar(8) Default('0')	
WebCamURL	Varchar(200) NULL	
Description	Varchar(-1) NULL	for customer dashboard
ForecastThreshold	Smallint(5) NULL	Check (isnull([ForecastThreshold],(0))>=(0) AND isnull
latitude	Decimal(12,9) NULL	decimal location
longitude	Decimal(12,9) NULL	decimal location
Active	Bit(1) Default((1))	
UpdateTS	Timestamp(8)	

Fields: 26

SPM

xsfProjectRevision

Project Revision

Each row describes a revision to a project budget

BudgetRevisionKey	Guid Default(newid())	Primary Key:1
DocRevKey	Guid	References xsfDocRevision.DocRevKey
Project	Char(16)	In Index AK_xsfProjectRevision (Unique):1
RevisionID	Int(10)	In Index AK_xsfProjectRevision (Unique):2
UpdateMask	Int(10) Default((0))	Bit Coded: Bid(1), EAC(2), FAC(4) In Index IX_xsfProjectRevision_Source:0
Description	Varchar(80) NULL	
ExternalID	Varchar(16) NULL	DSL: pjrevhdr.revid
ChangeOrder	Varchar(16) NULL	number
InPeriod	Char(6) Default("")	YYYYMM
DSLType	Char(1) NULL Default('x')	
Mode	Char(2) Default('x')	NT=Net
RevisionSource	Char(2) Default('x')	Budget, Chage order,Forecast
Status	Char(2) Default('P')	P=Posted
ByProg	Char(6) Default("")	Identifies the logic that created the revision
ByUser	Varchar(47) NULL	Identifies the user
Created	Datetime(23,3) Default(getdate())	In Index IX_xsfProjectRevision_Source:0
SourceDocRevKey	Guid NULL	Weak link to CCO, Change Order revision that created this budget revision In Index IX_xsfProjectRevision_Source:1
HitsCost	Bit(1) Default((0))	true if any child row has type=ex In Index IX_xsfProjectRevision_Source:0
HitsRevenue	Bit(1) Default((0))	TRUE if any child row has type=RV In Index IX_xsfProjectRevision_Source:0
UpdateTS	Timestamp(8)	

Fields: 20

SPM

xsfProjectRevisionWB

Project Revision Detail

Each row describes the change to a specific line

ProjectRevDetailKey	Guid	Primary Key:1
BudgetRevisionKey	Guid	In Index IX_xsfProjectRevisionWB (Unique) References xsfProjectRevision.BudgetRevisionKey
WBCode	Char(32)	In Index IX_xsfProjectRevisionWB (Unique)
WBPart	Char(16)	In Index IX_xsfProjectRevisionWB (Unique)
Quantity	Money(19,4)	
Amount	Money(19,4)	
NewPercentComplete	Int(10) NULL	
ChangeType	Int(10) Default(1)	1=net
Starting	Datetime(23,3) NULL	
Ending	Datetime(23,3) NULL	
Description	Varchar(50) Default("")	
UpdateTS	Timestamp(8)	

Fields: 12

SPM

xsfProjectWBS

Project Work Breakdown

Each row defines a task in a project work breakdown

ProjectWBSKey	Guid Default(newid())	Primary Key:1
Project	Char(16)	In Index AK_xsfProjectWBS (Unique):1 References xsfProject.Project
WBCode	Char(32)	Work Breakdown code, often a combination of a CSI and phase In Index AK_xsfProjectWBS (Unique):2
Description	Varchar(64)	
ContractType	Char(4) NULL	
UOM	Char(4) NULL	
Status	Varchar(8) NULL	
SOVLine	Varchar(32) NULL	
SchedStart	Datetime(23,3) NULL	
SchedFinish	Datetime(23,3) NULL	
ActStart	Datetime(23,3) NULL	
ActFinish	Datetime(23,3) NULL	
PercentComplete	Int(10) Default(0)	
CostingMethod	Char(2) Default('FP')	
UpdateTS	Timestamp(8) NULL	

Fields: 15

SPM

xsfProjectWBSegment

Descriptive Titles for Project WBS Segments

Each row defines the title for a given WBS code segment value on a specific project

ProjectWBSSegmentKey	Varbinary(16) Default(newid())	Primary Key:1
Project	Varchar(16)	In Index AK_xsfProjectWBSegment (Unique)
SegNumber	Smallint(5)	In Index AK_xsfProjectWBSegment (Unique)
SegValue	Varchar(32)	In Index AK_xsfProjectWBSegment (Unique)
SegValueDescription	Varchar(60)	
UpdateTS	Timestamp(8)	

Fields: 6

SPM

xsfReference

CSI and/or Uniformalt

Each row defines a reference with which documents and items can be associated. Includes optional Division and/or Rollup

UniReferenceKey	Guid Default(newid())	Primary Key:1
Description	Varchar(50)	
DivCode	Char(2) NULL	
Rollup	Char(10) NULL	
Active	Bit(1) Default((1))	
UpdateTS	Timestamp(8)	

Fields: 6

SPM

xsfRegion

Region Definition

Each row defines a region

Field Name	Field Type	Field Properties
RegionKey	Guid	Primary Key:1
RegionID	Varchar(10)	In Index AK_Region (Unique):1
Description	Varchar(64) NULL	
Created	Datetime(23,3) Default(getdate())	
UpdateTS	Timestamp(8)	

Fields: 5

SPM

xsfRegionMap

Company Region Map

Each row associates a contact company with a region

Field Name	Field Type	Field Properties
RegionMapKey	Guid	Primary Key:1
ContactCompanyKey	Guid	In Index AK_RegionMap (Unique):1
RegionKey	Guid	In Index AK_RegionMap (Unique):2 References xsfRegion.RegionKey
Comment	Varchar(64) NULL	
Created	Datetime(23,3) Default(getdate())	
Active	Bit(1) Default((1))	
UpdateTS	Timestamp(8)	

Fields: 7

SPM

xsfRoute

Routed Document User Detail

Enumerates the users to/through whom a document has been routed

RouteID	Guid Default(newid())	Primary Key:1
DocMasterKey	Guid Default(newid())	In Index AK_xsfRouteDetail (Unique):1 References xsfDocHeader.DocMasterKey
UserKey	Guid	The target Routee In Index AK_xsfRouteDetail (Unique):4 References xsfUser.UserKey
Stage	Smallint(5)	In Index AK_xsfRouteDetail (Unique):2
Sequence	Smallint(5)	In Index AK_xsfRouteDetail (Unique):3 Every document has at least one route record with stage=sequence=0 to indicate the originator
GroupNo	Smallint(5) Default((0))	
FromUser	Guid NULL	Used when forwarding In Index IX_xsfRouteToUser:0 Defaults to originator
Status	Char(1) Default('P')	Pending; Accepted; Rejected; Back; Hold; Cc; Destination; In Index IX_xsfRouteToUser:5
RouteVia	Char(1) NULL	
UserDocEdit	Bit(1) Default((0))	Controls edits to base document
SendAlerts	Bit(1) Default((0))	This routee wants watchdog alerts about this document
ReplyTo	Bit(1) Default((0))	When true, email based routing include this routee so that they will receive replies
Note	Varchar(-1) NULL	In Index IX_xsfRouteToUser:0
Request	Varchar(-1) NULL	
Response	Varchar(-1) NULL	
ResponseCode	Varchar(8) NULL	
WorkflowScript	Varchar(-1) NULL	Stores workflow directives
Alerted	Datetime(23,3) NULL	Set when email notification is sent
Viewed	Datetime(23,3) NULL	Set when first viewed In Index IX_xsfRouteToUser:4
Downloaded	Datetime(23,3) NULL	
Due	Datetime(23,3) NULL	Status change by this user is due by this time In Index IX_xsfRouteToUser:0
Acted	Datetime(23,3) NULL	Set by the data layer when Status changes
UpdateTS	Timestamp(8) NULL	Internal

Fields: 23

SPM

xsfRouteContentPending

Catalog content to be updated for routing

Each row flags a routed content that still needs to be updated before routing

RouteContentKey	Guid	In Index AK_xsfRouteContentPending:3 References xsfRoutedContent.RouteContentKey
DocKey	Guid	In Index AK_xsfRouteContentPending:1
AsOf	Datetime(23,3) Default(getdate())	In Index AK_xsfRouteContentPending:2
UpdateTs	Timestamp(8)	

Fields: 4

SPM

xsfRoutedContent

Enumerates content of document when routed to spec

Each row records a specific file version sent to a specific route

RouteContentKey	Guid	Primary Key:1
RouteStepKey	Guid	In Index AK_xsfRoutedContent:1
RouteID	Guid	In Index AK_xsfRoutedContent:2 References xsfRoute.RouteID
OutputRefKey	Guid	In Index IX_xsfRoutedContent_File:1
FileVerKey	Guid NULL	
FileBinKey	Guid NULL	
ItemRefKey	Guid NULL	
FromDocMasterKey	Guid	In Index AK_xsfRoutedContent:3
MergeWithSeq	Int(10) Default((0))	In Index AK_xsfRoutedContent:4
ContentSeq	Int(10)	In Index AK_xsfRoutedContent:5
NestedSeq	Int(10)	In Index AK_xsfRoutedContent:6
IncludeFlag	Char(1)	
UpdateTS	Timestamp(8)	

Fields: 13

SPM

xsfRouteList

Document Route Detail

Enumerates the users in a pre-defined route

RouteListKey	Guid Default(newid())	Primary Key:1
RouteKey	Guid	References xSfRouteListMaster.RouteKey
SeqNo	Smallint(5)	1 is reserved for originator
GroupNo	Smallint(5) Default((0))	
NoRepeats	Smallint(5) Default((0))	If true, will not add a user in this sequence if the user is already in the immediately prior seq
UserKey	Guid NULL	References xsfUser.UserKey
UCRoleKey	Guid NULL	Weak link to Role for Role-based routine rule Either UserKey or UCRoleKey, but not both
AccessLevel	Char(1) Default('V')	View or Update
DefaultStatus	Char(1) Default('P')	Pending; Cc; Access
DefaultVia	Char(1) NULL	FUTURE:default route via (E/F/H/W) - subject to other rules and contact data
DueInDays	Smallmoney(10,4) NULL	Makes this sequence due this much after the prior sequence. All prior sequences must have a value. Workflow recommended
DefaultNote	Varchar(500) NULL	The note that should be inserted into the xsfRoute row created by this entry
Description	Varchar(200) NULL	Free form explanation or generic description of this rows pupose
WorkflowScript	Varchar(-1) NULL	Workflow directives
SendAlerts	Bit(1) Default((0))	
UseTransmittal	Bit(1) Default((0))	
AtSourceContact	Bit(1) Default((0))	
SetEmailFrom	Bit(1) Default((0))	
UpdateTS	Timestamp(8) NULL	

Fields: 19

SPM

xSfRouteListMaster

Document Route List

Enumerates pre-defined routes

RouteKey	Guid Default(newid())	Primary Key:1
RouteName	Varchar(50)	In Index IX_xSfRouteListMaster (Unique):1
Active	Bit(1) Default(1)	
UpdateTS	Timestamp(8) NULL	

Fields: 4

SPM

xsfRouteSpecial

Document Route Selection Criteria

Criteria by which a pre-defined route should be chosen

RouteSpecialKey	Guid Default(newid())	Primary Key:1
DocTypeKey	Guid	In Index IX_xsfRouteSpecial:1 References xsfDocType.DocTypeKey
Project	Char(16) NULL	When specified, Limits this rule to documents with matching Project
ProjEntity	Char(32) NULL	Limits this rule to documents with matching ProjEntity (Cost Code). Values on items within the document are not considered.
DivisionID	Char(10) NULL	
Status	Char(2) NULL	When specified, Limits this rule to documents with matching Status.
Subtype	Varchar(8) NULL	
ProjectSubtype	Varchar(8) NULL	
AmountLo	Money(19,4) NULL	
AmountHi	Money(19,4) NULL	
Priority	Smallint(5) NULL	When specified, Limits this rule to documents with matching Priority.
UniReferenceKey	Guid NULL	
DocReference	Guid NULL	When specified, Limits this rule to documents with matching Reference.
ResponsibleParty	Guid NULL	Limits this rule to documents with matching Responsible Party. Any RPs on Items within the document are not considered.
SourceContact	Guid NULL	Limits this rule to documents with matching Source Contact. Use this criteria to create vendor based route rules.
RouteKey	Guid	Required References xSfRouteListMaster.RouteKey
Description	Varchar(200) NULL	Free form description of this rows purpose
AutoRoute	Bit(1) Default((0))	When true, the creator automatically approves the document so it moves to the next route sequence.
Active	Bit(1) Default((1))	When false, this row is ignored
UpdateTS	Timestamp(8) NULL	

Fields: 20

SPM

xsfRouteStep

Document Route Steps (Stage and Sequence)

Each row describes a route step for its document

RouteStepKey	Guid	Primary Key:1
DocMasterKey	Guid	In Index AK_xsfRouteStep (Unique):1 References xsfDocHeader.DocMasterKey
Stage	Smallint(5)	In Index AK_xsfRouteStep (Unique):2
Sequence	Smallint(5)	In Index AK_xsfRouteStep (Unique):3
Created	Datetime(23,3) Default(getdate())	
Reached	Datetime(23,3) NULL	
ContentSet	Datetime(23,3) NULL	
Resolved	Datetime(23,3) NULL	
NextStepKey	Guid NULL	
UpdateTS	Timestamp(8)	

Fields: 10

SPM

xsfRouteTransmittal

Extends a Route Entry with a Transmittal

Each row identifies a transmittal

RouteID	Guid Default(newid())	Every row is related to a Route row Primary Key:1 References xsfRoute.RouteID
ByUser	Guid	References xsfUser.UserKey
TransNumber	Int(10) Identity	The transmittal control number In Index AK_xsfRouteTransmittal (Unique):
Created	Datetime(23,3) Default(getdate())	
TransStatus	Char(2) NULL	not currently used
BinType	Varchar(8) Default('doc')	
BinData	Varbinary(-1) NULL	
UpdateTS	Timestamp(8) NULL	

Fields: 8

SPM

xsfRule

Logic Rules

Each row describes a rule

RuleKey	Guid Default(newid())	Primary Key:1
RuleName	Varchar(50)	The name of the rule as it is referenced In Index AK_xsfRule (Unique):1
FilterInfo	Varchar(50) NULL	A description of the filter value if one is applicable to this rule
ResultType	Char(10) NULL	
Description	Varchar(500) NULL	A description of the rules purpose

Fields: 5

SPM

xsfRuleItem

Logic Rule Detail

Each row defines the result for a set of inputs

RuleItemKey	Guid Default(newid())	Primary Key:1
RuleKey	Guid	In Index AK_xsfRuleItem (Unique):1 References xsfRule.RuleKey
IsDistributed	Bit(1) Default((0))	when true, Spitfire distributes this entry as a default In Index AK_xsfRuleItem (Unique):4
Immutable	Bit(1) Default((0))	when true, this distributed entry cannot be overridden via UI
TestValue	Varchar(40)	The input, often a value from xsfDocTypeSubcodes or another code In Index AK_xsfRuleItem (Unique):2
FilterValue	Varchar(64) NULL	In Index AK_xsfRuleItem (Unique):3
ResultValue	Varchar(196) NULL	
UpdateTS	Timestamp(8)	

Fields: 8

SPM

xsfRuleItemHistory

History of Rule settings

Each row preserves the value of a customization setting at a point in time

CfgHistoryKey	Guid	In Index AK_xsfRuleItemHistory (Unique):2 References xsfCustomizationHistory.CfgHistoryKey
RuleItemKey	Guid	Primary Key:2
RuleKey	Guid	In Index AK_xsfRuleItemHistory (Unique):1 References xsfRule.RuleKey
IsDistributed	Bit(1)	In Index AK_xsfRuleItemHistory (Unique):5
TestValue	Varchar(40)	In Index AK_xsfRuleItemHistory (Unique):3
FilterValue	Varchar(64) NULL	In Index AK_xsfRuleItemHistory (Unique):4
ResultValue	Varchar(196) NULL	
UpdateTS	Timestamp(8)	

Fields: 8

SPM

xsfRuleItemValidation

Rule Item Validation

Each row defines a validation for a rule entry

RuleItemValidationKey	Guid Default(newid())	Primary Key:1
RuleKey	Guid	In Index AK_xsfRuleItemValidation (Unique)
TestValueLike	Varchar(48)	Can include wildcard. Determines to which test values this validation applies In Index AK_xsfRuleItemValidation (Unique)
SuffixSeparator	Varchar(4) NULL	If the TestValueLike included a wildcard, this character help break it into two parts
SuffixSetName	Varchar(16) NULL	If specified, the Test Value (or its suffix) is validated against values in this code set
FilterType	Varchar(32)	References xsfRuleValueType.ValueTypeID
FilterSetName	Varchar(16) NULL	If specified, the Filter Value is validated against values in this code set
ResultType	Varchar(32)	References xsfRuleValueType.ValueTypeID
ResultSetName	Varchar(16) NULL	
ValidationSequence	Smallint(5) NULL Default((100))	allows multiple matching tests to be made in sequence
ValidationLayer	Smallint(5) Default((1))	Future: 1=TSQL;2=BLL;3=Both (currently only TSQL is supported)
ValidationType	Char(1) NULL Default('W')	Future - warn/block/etc
IsFinal	Bit(1) Default((0))	When true and the validation passes, entries with higher sequence are ignored
Active	Bit(1) Default((1))	
UpdateTS	Timestamp(8)	

Fields: 15

SPM

xsfRuleValueEnum

Rule Value Enumeration for Type

Each row defines a possible value that can be used for the corresponding rule value type

RIVVEnumKey	Guid Default(newid())	Primary Key:1
ValueTypeID	Varchar(32)	In Index AK_xsfRuleValueEnum (Unique):1
ValidValueLike	Varchar(128) NULL	In Index AK_xsfRuleValueEnum (Unique):2
UpdateTS	Timestamp(8) NULL	

Fields: 4

SPM

xsfRuleValueType

Rule Value Type

Each row defines a filter or result value type

RuleVVTKey	Guid Default(newid())	Primary Key:1
ValueTypeID	Varchar(32)	In Index AK_xsfRuleValueType (Unique):1
ForFiltering	Bit(1) Default((0))	
ForResults	Bit(1) Default((0))	
Comments	Varchar(700) NULL	
UpdateTS	Timestamp(8)	

Fields: 6

SPM

xsStaticResource

Protected System Resources

Each row identifies, by GUID, a row in another table that has limited mutability by sites

ResourceKey	Guid Default(newid())
Note	Varchar(64) NULL
Active	Bit(1)
Hidden	Bit(1) Default(0)
Immutable	Bit(1) Default(1)
UpdateTS	Timestamp(8) NULL

Fields: 6

SPM

xsTaxRate

Tax Rate Definitions

Each row defines a tax rate

TaxRateKey	Guid	Primary Key:1
TaxID	Char(10)	Weak Link to DSL In Index AK_xsTaxRate (Unique):1
VendorID	Char(16) NULL	Weak link to vendor (taxing authority)
TaxType	Varchar(8)	not currently used
Description	Varchar(60)	Freeform
TaxRate	Decimal(9,6)	8.25% as .0825
IncludeFreight	Char(10) Default((0))	
UpdateTS	Timestamp(8) NULL	

Fields: 8

SPM

xsUCFunction

System Function List

Enumerates system defined Capabilities

UCFunctionKey	Guid Default(newid())	Primary Key:1
UCModule	Char(4) Default('SYS')	In Index AK_xsUCFunction_Name (Unique):1
UCName	Varchar(50)	In Index AK_xsUCFunction_Name (Unique):2
PermitMask	Smallint(5) Default(31)	Bit mask of relevant permissions for this capability:1-Read;2-Insert;4-Update;8-Delete;16-Special;
P1Name	Varchar(16) Default('Read')	Allows custom capability level in place of the default (read)
P5Name	Varchar(16) Default('Special')	Allows custom capability level in place of the default (blanket/special)
Description	Varchar(64) NULL	

Fields: 7

SPM

xsUCFunctionMap

Maps Capabilities to affected UI Parts

Each row defines a capability that changes the capabilities of a user in a given part of the system

UCPartMapKey	Guid Default(newid())	Primary Key:1
UCFunctionKey	Guid	In Index IX_xsUCFunctionMap (Unique):2 References xsUCFunction.UCFunctionKey
PartName	Varchar(64)	In Index IX_xsUCFunctionMap (Unique):1
Notes	Varchar(176) Default("")	
Active	Bit(1) Default((1))	
UpdateTS	Timestamp(8) NULL	

Fields: 6

SPM

xsfUCFunctionPermit

Role Permission Settings

Functions assigned to various roles

PermitKey	Guid Default(newid())	Primary Key:1
UCFunctionKey	Guid	In Index AK_xsfUCFunctionPermit (Unique): References xsfUCFunction.UCFunctionKey
UCRoleKey	Guid	In Index AK_xsfUCFunctionPermit (Unique): References xsfUCRole.UCRoleKey
ReadOK	Bit(1) Default(1)	
InsOK	Bit(1) Default(0)	
UpdOk	Bit(1) Default(0)	
DelOK	Bit(1) Default(0)	
BlanketOK	Bit(1) Default(0)	Special permission one example of a special permission is blanket permission
UpdateTS	Timestamp(8) NULL	

Fields: 9

SPM

xsfUCRole

User Role Definitions

Enumerates Roles defined

UCRoleKey	Guid Default(newid())	Primary Key:1
RoleName	Varchar(50)	Descriptive name In Index AK_xsfUCRole (Unique):1
Description	Varchar(64) NULL	Role description
ConditionsAllowed	Int(10) Default((0))	Bit mask of allowed role filters:DocType - 1; Reference - 2; Project - 4; Specific Doc - 8; Sub Role - 512
AllowUnconditional	Bit(1) Default((1))	
Active	Bit(1) Default((1))	
UpdateTS	Timestamp(8) NULL	

Fields: 7

SPM

xsfUCSubRole

Sub Role

Each row identifies a sub role of the main role

SubRoleKey	Guid Default(newid())	Primary Key:1
UCRoleKey	Guid	In Index AK_xsfUCSubRole (Unique):1 References xsfUCRole.UCRoleKey
SubUCRoleKey	Guid	In Index AK_xsfUCSubRole (Unique):2 References xsfUCRole.UCRoleKey
DocType	Guid NULL	In Index AK_xsfUCSubRole (Unique):3 References xsfDocType.DocTypeKey

Fields: 4

SPM

xsfUIPart

User Interface Parts

Each row defines a User Interface part

PartName	Varchar(64)	Primary Key:1
FilterParam	Varchar(16)	
DisplayName	Varchar(96)	
Description	Varchar(250)	
UIFlags	Int(10) Default((0))	
ViaUI	Bit(1) Default((1))	
Active	Bit(1) Default((1))	
UpdateTS	Timestamp(8)	

Fields: 8

SPM

xsfUIPartItem

User Interface Items

Each row defines a user interface item on a part

PartItemKey	Guid Default(newid())	Primary Key:1
PartName	Varchar(64)	In Index AK_xsfUIPartItem (Unique):1 References xsfUIPart.PartName
ItemName	Varchar(64)	In Index AK_xsfUIPartItem (Unique):2
ItemType	Varchar(8)	
DisplayItem	Varchar(96) NULL	
DataMember	Varchar(64) NULL	
DataField	Varchar(128) NULL	
DefaultLabel	Varchar(64) NULL	
ViaUI	Bit(1)	
DefaultVisible	Bit(1)	
UIFlags	Int(10)	
UpdateTS	Timestamp(8)	

Fields: 12

SPM

xsfUIPartItemHistory

History of UI Part Distributed Defaults

Each row preserves the value of a customization setting at a point in time

CfgHistoryKey	Guid	Primary Key:1 References xsfCustomizationHistory.CfgHistoryKey
PartItemKey	Guid	Primary Key:2
PartName	Varchar(64)	References xsfUIPart.PartName
ItemName	Varchar(64)	
ItemType	Varchar(8)	
DisplayItem	Varchar(96) NULL	
DataMember	Varchar(64) NULL	
DataField	Varchar(128) NULL	
DefaultLabel	Varchar(64) NULL	
ViaUI	Bit(1)	
DefaultVisible	Bit(1)	
UIFlags	Int(10)	
UpdateTS	Timestamp(8)	

Fields: 13

SPM

xsFUser	System Users	
Contacts and Users		
UserKey	Guid Default(newid())	Primary Key:1
UserName	Varchar(60)	Proper name for display - John Smith; replaces ~U placeholder in Salutation
UserLogin	Varchar(47)	Login name In Index AK_xsFUser_login (Unique):1
Password	Varchar(50)	salted and hashed
SortName	Varchar(40)	Smith for Jon Smith; corresponds to ~S salutation placeholder
FamiliarName	Varchar(40) NULL	Jack for Jon Smith; corresponds to ~F salutation placeholder
Salutation	Varchar(50) NULL	Default is Dear ~U; placeholders: ~ F,S,U,C,T,R
Title	Varchar(60) NULL	Free form; replaces ~T placeholder in Salutation
Role	Varchar(50) NULL	Free form; replaces ~R placeholder in Salutation
EMail	Varchar(80) NULL	
phone	Varchar(30) NULL	
fax	Varchar(30) NULL	
cell	Varchar(30) NULL	
pager	Varchar(30) NULL	
Company	Varchar(60) NULL	free form; replaces ~C placeholder in Salutation
address	Varchar(60) NULL	
address2	Varchar(60) NULL	
city	Varchar(30) NULL	
state	Char(2) NULL	
zip	Varchar(10) NULL	
Country	Char(3) NULL	Uses xsfCodeSet
County	Varchar(40) NULL	
TimeZone	Char(3) Default('UNK')	EST, PST, etc
IMService	Char(2) Default('NA')	Instant Messaging Service
IMHandle	Varchar(80) NULL	Instant Messaging Handle
WebURL	Varchar(200) NULL	
VendorID	Char(16) NULL	Vendor Company ID In Index IX_VendorContact (Unique):2
EmployeeID	Char(10) NULL	Weak link to Solomon In Index IX_VendorContact (Unique):3
ContactType	Char(1) Default('0')	Emp, Vendor, Customer, Standard Check (charindex([ContactType], '0ECV')>(0)) In Index IX_VendorContact (Unique):1
RouteVia	Char(1) Default('W')	Web; E-mail; Fax; Hard Copy Check (charindex([RouteVia], 'EFVVH')>(0))
ShowPhone	Smallint(5) Default((1))	1=Phone; 2=Cell; 3=Pager
RouteProxy	Guid NULL	References xsfUCRole.UCRoleKey
DefaultResponsibility	Guid NULL	A role with a responsibility References xsfUCRole.UCRoleKey
ContactCompanyKey	Guid NULL	In Index IX_xsFUser_Company:1
Signature	Guid NULL	
Likeness	Guid NULL	
UseCompanyAddr	Bit(1) Default((0))	When TRUE, trigger updates address if company address changes
ShowNewProjects	Bit(1) Default((1))	When true, new projects are added to the dashboard automatically

sfUser	Bit(1) Default((1))	When True, can log in to dashboard
IsPublic	Bit(1) Default((1))	When true, this contact is published to lookups
Active	Bit(1) Default((1))	When false, hidden from lookups
SolomonUser	Bit(1) Default((0))	When true, is also an integrated DSL User
SlidingExpiration	Bit(1) Default((0))	When TRUE, expiration date is advanced each day the user logs in
PWMustChange	Bit(1) Default((0))	When TRUE, user must change password
PWAging	Bit(1) Default((0))	When TRUE, user can be locked out because of password age
DivisionID	Char(10) Default("")	Default Solomon company
LockoutReason	Varchar(60) NULL	Why user has been blocked
OrgLevel	Int(10) Default((0))	When a user does a contact lookup, they can only see contacts with an OrgLevel <= 1.112 times their own OrgLevel
SynchCheck	Int(10) Default((0))	Checksum of all externally syched data
FailedLoginRun	Int(10) Default((0))	Number of consecutive login failures (reset upon success)
SuppressNotifyUntil	Datetime(23,3) NULL	Email notifications suppressed until this time
LastLogin	Datetime(23,3) NULL	Set by data layer each time the user logs in
LastPWChange	Datetime(23,3) NULL	
LockedOutUntil	Datetime(23,3) NULL	User cannot login until this time
Expiration	Datetime(23,3) NULL	After this date, the user can no longer login
Created	Datetime(23,3) Default(getdate())	
UpdateTS	Timestamp(8) NULL	

Fields: 57

SPM

xsfUserNotify

User Notification Settings

Criteria by which the system can decide if a notification message should be sent

UserNotifyKey	Guid Default(newid())	Primary Key:1
UserKey	Guid	References xsfUser.UserKey
DocTypeKey	Guid	References xsfDocType.DocTypeKey
PriorityOver	Smallint(5) Default((9))	When 1, no emails are sent
RouteVia	Char(1) NULL	
UpdateTs	Timestamp(8) NULL	

Fields: 6

SPM

xsfUserProject

User Project Relationship

Controls appearance of a Project on the User Dashboard and the User in the Project Team

UserProjectKey	Guid Default(newid())	Primary Key:1
UserKey	Guid	In Index AK_UserProject (Unique):1 References xsfUser.UserKey
Project	Char(16)	Reference to Solomon Project In Index AK_UserProject (Unique):2
ContactProject	Varchar(50) NULL	Freeform and Informational. Intended for External contacts project reference
RoleDescription	Varchar(64) NULL	
Responsibility	Guid NULL	Links to a role with a "work" capability In Index AK_UserProject (Unique):3 References xsfUCRole.UCRoleKey
Starting	Datetime(23,3) NULL	
Ending	Datetime(23,3) NULL	
UserList	Bit(1) Default((1))	When true, project shows on users dashboard
TeamList	Bit(1) Default((0))	When true, user shows on Team List
IsPublic	Bit(1) Default((0))	TRUE makes a private contact public within the context of a project; you can NOT make a public contact private
Active	Bit(1) Default((1))	
UpdateTS	Timestamp(8) NULL	

Fields: 13

SPM

xsfUserRole

User Role Membership

Role membership of system users

RoleUserKey	Guid Default(newid())	Primary Key:1
UserKey	Guid	In Index IX_xsfUserRole (Unique):1 References xsfUser.UserKey
UCRoleKey	Guid	In Index IX_xsfUserRole (Unique):2 References xsfUCRole.UCRoleKey
DocType	Guid NULL	In Index IX_xsfUserRole (Unique):3 References xsfDocType.DocTypeKey
DocReference	Guid NULL	In Index IX_xsfUserRole (Unique):4 References xsfDocReference.DocReferenceKey
DocMasterKey	Guid NULL	In Index IX_xsfUserRole (Unique):5 References xsfDocHeader.DocMasterKey
DivisionID	Char(10) NULL	
Project	Char(16) NULL	In Index IX_xsfUserRole (Unique):6
ProgramID	Varchar(24) NULL	
UpdateTS	Timestamp(8) NULL	

Fields: 10

SPM

xsfUserSession

User sessions

Each row defines a user session

UserSessionKey	Guid Default(newid())	Primary Key:1
UserKey	Guid	In Index AK_xsfUserSession (Unique):1 References xsfUser.UserKey
LoginTime	Datetime(23,3) Default(getdate())	In Index AK_xsfUserSession (Unique):2
LogoutTime	Datetime(23,3) NULL	
IISID	Varchar(32)	In Index AK_xsfUserSession (Unique):3
AgentInfo	Varchar(32) NULL	If the session was from full dashboard, Android app, native ie, chrome, etc
TotalRequests	Int(10) NULL	Number of web app requests in this session
TotalMS	Int(10) NULL	Total MS spent by the web app servicing this session
InvalidPW	Bit(1) Default((0))	
UpdateTS	Timestamp(8)	

Fields: 10

SPM

xsfWBPart

Work Breakdown Detail

Each row defines a category that can be used to detail a project task in the work breakdown

WBPartKey	Guid Default(newid())	Primary Key:1
WBPart	Char(16)	In Index AK_xsfWBPart (Unique):1
LongName	Varchar(50)	
WBType	Char(2) Default('EX')	
WBClass	Char(2) NULL	
Sequence	Smallint(5) Default(1000)	
GLAcct	Char(14) NULL	
Note	Varchar(1000) NULL	
BudgetTemplate	Bit(1) Default(1)	
ChangeOrders	Bit(1) Default(1)	
Active	Bit(1) Default(1)	
UpdateTS	Timestamp(8) NULL	

Fields: 12

SPM

xsfWeatherLocation

Weather Report Locations

Each row identifies a combination of location and provider

WeatherLocationKey	Guid Default(newid())	Primary Key:1
LocationCode	Varchar(10)	Typically a zip code In Index AK_xsfWeatherLocation (Unique):1
Location	Varchar(80)	City, State In Index AK_xsfWeatherLocation (Unique):2
RecordedAt	Varchar(80)	The weather stations actual location, if known and different than Location In Index AK_xsfWeatherLocation (Unique):3
Provider	Varchar(80)	The web service provider In Index AK_xsfWeatherLocation (Unique):4

Fields: 5

SPM

xsfWeatherReading

Weather Reading Data

Each row contains data from a reading

WeatherInfoKey	Guid Default(newid())	Primary Key:1
WeatherLocationKey	Guid	In Index AK_xsfWeatherReading (Unique):1 References xsfWeatherLocation.WeatherLocationKey
Reported	Datetime(23,3)	In Index AK_xsfWeatherReading (Unique):2
Conditions	Varchar(50)	Short forecast summary, such as Chance of Snow/Rain
Visibility	Smallint(5) Default(0)	in miles
Temperature	Smallint(5) Default(0)	in degrees F
FeelsLike	Smallint(5) Default(0)	in degrees F
Dewpoint	Smallint(5) Default(0)	in degrees F
HumidityPct	Smallint(5) Default(0)	
WindDirection	Char(6) Default("")	
Wind	Smallint(5) Default(0)	in MPH
Barometer	Decimal(5,2) Default(0)	in inches of mercury

Fields: 12

SPM

xsfWorkflowLib

Workflow Script Library

Each row defines a workflow script that can be mapped to a triggering event

WorkflowScriptKey	Guid Default(newid())	Primary Key:1
WorkflowScriptName	Varchar(50)	In Index AK_xsfWorkflowLib:1
WorkflowScript	Varchar(-1)	
IsDistributed	Bit(1) Default((0))	
Active	Bit(1) Default((1))	
UpdateTS	Timestamp(8)	

Fields: 6

Data Dictionary - Field Index

Wednesday, June 05, 2013

2:03 PM

Field	Type	Name	Description
Accessed	(datetime, 23)		
	Table	xsfFileAccess AK_xsfFileAccess_ByFile (Unique)	File Access Log
AccessLevel	(char, 1)		
	Table	xsfFileAttach	Document Attachment List
	Table	xsfRouteList	Document Route Detail
AccountCategory	(char, 16)		
	Table	xsfChgMarkup AK_Markup (Unique):3	Change Order Markup
	Table	xsfDocItemTask IX_xsfDocItemTask:3	Revenue and Expense Details for an Item
	Table	xsfForecast AK_xsfForecast (Unique):3	Forecast
Acct	(char, 10)		
	Table	xsfAPInfo	AP Doc Summary by Project
ActAmount	(money, 19)		
	Table	xsfFSnapshotByPeriod	Project Budget by Period Snapshot
Acted	(datetime, 23)		
	Table	xsfRoute	Routed Document User Detail
ActFinish	(datetime, 23)		
	Table	xsfDocDates	Document Dates
	Table	xsfProjectWBS	Project Work Breakdown
ActionText	(varchar, 128)		
	Table	xsfDashboardMenu	Spitfire Dashboard Menu
Active	(bit, 1)		
	Table	xsfAlertSubscription	Alert Subscriptions
	Table	xsfAlertType	Alert Types
	Table	xsfAllocation	Allocations and Markups

Field	Type	Name	Description
Active	(bit, 1)		
	Table	xsfCodeList	Coded Choices
	Table	xsfCodeListHistory	History of Codes
	Table	xsfCompanyCSIMap	Company CSI Map
	Table	xsfCompliance	Vendor Subcontract Compliance Items
	Table	xsfComplianceType	Compliance Type
	Table	xsfComplianceTypeMap	Maps Compliance Type to Vendor and Commitments
	Table	xsfCSI	CSI Definition
	Table	xsfDashboardMenu	Spitfire Dashboard Menu
	Table	xsfDivision	Company Division List
	Table	xsfDocAlert	Document Alert
	Table	xsfDocDateType	Date Types
	Table	xsfDocReference	Document Catagorical Reference
	Table	xsfDocSession	User Document Sessions
	Table	xsfDocTemplate	Word Document Template
	Table	xsfDocType	Routable Document Types
	Table	xsfDocTypeSubcodes	Type Dependant Codes
	Table	xsfDocTypeSubcodesHistory	History of Doc Type Specific Codes
	Table	xsfDocWorkflow	Document Workflow Events
	Table	xsfEventAgent	Event Notification Consumer Agents
	Table	xsfEventSubscription	Event Subscriptions
	Table	xsfPartConfig	User Interface Part Customization
	Table	xsfPartConfigHistory	History of UI Part customizations
	Table	xsfProgram	Project Programs
	Table	xsfProgramProjectMap	Program Project List
	Table	xsfProject	Project Information
	Table	xsfReference	CSI and/or Unifomat
	Table	xsfRegionMap	Company Region Map
	Table	xSfRouteListMaster	Document Route List
	Table	xsfRouteSpecial	Document Route Selection Criteria
	Table	xsfRuleItemValidation	Rule Item Validation
	Table	xsfStaticResource	Protected System Resources
	Table	xsfUCFunctionMap	Maps Capabilities to affected UI Parts
	Table	xsfUCRole	User Role Definitions
	Table	xsfUIPart	User Interface Parts
	Table	xsfUser	System Users
	Table	xsfUserProject	User Project Relationship

Data Dictionary - Field Index

Wednesday, June 05, 2013

2:03 PM

Field	Type	Name	Description
Active	(bit, 1)		
	Table	xsfWBPart	Work Breakdown Detail
	Table	xsfWorkflowLib	Workflow Script Library
ActStart	(datetime, 23)		
	Table	xsfDocDates	Document Dates
	Table	xsfProjectWBS	Project Work Breakdown
ActualCP	(money, 19)		
	Table	xsfForecast	Forecast
ActualCY	(money, 19)		
	Table	xsfForecast	Forecast
ActualPP	(money, 19)		
	Table	xsfForecast	Forecast
ActualPY	(money, 19)		
	Table	xsfForecast	Forecast
ActualToDate	(money, 19)		
	Table	xsfForecast	Forecast
ActualUnits	(numeric, 17)		
	Table	xsfForecast	Forecast
ActualUnitsCP	(money, 19)		
	Table	xsfForecast	Forecast
ActualUnitsCY	(money, 19)		
	Table	xsfForecast	Forecast
ActualUnitsPP	(money, 19)		
	Table	xsfForecast	Forecast

Data Dictionary - Field Index

Wednesday, June 05, 2013

2:03 PM

Field	Type	Name	Description
ActualUnitsPY	(money, 19)		
	Table	xsfForecast	Forecast
Addr1	(varchar, 60)		
	Table	xsfDivision	Company Division List
	Table	xsfDocAddr	Address
	Table	xsfProject	Project Information
Addr2	(varchar, 60)		
	Table	xsfDivision	Company Division List
	Table	xsfDocAddr	Address
	Table	xsfProject	Project Information
address	(varchar, 60)		
	Table	xsfUser	System Users
address2	(varchar, 60)		
	Table	xsfUser	System Users
AddrType	(char, 1)		
	Table	xsfDocAddr	Address
		IX_xsfDocAddr (Unique):2	
AgentInfo	(varchar, 32)		
	Table	xsfUserSession	User sessions
AgentName	(varchar, 32)		
	Table	xsfEventAgent	Event Notification Consumer Agents
		AK_xsfEventAgent (Unique):1	
AgentType	(char, 2)		
	Table	xsfEventAgent	Event Notification Consumer Agents
AgentURI	(varchar, 300)		
	Table	xsfEventAgent	Event Notification Consumer Agents

Data Dictionary - Field Index

Wednesday, June 05, 2013

2:03 PM

Field	Type	Name	Description
Alert	(bit, 1)		
	Table	xsfComplianceType	Compliance Type
	Table	xsfDocDateType	Date Types
AlertDate	(datetime, 23)		
	Table	xsfDocAlert	Document Alert
AlertDefKey	(uniqueidentifier, 16)		
	Table	xsfAlertSubscription	Alert Subscriptions
Alerted	(datetime, 23)		
	Table	xsfRoute	Routed Document User Detail
AlertKey	(uniqueidentifier, 16)		
	Table	xsfAlert	User Alerts List
		Primary Key:1	
AlertName	(varchar, 50)		
	Table	xsfAlertType	Alert Types
		IX_xsfAlertType:2	
	Table	xsfDocAlert	Document Alert
		IX_xsfDocAlert:2	
Alerts	(bit, 1)		
	Table	xsfCompliance	Vendor Subcontract Compliance Items
AlertSubscriptionKey	(uniqueidentifier, 16)		
	Table	xsfAlertSubscription	Alert Subscriptions
		Primary Key:1	
AlertText	(varchar, 2000)		
	Table	xsfAlert	User Alerts List
AlertToRole	(uniqueidentifier, 16)		
	Table	xsfDocAlert	Document Alert

Data Dictionary - Field Index

Wednesday, June 05, 2013
2:03 PM

Field	Type	Name	Description
AlertTypeKey	(uniqueidentifier, 16)		
	Table	xsfAlertType Primary Key:1	Alert Types
	Table	xsfDocAlert	Document Alert
AllocationAmount	(money, 19)		
	Table	xsfAllocation	Allocations and Markups
AllocationKey	(uniqueidentifier, 16)		
	Table	xsfAllocation Primary Key:1	Allocations and Markups
AllocationPct	(numeric, 7)		
	Table	xsfAllocation	Allocations and Markups
AllowAdd	(bit, 1)		
	Table	xsfCodeSet	Code Sets
	Table	xsfCodeSetHistory	History of Code Sets
AllowAmount	(bit, 1)		
	Table	xsfComplianceType	Compliance Type
AllowCarrier	(bit, 1)		
	Table	xsfComplianceType	Compliance Type
AllowDescription	(bit, 1)		
	Table	xsfComplianceType	Compliance Type
AllowEdit	(bit, 1)		
	Table	xsfCodeSet	Code Sets
	Table	xsfCodeSetHistory	History of Code Sets
AllowEffective	(bit, 1)		
	Table	xsfComplianceType	Compliance Type

Data Dictionary - Field Index

Wednesday, June 05, 2013

2:03 PM

Field	Type	Name	Description
AllowExpiration	(bit, 1)		
	Table	xsfComplianceType	Compliance Type
AllowLeadDays	(bit, 1)		
	Table	xsfComplianceType	Compliance Type
AllowMultiple	(bit, 1)		
	Table	xsfComplianceType	Compliance Type
AllowNextSet	(bit, 1)		
	Table	xsfCodeSet	Code Sets
	Table	xsfCodeSetHistory	History of Code Sets
AllowProof	(bit, 1)		
	Table	xsfComplianceType	Compliance Type
AllowRekurs	(bit, 1)		
	Table	xsfComplianceType	Compliance Type
AllowsLeadTime	(bit, 1)		
	Table	xsfAlertType	Alert Types
AllowsRecur	(bit, 1)		
	Table	xsfAlertType	Alert Types
AllowTitles	(bit, 1)		
	Table	xsfFlexKeySegments	Flex Key Segment Definition
AllowUnconditional	(bit, 1)		
	Table	xsfUCRole	User Role Definitions
AltFileContact	(uniqueidentifier, 16)		
	Table	xsfFile	Stored File
Amount	(money, 19)		
	Table	xsfAttribute	Document Attributes

Data Dictionary - Field Index

Wednesday, June 05, 2013
2:03 PM

Field	Type	Name	Description
Amount	(money, 19)		
	Table	xsfCompliance	Vendor Subcontract Compliance Items
	Table	xsfMeetingAttendee	Meeting Attendee
	Table	xsfPjPeriodRevBD	Project Budget by Period Revision Detail
	Table	xsfProjectRevisionWB	Project Revision Detail
AmountHi	(money, 19)		
	Table	xsfRouteSpecial	Document Route Selection Criteria
AmountLo	(money, 19)		
	Table	xsfRouteSpecial	Document Route Selection Criteria
Approved	(datetime, 23)		
	Table	xsfFileVersionInfo	Stored File Version Attributes
ApprovedBy	(uniqueidentifier, 16)		
	Table	xsfFileVersionInfo	Stored File Version Attributes
		IX_xsfFileVersionInfo_Approver:1	
ApprovedCO	(money, 19)		
	Table	xsfForecast	Forecast
ApprovedCORevenue	(money, 19)		
	Table	xsfForecast	Forecast
ApprovedSCO	(money, 19)		
	Table	xsfForecast	Forecast
ApproxDeltas	(int, 10)		
	Table	xsfDocSession	User Document Sessions
	Table	xsfDocWriteTx	Document Save Transaction Header
ApproxSaveTx	(int, 10)		
	Table	xsfDocSession	User Document Sessions

Data Dictionary - Field Index

Wednesday, June 05, 2013

2:03 PM

Field	Type	Name	Description
ArchitectInitialNumber	(varchar, 30)		
	Table	xsfDocItem	Document Item List
ArchitectItemNumber	(varchar, 30)		
	Table	xsfDocItem	Document Item List
ArchiveDBKey	(uniqueidentifier, 16)		
	Table	xsfArchiveDB Primary Key:1	Archive Databases for static catalog content
	Table	xsfFileVersionInfo	Stored File Version Attributes
ArchiveDBN	(varchar, 50)		
	Table	xsfArchiveDB AK_xsfArchiveDB (Unique):1	Archive Databases for static catalog content
ArchProject	(char, 16)		
	Table	xsfDocRevision	Document Revision
Area	(int, 10)		
	Table	xsfDocHeader	Document Header
AsOf	(datetime, 23)		
	Table	xsfFileRStatus IX_FileStatus:2	Store File Content Recognition Status
	Table	xsfRouteContentPending AK_xsfRouteContentPending:2	Catalog content to be updated for routing
AsSubscribed	(bit, 1)		
	Table	xsfDocAlert	Document Alert
AtSourceContact	(bit, 1)		
	Table	xsfRouteList	Document Route Detail
AttachedDocMaster	(uniqueidentifier, 16)		
	Table	xsfFileAttach IX_xsfFileAttachDoc:1	Document Attachment List

Data Dictionary - Field Index

Wednesday, June 05, 2013
2:03 PM

Field	Type	Name	Description
AttachedRevID	(smallint, 5) Table	xsfFileAttach	Document Attachment List
AttachSeq	(smallint, 5) Table	xsfFileAttach	Document Attachment List
AttendeeKey	(uniqueidentifier, 16) Table	xsfMeetingAttendee Primary Key:1	Meeting Attendee
AttendeeName	(varchar, 50) Table	xsfMeetingAttendee IX_xsfMeetingAttendee:2	Meeting Attendee
AttrOwnerKey	(uniqueidentifier, 16) Table	xsfAttribute AK_xsfAttribute (Unique):1	Document Attributes
AttrType	(varchar, 8) Table	xsfAttribute AK_xsfAttribute (Unique):2	Document Attributes
AttrValue	(varchar, 8) Table	xsfAttribute AK_xsfAttribute (Unique):3	Document Attributes
AutoAdd	(bit, 1) Table	xsfCSI	CSI Definition
AutoControl	(bit, 1) Table	xsfComplianceType	Compliance Type
AutoRoute	(bit, 1) Table	xsfRouteSpecial	Document Route Selection Criteria

Data Dictionary - Field Index

Wednesday, June 05, 2013

2:03 PM

Field	Type	Name	Description
AutoTitled	(bit, 1)		
	Table	xsfDocHeader	Document Header
AuxData	(varchar, 250)		
	Table	xsfPartConfig	User Interface Part Customization
	Table	xsfPartConfigHistory	History of UI Part customizations
Barometer	(decimal, 5)		
	Table	xsfWeatherReading	Weather Reading Data
BatNbr	(char, 10)		
	Table	xsfAPIInfo Primary Key:2	AP Doc Summary by Project
BCS	(int, 10)		
	Table	xsfContentHistory	Detailed History of Table Content
Billable	(bit, 1)		
	Table	xsfDocItem	Document Item List
BinData	(varbinary, -1)		
	Table	xsfDocTemplate	Word Document Template
	Table	xsfFileMarkup	File Version Markups and Resources
	Table	xsfFileVersion	Stored File Version
	Table	xsfPersistedData	Transient System Data
	Table	xsfRouteTransmittal	Extends a Route Entry with a Transmittal
BinSize	(int, 10)		
	Table	xsfFileVersion	Stored File Version
	Table	xsfFileVersionInfo	Stored File Version Attributes
BinType	(char, 8)		
	Table	xsfPersistedData	Transient System Data
BinType	(varchar, 8)		
	Table	xsfDocTemplate	Word Document Template

Data Dictionary - Field Index

Wednesday, June 05, 2013

2:03 PM

Field	Type	Name	Description
BinType	(varchar, 8)		
	Table	xsfRouteTransmittal	Extends a Route Entry with a Transmittal
BlanketOK	(bit, 1)		
	Table	xsfItemPermit	Item Permission settings
	Table	xsfUCFunctionPermit	Role Permission Settings
Bond	(money, 19)		
	Table	xsfDocRevision	Document Revision
BondRate	(decimal, 9)		
	Table	xsfDocRevision	Document Revision
Boundary	(datetime, 23)		
	Table	xsfPersistedData	Transient System Data
		IX_xsfPersistedData_ByBoundary:1	
BTDRevenue	(money, 19)		
	Table	xsfForecast	Forecast
BudgetedRevenue	(money, 19)		
	Table	xsfForecast	Forecast
BudgetRevFlag	(char, 4)		
	Table	xsfDocHeader	Document Header
BudgetRevision	(money, 19)		
	Table	xsfForecast	Forecast
BudgetRevisionKey	(uniqueidentifier, 16)		
	Table	xsfProjectRevision	Project Revision
		Primary Key:1	
	Table	xsfProjectRevisionWB	Project Revision Detail
		IX_xsfProjectRevisionWB (Unique)	Ref: xsfProjectRevision

Data Dictionary - Field Index

Wednesday, June 05, 2013

2:03 PM

Field	Type	Name	Description
BudgetTemplate	(bit, 1)		
	Table	xsfWBPart	Work Breakdown Detail
BuiltIn	(bit, 1)		
	Table	xsfAlertType	Alert Types
ByDocMasterKey	(uniqueidentifier, 16)		
	Table	xsfFile	Stored File
ByProg	(char, 6)		
	Table	xsfProjectRevision	Project Revision
ByUser	(uniqueidentifier, 16)		
	Table	xsfRouteTransmittal	Extends a Route Entry with a Transmittal
		See also: xsfUser.UserKey	
ByUser	(varchar, 47)		
	Table	xsfProjectRevision	Project Revision
Carrier	(varchar, 50)		
	Table	xsfCompliance	Vendor Subcontract Compliance Items
Cataloged	(datetime, 23)		
	Table	xsfFileVersion	Stored File Version
	Table	xsfFileVersionInfo	Stored File Version Attributes
CatType	(uniqueidentifier, 16)		
	Table	xsfFile	Stored File
cell	(varchar, 30)		
	Table	xsfUser	System Users
CertificateReqd	(bit, 1)		
	Table	xsfCompliance	Vendor Subcontract Compliance Items

Data Dictionary - Field Index

Wednesday, June 05, 2013
2:03 PM

Field	Type	Name	Description
Certification	(varchar, 8)		
	Table	xsfDocItem	Document Item List
CfgHistoryKey	(uniqueidentifier, 16)		
	Table	xsfCodeListHistory	History of Codes
		Primary Key:1	Ref: xsfCustomizationHistory
	Table	xsfCodeSetHistory	History of Code Sets
		Primary Key:1	Ref: xsfCustomizationHistory
	Table	xsfCustomizationHistory	Customization History Snapshot Header
		Primary Key:1	
	Table	xsfDocTypeSubcodesHistory	History of Doc Type Specific Codes
	Primary Key:1	Ref: xsfCustomizationHistory	
Table	xsfPartConfigHistory	History of UI Part customizations	
	Primary Key:1	Ref: xsfCustomizationHistory	
Table	xsfRuleItemHistory	History of Rule settings	
	AK_xsfRuleItemHistory (Unique):2	Ref: xsfCustomizationHistory	
Table	xsfUIPartItemHistory	History of UI Part Distributed Defaults	
	Primary Key:1	Ref: xsfCustomizationHistory	
ChangeAccountProduction Units	(money, 19)		
	Table	xsfForecast	Forecast
ChangeAmount	(money, 19)		
	Table	xsfForecast	Forecast
ChangeAmountNet	(money, 19)		
	Table	xsfFSnapshotByPeriod	Project Budget by Period Snapshot
ChangeBudgetAmount	(money, 19)		
	Table	xsfForecast	Forecast
ChangeBudgetType	(smallint, 5)		
	Table	xsfForecast	Forecast
		IX_xsfForecast_Chain:5	

Data Dictionary - Field Index

Wednesday, June 05, 2013

2:03 PM

Field	Type	Name	Description
ChangeBudgetUnit	(money, 19) Table	xsfForecast	Forecast
ChangeByUserKey	(uniqueidentifier, 16) Table	xsfForecast IX_xsfForecast_Chain:4	Forecast
ChangeDollarsPerUnit	(money, 19) Table	xsfForecast	Forecast
ChangeFACorFTC	(smallint, 5) Table	xsfForecast IX_xsfForecast_Chain:6	Forecast
ChangeHrsPerUnit	(money, 19) Table	xsfForecast	Forecast
ChangeOrder	(varchar, 16) Table	xsfProjectRevision	Project Revision
ChangeOrders	(bit, 1) Table	xsfWBPart	Work Breakdown Detail
ChangePercentComplete	(numeric, 5) Table	xsfForecast	Forecast
ChangeProductionRate	(money, 19) Table	xsfForecast	Forecast
ChangeProductivityFactor	(money, 19) Table	xsfForecast	Forecast
ChangeTaskProductionUnits	(money, 19) Table	xsfForecast	Forecast

Data Dictionary - Field Index

Wednesday, June 05, 2013

2:03 PM

Field	Type	Name	Description
ChangeType	(int, 10)		
	Table	xsfProjectRevisionWB	Project Revision Detail
ChangeType	(smallint, 5)		
	Table	xsfSnapshotByPeriod	Project Budget by Period Snapshot
ChangeUnitsPerHr	(money, 19)		
	Table	xsfForecast	Forecast
ChangeWhen	(datetime, 23)		
	Table	xsfDocWriteTx AK_xsfDocWriteTx (Unique):2	Document Save Transaction Header
ChangeWorkingAmountGL	(money, 19)		
	Table	xsfForecast	Forecast
ChangeWorkingFAC	(money, 19)		
	Table	xsfForecast	Forecast
ChangeWorkingFACUnits	(money, 19)		
	Table	xsfForecast	Forecast
ChangeWorkingPercentComplete	(money, 19)		
	Table	xsfForecast	Forecast
ChangeWorkingProdUnitGL	(money, 19)		
	Table	xsfForecast	Forecast
ChangeWorkingUnitGL	(money, 19)		
	Table	xsfForecast	Forecast
ChargesToDate	(money, 19)		
	Table	xsfForecast	Forecast

Data Dictionary - Field Index

Wednesday, June 05, 2013

2:03 PM

Field	Type	Name	Description
CheckAmount	(bit, 1)		
	Table	xsfComplianceType	Compliance Type
CheckCompliance	(bit, 1)		
	Table	xsfDocType	Routable Document Types
CheckedIn	(datetime, 23)		
	Table	xsfFileCheckout	File Checkout Information
CheckedOut	(datetime, 23)		
	Table	xsfFileCheckout	File Checkout Information
CheckoutKey	(uniqueidentifier, 16)		
	Table	xsfFileCheckout Primary Key:1	File Checkout Information
ChgMarkupKey	(uniqueidentifier, 16)		
	Table	xsfChgMarkup Primary Key:1	Change Order Markup
City	(varchar, 30)		
	Table	xsfDivision	Company Division List
	Table	xsfDocAddr	Address
	Table	xsfProject	Project Information
Closed	(datetime, 23)		
	Table	xsfDocHeader	Document Header
		IX_DocByType:0	
Code	(varchar, 8)		
	Table	xsfDocTypeSubcodes	Type Dependant Codes
		AK_xsfDocSubtype (Unique):3	
	Table	xsfDocTypeSubcodesHistory	History of Doc Type Specific Codes

Data Dictionary - Field Index

Wednesday, June 05, 2013
2:03 PM

Field	Type	Name	Description
Code	(varchar, 16)		
	Table	xsfCodeList AK_CodeList (Unique):2	Coded Choices
	Table	xsfCodeListHistory	History of Codes
CodeFlag	(bit, 1)		
	Table	xsfDocTypeSubcodes	Type Dependant Codes
	Table	xsfDocTypeSubcodesHistory	History of Doc Type Specific Codes
CodeFlagLabel	(varchar, 24)		
	Table	xsfCodeSet	Code Sets
	Table	xsfCodeSetHistory	History of Code Sets
CodeLike	(varchar, 32)		
	Table	xsfDocWorkflow AK_xsfDocWorkflow:3	Document Workflow Events
CodeSetKey	(uniqueidentifier, 16)		
	Table	xsfCodeSet Primary Key:1	Code Sets
	Table	xsfCodeSetHistory Primary Key:2	History of Code Sets
CodeSize	(smallint, 5)		
	Table	xsfCodeSet	Code Sets
	Table	xsfCodeSetHistory	History of Code Sets
CodeValueKey	(uniqueidentifier, 16)		
	Table	xsfCodeList Primary Key:1	Coded Choices
	Table	xsfCodeListHistory Primary Key:2	History of Codes
Comment	(varchar, 64)		
	Table	xsfRegionMap	Company Region Map

Data Dictionary - Field Index

Wednesday, June 05, 2013

2:03 PM

Field	Type	Name	Description
Comment	(varchar, 128)		
	Table	xsfContentHistoryList	Index of Content History Snapshots
Comments	(varchar, 700)		
	Table	xsfRuleValueType	Rule Value Type
CommittedToDate	(money, 19)		
	Table	xsfForecast	Forecast
Company	(varchar, 60)		
	Table	xsfDocAddr	Address
	Table	xsfProject	Project Information
	Table	xsfUser	System Users
CompanyName	(varchar, 60)		
	Table	xsfContactCompany	Contact Company
completed	(datetime, 23)		
	Table	xsfDocItem	Document Item List
	Table	xsfFileAccess	File Access Log
ComplianceItemKey	(uniqueidentifier, 16)		
	Table	xsfCompliance Primary Key:1	Vendor Subcontract Compliance Items
ComplianceName	(varchar, 50)		
	Table	xsfComplianceType AK_xsfComplianceType (Unique):1	Compliance Type
ComplianceTypeKey	(uniqueidentifier, 16)		
	Table	xsfCompliance	Vendor Subcontract Compliance Items
	Table	xsfComplianceType Primary Key:1	Compliance Type
	Table	xsfComplianceTypeMap AK_xsfComplianceTypeMap (Unique)	Maps Compliance Type to Vendor and Commitments Ref: xsfComplianceType

Data Dictionary - Field Index

Wednesday, June 05, 2013
2:03 PM

Field	Type	Name	Description
Complied	(bit, 1)		
	Table	xsfCompliance	Vendor Subcontract Compliance Items
CompTypeMapKey	(uniqueidentifier, 16)		
	Table	xsfComplianceTypeMap	Maps Compliance Type to Vendor and Commitments
		Primary Key:1	
Conditions	(varchar, 50)		
	Table	xsfWeatherReading	Weather Reading Data
ConditionsAllowed	(int, 10)		
	Table	xsfUCRole	User Role Definitions
Confidential	(bit, 1)		
	Table	xsfDocHeader	Document Header
ContactCompanyKey	(uniqueidentifier, 16)		
	Table	xsfCompanyCSIMap	Company CSI Map
		IX_xsfCompanyCSIMap (Unique):1	
	Table	xsfContactCompany	Contact Company
		Primary Key:1	
	Table	xsfRegionMap	Company Region Map
		AK_RegionMap (Unique):1	
	Table	xsfUser	System Users
		IX_xsfUser_Company:1	
ContactProject	(varchar, 50)		
	Table	xsfUserProject	User Project Relationship
ContactType	(char, 1)		
	Table	xsfUser	System Users
		IX_VendorContact (Unique):1	

Data Dictionary - Field Index

Wednesday, June 05, 2013

2:03 PM

Field	Type	Name	Description
Container	(varchar, 50)		
	Table	xsfPartConfig IX_xsfPartConfig:4	User Interface Part Customization
	Table	xsfPartConfigHistory	History of UI Part customizations
ContainerKey	(uniqueidentifier, 16)		
	Table	xsfContainerPermitCache AK_xsfContainerPermitCache (Uniq	Preresolved Container Permissions by User
	Table	xsfDashboardMenu AK_xsfDashboardMenu (Unique):1	Spitfire Dashboard Menu
	Table	xsfDocRevItem	Document Revision Items
	Table	xsfEventSubscription	Event Subscriptions
	Table	xsfFile AK_xsfFile:1	Stored File
ContentAsOf	(datetime, 23)		
	Table	xsfContentHistory Primary Key:1	Detailed History of Table Content Ref: xsfContentHistoryList
	Table	xsfContentHistoryList Primary Key:1	Index of Content History Snapshots
ContentSeq	(int, 10)		
	Table	xsfRoutedContent AK_xsfRoutedContent:5	Enumerates content of document when routed to spec
ContentSet	(datetime, 23)		
	Table	xsfRouteStep	Document Route Steps (Stage and Sequence)
ContractType	(char, 4)		
	Table	xsfProjectWBS	Project Work Breakdown
ContractType	(varchar, 8)		
	Table	xsfAllocation	Allocations and Markups
	Table	xsfDocHeader	Document Header

Data Dictionary - Field Index

Wednesday, June 05, 2013

2:03 PM

Field	Type	Name	Description
Cost	(money, 19)		
	Table	xsfComment	Comment
CostImpact	(money, 19)		
	Table	xsfDocRevision	Document Revision
CostingMethod	(char, 2)		
	Table	xsfForecast	Forecast
	Table	xsfProjectWBS	Project Work Breakdown
CostType	(char, 2)		
	Table	xsfDocItemTask	Revenue and Expense Details for an Item
Country	(char, 3)		
	Table	xsfDivision	Company Division List
	Table	xsfUser	System Users
County	(varchar, 40)		
	Table	xsfProject	Project Information
	Table	xsfUser	System Users
Created	(datetime, 23)		
	Table	xsfAlert	User Alerts List
		IX_xsfAlert:3	
	Table	xsfArchiveDB	Archive Databases for static catalog content
	Table	xsfComment	Comment
	Table	xsfCompanyCSIMap	Company CSI Map
	Table	xsfContactCompany	Contact Company
	Table	xsfCSI	CSI Definition
	Table	xsfDocItemTask	Revenue and Expense Details for an Item
	Table	xsfDocRevision	Document Revision
	Table	xsfDocRevItem	Document Revision Items
	Table	xsfDocTemplate	Word Document Template
	Table	xsfFileAttach	Document Attachment List
	Table	xsfFileMarkup	File Version Markups and Resources
		IX_xsfFileMarkup:3	

Data Dictionary - Field Index

Wednesday, June 05, 2013
2:03 PM

Field	Type	Name	Description
Created	(datetime, 23)		
	Table	xsfItemContainer	Heirachical Container
	Table	xsfPersistedData	Transient System Data
	Table	xsfPjPeriodRev	Project Budget by Period Revision Header
	Table	xsfProgramProjectMap	Program Project List
	Table	xsfProjectRevision	Project Revision
		IX_xsfProjectRevision_Source:0	
	Table	xsfRegion	Region Definition
	Table	xsfRegionMap	Company Region Map
	Table	xsfRouteStep	Document Route Steps (Stage and Sequence)
	Table	xsfRouteTransmittal	Extends a Route Entry with a Transmittal
	Table	xsfUser	System Users
csAmount	(money, 19)		
	Table	xsfDocItemTask	Revenue and Expense Details for an Item
	Table	xsfDocRevision	Document Revision
	Table	xsfInclusion	Include and Exclusion Items
	Table	xsfMeetingAttendee	Meeting Attendee
csCheck	(bit, 1)		
	Table	xsfDocItemTask	Revenue and Expense Details for an Item
	Table	xsfDocRevision	Document Revision
	Table	xsfInclusion	Include and Exclusion Items
	Table	xsfMeetingAttendee	Meeting Attendee
csDate	(datetime, 23)		
	Table	xsfDocItemTask	Revenue and Expense Details for an Item
	Table	xsfDocRevision	Document Revision
	Table	xsfInclusion	Include and Exclusion Items
	Table	xsfMeetingAttendee	Meeting Attendee
CSICode	(varchar, 6)		
	Table	xsfCompanyCSIMap	Company CSI Map
		IX_xsfCompanyCSIMap (Unique):2	Ref: xsfCSI
	Table	xsfCSI	CSI Definition
		AK_CSI (Unique):1	

Data Dictionary - Field Index

Wednesday, June 05, 2013

2:03 PM

Field	Type	Name	Description
CSIDescription	(varchar, 64)		
	Table	xsfCSI	CSI Definition
CSIKey	(uniqueidentifier, 16)		
	Table	xsfCSI Primary Key:1	CSI Definition
CSIMapKey	(uniqueidentifier, 16)		
	Table	xsfCompanyCSIMap Primary Key:1	Company CSI Map
csString016	(varchar, 16)		
	Table	xsfDocItemTask	Revenue and Expense Details for an Item
	Table	xsfDocRevision	Document Revision
	Table	xsfInclusion	Include and Exclusion Items
	Table	xsfMeetingAttendee	Meeting Attendee
csString030	(varchar, 30)		
	Table	xsfDocItemTask	Revenue and Expense Details for an Item
	Table	xsfDocRevision	Document Revision
	Table	xsfInclusion	Include and Exclusion Items
	Table	xsfMeetingAttendee	Meeting Attendee
csString060	(varchar, 60)		
	Table	xsfDocItemTask	Revenue and Expense Details for an Item
	Table	xsfDocRevision	Document Revision
	Table	xsfInclusion	Include and Exclusion Items
	Table	xsfMeetingAttendee	Meeting Attendee
CurrentBudget	(money, 19)		
	Table	xsfForecast	Forecast
CustomerID	(char, 16)		
	Table	xsfDocTemplate	Word Document Template

Data Dictionary - Field Index

Wednesday, June 05, 2013

2:03 PM

Field	Type	Name	Description
CWRetention	(money, 19)		
	Table	xsfDocItem	Document Item List
	Table	xsfDocRevision	Document Revision
czUDSAmt1	(money, 19)		
	Table	xsfForecast	Forecast
czUDSAmt2	(money, 19)		
	Table	xsfForecast	Forecast
czUDSAmt3	(money, 19)		
	Table	xsfForecast	Forecast
czUDSText1	(varchar, 255)		
	Table	xsfForecast	Forecast
czUDSText2	(varchar, 255)		
	Table	xsfForecast	Forecast
DataField	(varchar, 128)		
	Table	xsfUIPartItem	User Interface Items
	Table	xsfUIPartItemHistory	History of UI Part Distributed Defaults
DataHash	(char, 32)		
	Table	xsfFileVersionInfo	Stored File Version Attributes
		IX_xsfFileVersionHash:1	
DataMember	(varchar, 64)		
	Table	xsfUIPartItem	User Interface Items
	Table	xsfUIPartItemHistory	History of UI Part Distributed Defaults
DataMethod	(char, 4)		
	Table	xsfFileMarkup	File Version Markups and Resources
	Table	xsfFileVersion	Stored File Version
	Table	xsfPersistedData	Transient System Data

Data Dictionary - Field Index

Wednesday, June 05, 2013

2:03 PM

Field	Type	Name	Description
DaysApproved	(smallint, 5)		
	Table	xsfDocRevision	Document Revision
DaysRequested	(smallint, 5)		
	Table	xsfDocRevision	Document Revision
DeclaredPercentComplete	(money, 19)		
	Table	xsfForecast	Forecast
DeclaredUnits	(money, 19)		
	Table	xsfForecast	Forecast
DefaultInclude	(char, 1)		
	Table	xsfDocTemplate	Word Document Template
DefaultLabel	(varchar, 64)		
	Table	xsfUIPartItem	User Interface Items
	Table	xsfUIPartItemHistory	History of UI Part Distributed Defaults
DefaultNote	(varchar, 500)		
	Table	xsfRouteList	Document Route Detail
DefaultResponsibility	(uniqueidentifier, 16)		
	Table	xsfUser	System Users
		See also: xsfUCRole.UCRoleKey	
DefaultStatus	(char, 1)		
	Table	xsfRouteList	Document Route Detail
DefaultVia	(char, 1)		
	Table	xsfRouteList	Document Route Detail
DefaultVisible	(bit, 1)		
	Table	xsfUIPartItem	User Interface Items
	Table	xsfUIPartItemHistory	History of UI Part Distributed Defaults

Data Dictionary - Field Index

Wednesday, June 05, 2013

2:03 PM

Field	Type	Name	Description
DelOK	(bit, 1)		
	Table	xsfItemPermit	Item Permission settings
	Table	xsfUCFunctionPermit	Role Permission Settings
Depth	(tinyint, 3)		
	Table	xsfDocWriteTxFact	Document Save Facts
Descript	(nvarchar, 50)		
	Table	xsfCodeList	Coded Choices
	Table	xsfCodeListHistory	History of Codes
Description	(varchar, -1)		
	Table	xsfDocItem	Document Item List
	Table	xsfProject	Project Information
Description	(varchar, 50)		
	Table	xsfAlert	User Alerts List
	Table	xsfCompliance	Vendor Subcontract Compliance Items
	Table	xsfDocReference	Document Catagorical Reference
	Table	xsfDocRevision	Document Revision
	Table	xsfProjectRevisionWB	Project Revision Detail
	Table	xsfReference	CSI and/or Unifomat
Description	(varchar, 60)		
	Table	xsfTaxRate	Tax Rate Definitions
Description	(varchar, 62)		
	Table	xsfDocTypeSubcodes	Type Dependant Codes
	Table	xsfDocTypeSubcodesHistory	History of Doc Type Specific Codes
Description	(varchar, 64)		
	Table	xsfProjectWBS	Project Work Breakdown
	Table	xsfRegion	Region Definition
	Table	xsfUCFunction	System Function List
	Table	xsfUCRole	User Role Definitions

Data Dictionary - Field Index

Wednesday, June 05, 2013

2:03 PM

Field	Type	Name	Description
DisplayName	(varchar, 96)		
	Table	xsfUIPart	User Interface Parts
DivCode	(char, 2)		
	Table	xsfReference	CSI and/or Unifomat
DivisionID	(char, 10)		
	Table	xsfAlertSubscription	Alert Subscriptions
	Table	xsfDivision	Company Division List
		AK_xsfCompany (Unique):1	
	Table	xsfDocHeader	Document Header
	Table	xsfDocTemplate	Word Document Template
	Table	xsfFile	Stored File
	Table	xsfRouteSpecial	Document Route Selection Criteria
	Table	xsfUser	System Users
	Table	xsfUserRole	User Role Membership
DivisionKey	(uniqueidentifier, 16)		
	Table	xsfDivision	Company Division List
		Primary Key:1	
DivisionName	(varchar, 60)		
	Table	xsfDivision	Company Division List
DMSType	(varchar, 16)		
	Table	xsfFileMarkup	File Version Markups and Resources
		IX_xsfFileMarkup:2	
DocAddrKey	(uniqueidentifier, 16)		
	Table	xsfDocAddr	Address
		Primary Key:1	
DocAlertKey	(uniqueidentifier, 16)		
	Table	xsfDocAlert	Document Alert
		Primary Key:1	

Data Dictionary - Field Index

Wednesday, June 05, 2013

2:03 PM

Field	Type	Name	Description
DocAttachKey	(uniqueidentifier, 16)		
	Table	xsfFileAttach Primary Key:1	Document Attachment List
DocAttributeKey	(uniqueidentifier, 16)		
	Table	xsfAttribute Primary Key:1	Document Attributes
DocBal	(money, 19)		
	Table	xsfAPInfo	AP Doc Summary by Project
DocBatchNo	(varchar, 16)		
	Table	xsfDocHeader	Document Header
DocCommentKey	(uniqueidentifier, 16)		
	Table	xsfComment IX_xsfDocContent (Unique):2	Comment
DocDate	(datetime, 23)		
	Table	xsfDocHeader IX_DocOCD:1	Document Header
DocDateName	(varchar, 50)		
	Table	xsfDocDateType AK_xsfDocDateType (Unique):2	Date Types
DocDateRowKey	(uniqueidentifier, 16)		
	Table	xsfDocDates Primary Key:1	Document Dates
DocDateTypeKey	(uniqueidentifier, 16)		
	Table	xsfDocDates	Document Dates
	Table	xsfDocDateType Primary Key:1	Date Types

Data Dictionary - Field Index

Wednesday, June 05, 2013
2:03 PM

Field	Type	Name	Description
DocEdit	(bit, 1)		
	Table	xsfDocHeader	Document Header
DocFlag	(bit, 1)		
	Table	xsfDocHeader	Document Header
DocItemKey	(uniqueidentifier, 16)		
	Table	xsfDocItem Primary Key:1	Document Item List
	Table	xsfDocItemTask IX_xsfDocItemTask:1	Revenue and Expense Details for an Item Ref: xsfDocItem
	Table	xsfDocRevItem IX_xsfDocItemOn:1	Document Revision Items Ref: xsfDocItem
DocKey	(uniqueidentifier, 16)		
	Table	xsfFile Primary Key:1	Stored File
	Table	xsfFileAccess AK_xsfFileAccess_ByFile (Unique)	File Access Log Ref: xsfFileVersionInfo
	Table	xsfFileAttach IX_xsfFileAttachFile:1	Document Attachment List Ref: xsfFile
	Table	xsfFileRStatus Primary Key:2	Store File Content Recognition Status
	Table	xsfFileVersionInfo AK_xsfFileVersionInfo (Unique):1	Stored File Version Attributes Ref: xsfFile
	Table	xsfRouteContentPending AK_xsfRouteContentPending:1	Catalog content to be updated for routing
DocMasterKey	(uniqueidentifier, 16)		
	Table	xsfAlert	User Alerts List
	Table	xsfCompliance IX_xsfCompliance:1	Vendor Subcontract Compliance Items Ref: xsfDocHeader
	Table	xsfDocAddr IX_xsfDocAddr (Unique):1	Address Ref: xsfDocHeader
	Table	xsfDocAlert IX_xsfDocAlert:1	Document Alert Ref: xsfDocHeader

Data Dictionary - Field Index

Wednesday, June 05, 2013

2:03 PM

Field	Type	Name	Description
DocMasterKey	(uniqueidentifier, 16)		
	Table	xsfDocDates IX_xsfDocDates:1	Document Dates Ref: xsfDocHeader
	Table	xsfDocHeader Primary Key:1	Document Header
	Table	xsfDocPosting AK_xsfDocPosting (Unique):1	Document Posting Ref: xsfDocHeader
	Table	xsfDocRevision AK_DocRevision (Unique):1	Document Revision
	Table	xsfDocSession AK_xsfDocSession (Unique):1	User Document Sessions Ref: xsfDocHeader
	Table	xsfDocSingleUser Primary Key:1	Document Exclusive User Reservation Ref: xsfDocHeader
	Table	xsfDocWriteTx AK_xsfDocWriteTx (Unique):1	Document Save Transaction Header Ref: xsfDocHeader
	Table	xsfEventSubscription	Event Subscriptions
	Table	xsfFileAttach IX_xsfDocAttach:1	Document Attachment List
	Table	xsfMeetingAttendee IX_xsfMeetingAttendee:1	Meeting Attendee Ref: xsfDocHeader
	Table	xsfRoute AK_xsfRouteDetail (Unique):1	Routed Document User Detail Ref: xsfDocHeader
	Table	xsfRouteStep AK_xsfRouteStep (Unique):1	Document Route Steps (Stage and Sequence) Ref: xsfDocHeader
	Table	xsfUserRole IX_xsfUserRole (Unique):5	User Role Membership Ref: xsfDocHeader
DocNo	(char, 16)		
	Table	xsfDocHeader IX_DocList:3	Document Header
DocPostingKey	(uniqueidentifier, 16)		
	Table	xsfDocPosting Primary Key:1	Document Posting

Data Dictionary - Field Index

Wednesday, June 05, 2013
2:03 PM

Field	Type	Name	Description
DocReference	(uniqueidentifier, 16)		
	Table	xsfContainerPermitCache AK_xsfContainerPermitCache (Uniq	Preresolved Container Permissions by User
	Table	xsfDocHeader IX_DocOCD:0 See also: xsfDocReference.DocReferenceKey	Document Header
	Table	xsfDocTemplate	Word Document Template
	Table	xsfFile See also: xsfDocReference.DocReferenceKey	Stored File
	Table	xsfRouteSpecial	Document Route Selection Criteria
	Table	xsfUserRole IX_xsfUserRole (Unique):4 See also: xsfDocReference.DocReferenceKey	User Role Membership
DocReferenceKey	(uniqueidentifier, 16)		
	Table	xsfDocReference IX_xsfDocReference:1	Document Catagorical Reference
DocRevItemKey	(uniqueidentifier, 16)		
	Table	xsfDocRevItem Primary Key:1	Document Revision Items
DocRevKey	(uniqueidentifier, 16)		
	Table	xsfDocRevision AK_DocRevision (Unique):3	Document Revision
	Table	xsfDocRevItem IX_xsfDocRevItem:1	Document Revision Items Ref: xsfDocRevision
	Table	xsfForecast AK_xsfForecast (Unique):1	Forecast
	Table	xsfInclusion IX_xsfInclusion (Unique):1	Include and Exclusion Items Ref: xsfDocRevision
	Table	xsfPjPeriodRev	Project Budget by Period Revision Header
	Table	xsfProjectRevision	Project Revision

Data Dictionary - Field Index

Wednesday, June 05, 2013
2:03 PM

Field	Type	Name	Description
DocSessionKey	(uniqueidentifier, 16)		
	Table	xsfDocSession Primary Key:1	User Document Sessions
	Table	xsfDocSingleUser IX_xsfDocSingleUser_DocSession:	Document Exclusive User Reservation Ref: xsfDocSession
DocSubtypeKey	(uniqueidentifier, 16)		
	Table	xsfDocTypeSubcodes Primary Key:1	Type Dependant Codes
	Table	xsfDocTypeSubcodesHistory Primary Key:2	History of Doc Type Specific Codes
DocType	(char, 2)		
	Table	xsfAPInfo	AP Doc Summary by Project
DocType	(uniqueidentifier, 16)		
	Table	xsfContainerPermitCache AK_xsfContainerPermitCache (Uniq	Preresolved Container Permissions by User
	Table	xsfUCSubRole AK_xsfUCSubRole (Unique):3 See also: xsfDocType.DocTypeKey	Sub Role
	Table	xsfUserRole IX_xsfUserRole (Unique):3 See also: xsfDocType.DocTypeKey	User Role Membership
DocType	(varchar, 50)		
	Table	xsfDocType AK_Table1 (Unique):1	Routable Document Types
DocTypeKey	(uniqueidentifier, 16)		
	Table	xsfAlertSubscription	Alert Subscriptions
	Table	xsfComplianceTypeMap AK_xsfComplianceTypeMap (Unique)	Maps Compliance Type to Vendor and Commitments Ref: xsfDocType
	Table	xsfDashboardMenu	Spitfire Dashboard Menu

Field	Type	Name	Description
DocTypeKey	(uniqueidentifier, 16)		
	Table	xsfDocDateType AK_xsfDocDateType (Unique):1	Date Types
	Table	xsfDocHeader IX_DocList:2	Document Header Ref: xsfDocType
	Table	xsfDocReference	Document Catagorical Reference
	Table	xsfDocTemplate AK_xsfDocTemplateByType (Unique)	Word Document Template Ref: xsfDocType
	Table	xsfDocType Primary Key:1	Routable Document Types
	Table	xsfDocTypeSubcodes AK_xsfDocSubtype (Unique):1	Type Dependant Codes Ref: xsfDocType
	Table	xsfDocTypeSubcodesHistory	History of Doc Type Specific Codes
	Table	xsfDocWorkflow AK_xsfDocWorkflow:1	Document Workflow Events
	Table	xsfEventSubscription	Event Subscriptions
	Table	xsfPartConfig IX_xsfPartConfig:3	User Interface Part Customization Ref: xsfDocType
	Table	xsfPartConfigHistory	History of UI Part customizations
	Table	xsfRouteSpecial IX_xsfRouteSpecial:1	Document Route Selection Criteria Ref: xsfDocType
	Table	xsfUserNotify	User Notification Settings
DocWorkflowKey	(uniqueidentifier, 16)		
	Table	xsfDocWorkflow Primary Key:1	Document Workflow Events
DocWriteFactKey	(uniqueidentifier, 16)		
	Table	xsfDocWriteTxFact Primary Key:1	Document Save Facts
DocWriteKey	(uniqueidentifier, 16)		
	Table	xsfDocWriteTx Primary Key:1	Document Save Transaction Header
	Table	xsfDocWriteTxFact	Document Save Facts

Data Dictionary - Field Index

Wednesday, June 05, 2013

2:03 PM

Field	Type	Name	Description
Downloaded	(datetime, 23)		
	Table	xsfRoute	Routed Document User Detail
DraftNumber	(char, 10)		
	Table	xsfDocRevision	Document Revision
DrawingNumber	(varchar, 20)		
	Table	xsfDocItem	Document Item List
Drawings	(varchar, 8)		
	Table	xsfDocItem	Document Item List
DSLType	(char, 1)		
	Table	xsfProjectRevision	Project Revision
Due	(datetime, 23)		
	Table	xsfDocHeader IX_DocOCD:0	Document Header
	Table	xsfDocItem	Document Item List
	Table	xsfRoute IX_xsfRouteToUser:0	Routed Document User Detail
DueInDays	(smallmoney, 10)		
	Table	xsfRouteList	Document Route Detail
Duration	(int, 10)		
	Table	xsfDocHeader	Document Header
EACAmount	(money, 19)		
	Table	xsfFSnapshotByPeriod	Project Budget by Period Snapshot
EditName	(bit, 1)		
	Table	xsfAlertType	Alert Types
Effective	(datetime, 23)		
	Table	xsfCompliance	Vendor Subcontract Compliance Items

Data Dictionary - Field Index

Wednesday, June 05, 2013

2:03 PM

Field	Type	Name	Description
Effective	(datetime, 23)		
	Table	xsfDocSingleUser	Document Exclusive User Reservation
Email	(varchar, 80)		
	Table	xsfDocAddr	Address
	Table	xsfUser	System Users
EmailSubject	(varchar, 80)		
	Table	xsfDocRevision	Document Revision
EmployeeID	(char, 10)		
	Table	xsfUser	System Users
		IX_VendorContact (Unique):3	
Ending	(datetime, 23)		
	Table	xsfProjectRevisionWB	Project Revision Detail
	Table	xsfUserProject	User Project Relationship
EntryType	(char, 1)		
	Table	xsfAllocation	Allocations and Markups
Evaluation	(varchar, 8)		
	Table	xsfDocItem	Document Item List
EventAgentKey	(uniqueidentifier, 16)		
	Table	xsfEventAgent	Event Notification Consumer Agents
		Primary Key:1	
	Table	xsfEventSubscription	Event Subscriptions
EventFlags	(int, 10)		
	Table	xsfEventSubscription	Event Subscriptions
ExpenseAmount	(money, 19)		
	Table	xsfDocItemTask	Revenue and Expense Details for an Item
		IX_xsfDocItemTask_ProjectCharge:	

Data Dictionary - Field Index

Wednesday, June 05, 2013

2:03 PM

Field	Type	Name	Description
Expiration	(datetime, 23)		
	Table	xsfCompliance	Vendor Subcontract Compliance Items
	Table	xsfUser	System Users
Expires	(datetime, 23)		
	Table	xsfDocSingleUser	Document Exclusive User Reservation
		IX_xsfDocSingleUser_Expiration:2	
	Table	xsfFileCheckout	File Checkout Information
ExtendedDescription	(varchar, 4096)		
	Table	xsfCSI	CSI Definition
Extension	(varchar, 8)		
	Table	xsfFileVersion	Stored File Version
ExternalDocNo	(varchar, 30)		
	Table	xsfDocHeader	Document Header
ExternalID	(char, 16)		
	Table	xsfContactCompany	Contact Company
		IX_xsfContactCompany:1	
ExternalID	(varchar, 16)		
	Table	xsfProjectRevision	Project Revision
ExternalSchedule	(varchar, 8)		
	Table	xsfProject	Project Information
ExternalStatus	(varchar, 8)		
	Table	xsfProject	Project Information
ExternalType	(char, 1)		
	Table	xsfContactCompany	Contact Company
		IX_xsfContactCompany:2	

Data Dictionary - Field Index

Wednesday, June 05, 2013

2:03 PM

Field	Type	Name	Description
FACAmount	(money, 19)		
	Table	xsfFSnapshotByPeriod	Project Budget by Period Snapshot
FactFlags	(tinyint, 3)		
	Table	xsfDocWriteTxFact	Document Save Facts
FailedLoginRun	(int, 10)		
	Table	xsfUser	System Users
FamiliarName	(varchar, 40)		
	Table	xsfUser	System Users
Fax	(varchar, 20)		
	Table	xsfDivision	Company Division List
	Table	xsfProject	Project Information
Fax	(varchar, 30)		
	Table	xsfDocAddr	Address
	Table	xsfUser	System Users
FeelsLike	(smallint, 5)		
	Table	xsfWeatherReading	Weather Reading Data
FieldMockup	(varchar, 8)		
	Table	xsfDocItem	Document Item List
FileAccessKey	(uniqueidentifier, 16)		
	Table	xsfFileAccess Primary Key:1	File Access Log
FileBinKey	(uniqueidentifier, 16)		
	Table	xsfFileVersion Primary Key:1	Stored File Version
	Table	xsfFileVersionInfo IX_xsfFileVersionInfo:1	Stored File Version Attributes

Field	Type	Name	Description
FileBinKey	(uniqueidentifier, 16)		
	Table	xsfRoutedContent	Enumerates content of document when routed to spec
FileDocKey	(uniqueidentifier, 16)		
	Table	xsfFileCheckout	File Checkout Information
		AK_xsfFileCheckout (Unique):1	
		See also: xsfFileVersionInfo.DocKey	
FileKey	(uniqueidentifier, 16)		
	Table	xsfEventSubscription	Event Subscriptions
FileMarkupKey	(uniqueidentifier, 16)		
	Table	xsfFileMarkup	File Version Markups and Resources
		Primary Key:1	
FileName	(varchar, 80)		
	Table	xsfFile	Stored File
		AK_xsfFile:4	
FileType	(char, 4)		
	Table	xsfEventSubscription	Event Subscriptions
FileType	(varchar, 8)		
	Table	xsfFile	Stored File
FileVerKey	(uniqueidentifier, 16)		
	Table	xsfFileMarkup	File Version Markups and Resources
		IX_xsfFileMarkup:1	Ref: xsfFileVersionInfo
	Table	xsfFileVersionInfo	Stored File Version Attributes
		Primary Key:1	
Filter	(varchar, 64)		
	Table	xsfPartConfig	User Interface Part Customization
		IX_xsfPartConfig:5	

Data Dictionary - Field Index

Wednesday, June 05, 2013

2:03 PM

Field	Type	Name	Description
Filter	(varchar, 64)		
	Table	xsfPartConfigHistory	History of UI Part customizations
FilterInfo	(varchar, 50)		
	Table	xsfRule	Logic Rules
FilterParam	(varchar, 16)		
	Table	xsfUIPart	User Interface Parts
FilterSetName	(varchar, 16)		
	Table	xsfRuleItemValidation	Rule Item Validation
FilterType	(varchar, 32)		
	Table	xsfRuleItemValidation	Rule Item Validation
			See also: xsfRuleValueType.ValueTypeID
FilterValue	(varchar, 64)		
	Table	xsfRuleItem	Logic Rule Detail
		AK_xsfRuleItem (Unique):3	
	Table	xsfRuleItemHistory	History of Rule settings
		AK_xsfRuleItemHistory (Unique):4	
Final	(bit, 1)		
	Table	xsfDocHeader	Document Header
FiscalPeriod	(char, 6)		
	Table	xsfFSnapshotByPeriod	Project Budget by Period Snapshot
		AK_xsfFSnapshotByPeriod (Unique)	
	Table	xsfPjPeriodRevBD	Project Budget by Period Revision Detail
		AK_xsfPjPeriodRevBD (Unique):4	
FlexName	(char, 30)		
	Table	xsfFlexKeySegments	Flex Key Segment Definition
		AK_xsfFlexKeySegments (Unique):1	

Data Dictionary - Field Index

Wednesday, June 05, 2013

2:03 PM

Field	Type	Name	Description
FlexSegmentKey	(uniqueidentifier, 16)		
	Table	xsfFlexKeySegments Primary Key:1	Flex Key Segment Definition
Folder	(uniqueidentifier, 16)		
	Table	xsfFileMarkup	File Version Markups and Resources
ForecastRowKey	(uniqueidentifier, 16)		
	Table	xsfForecast Primary Key:1	Forecast
	Table	xsfFSnapshotByPeriod AK_xsfFSnapshotByPeriod (Unique)	Project Budget by Period Snapshot Ref: xsfForecast
ForecastThreshold	(smallint, 5)		
	Table	xsfProject	Project Information
ForFiltering	(bit, 1)		
	Table	xsfRuleValueType	Rule Value Type
ForResults	(bit, 1)		
	Table	xsfRuleValueType	Rule Value Type
ForSubtype	(varchar, 8)		
	Table	xsfComplianceTypeMap AK_xsfComplianceTypeMap (Unique)	Maps Compliance Type to Vendor and Commitments
FromDocMasterKey	(uniqueidentifier, 16)		
	Table	xsfRoutedContent AK_xsfRoutedContent:3	Enumerates content of document when routed to spec
FromUser	(uniqueidentifier, 16)		
	Table	xsfComment See also: xsfUser.UserKey	Comment
	Table	xsfDocRevision	Document Revision
	Table	xsfDocRevItem	Document Revision Items

Data Dictionary - Field Index

Wednesday, June 05, 2013

2:03 PM

Field	Type	Name	Description
FromUser	(uniqueidentifier, 16)		
	Table	xsfDocTemplate	Word Document Template See also: xsfUser.UserKey
	Table	xsfEventSubscription	Event Subscriptions
	Table	xsfFileAttach	Document Attachment List See also: xsfUser.UserKey
	Table	xsfFileMarkup	File Version Markups and Resources See also: xsfUser.UserKey
	Table	xsfFileVersionInfo	Stored File Version Attributes IX_xsfFileVersionInfo_FromUser:1 See also: xsfUser.UserKey
	Table	xsfRoute	Routed Document User Detail IX_xsfRouteToUser:0
Future	(char, 2)		
Table	xsfDocReference	Document Catagorical Reference	
GeoLat	(decimal, 9)		
Table	xsfFile	Stored File	
GeoLng	(decimal, 9)		
Table	xsfFile	Stored File	
GLAcct	(char, 10)		
Table	xsfDocItemTask	Revenue and Expense Details for an Item	
GLAcct	(char, 14)		
Table	xsfWBPart	Work Breakdown Detail	
GLSub	(char, 24)		
Table	xsfDocItemTask	Revenue and Expense Details for an Item	
GroupNo	(smallint, 5)		
	Table	xsfRoute	Routed Document User Detail
	Table	xsfRouteList	Document Route Detail

Data Dictionary - Field Index

Wednesday, June 05, 2013
2:03 PM

Field	Type	Name	Description
Guarantee	(varchar, 8)		
	Table	xsfDocItem	Document Item List
HasBookmarks	(bit, 1)		
	Table	xsfDocTemplate	Word Document Template
HelpText	(varchar, 200)		
	Table	xsfPartConfig	User Interface Part Customization
	Table	xsfPartConfigHistory	History of UI Part customizations
Hidden	(bit, 1)		
	Table	xsfStaticResource	Protected System Resources
HitsCost	(bit, 1)		
	Table	xsfProjectRevision IX_xsfProjectRevision_Source:0	Project Revision
HitsRevenue	(bit, 1)		
	Table	xsfProjectRevision IX_xsfProjectRevision_Source:0	Project Revision
HSDepth	(smallint, 5)		
	Table	xsfDocWriteTx	Document Save Transaction Header
HSSeq	(smallint, 5)		
	Table	xsfDocWriteTx AK_xsfDocWriteTxHs (Unique):2	Document Save Transaction Header
HumidityPct	(smallint, 5)		
	Table	xsfWeatherReading	Weather Reading Data
IISID	(varchar, 32)		
	Table	xsfUserSession AK_xsfUserSession (Unique):3	User sessions

Data Dictionary - Field Index

Wednesday, June 05, 2013

2:03 PM

Field	Type	Name	Description
IISMS	(int, 10)		
	Table	xsfDocWriteTx	Document Save Transaction Header
IMHandle	(varchar, 80)		
	Table	xsfUser	System Users
Immutable	(bit, 1)		
	Table	xsfRuleItem	Logic Rule Detail
	Table	xsfStaticResource	Protected System Resources
IMService	(char, 2)		
	Table	xsfUser	System Users
IncludeFinish	(bit, 1)		
	Table	xsfDocDateType	Date Types
IncludeFlag	(char, 1)		
	Table	xsfRoutedContent	Enumerates content of document when routed to spec
IncludeFreight	(char, 10)		
	Table	xsfTaxRate	Tax Rate Definitions
IncludeRoutees	(bit, 1)		
	Table	xsfAlertSubscription	Alert Subscriptions
	Table	xsfDocAlert	Document Alert
IncludeStart	(bit, 1)		
	Table	xsfDocDateType	Date Types
InclusionKey	(uniqueidentifier, 16)		
	Table	xsfInclusion	Include and Exclusion Items
		Primary Key:1	

Data Dictionary - Field Index

Wednesday, June 05, 2013
2:03 PM

Field	Type	Name	Description
InclusionStockKey	(uniqueidentifier, 16)		
	Table	xsfInclusionStock Primary Key:1	Source list of stock inclusion entries
Info	(varchar, 128)		
	Table	xsfDocWriteTxFact	Document Save Facts
Info1	(varchar, 50)		
	Table	xsfAlert	User Alerts List
Info2	(varchar, 50)		
	Table	xsfAlert	User Alerts List
InPeriod	(char, 6)		
	Table	xsfDocRevision	Document Revision
	Table	xsfPjPeriodRev	Project Budget by Period Revision Header
	Table	xsfProjectRevision	Project Revision
InsOK	(bit, 1)		
	Table	xsfContainerPermitCache	Preresolved Container Permissions by User
	Table	xsfItemPermit	Item Permission settings
	Table	xsfUCFunctionPermit	Role Permission Settings
InvalidPW	(bit, 1)		
	Table	xsfUserSession	User sessions
IsDistributed	(bit, 1)		
	Table	xsfDocWorkflow	Document Workflow Events
	Table	xsfPartConfig IX_xsfPartConfig:6	User Interface Part Customization
	Table	xsfPartConfigHistory	History of UI Part customizations
	Table	xsfRuleItem AK_xsfRuleItem (Unique):4	Logic Rule Detail
	Table	xsfRuleItemHistory AK_xsfRuleItemHistory (Unique):5	History of Rule settings
	Table	xsfWorkflowLib	Workflow Script Library

Data Dictionary - Field Index

Wednesday, June 05, 2013
2:03 PM

Field	Type	Name	Description
IsExclusive	(bit, 1)		
	Table	xsfDocSession	User Document Sessions
	Table	xsfDocSingleUser IX_xsfDocSingleUser_Expiration:1	Document Exclusive User Reservation
IsFinal	(bit, 1)		
	Table	xsfRuleItemValidation	Rule Item Validation
IsPreliminary	(bit, 1)		
	Table	xsfContactCompany	Contact Company
IsPrimary	(bit, 1)		
	Table	xsfDivision	Company Division List
IsPublic	(bit, 1)		
	Table	xsfUser	System Users
	Table	xsfUserProject	User Project Relationship
IsQualified	(bit, 1)		
	Table	xsfContactCompany	Contact Company
IsReadOnly	(bit, 1)		
	Table	xsfPartConfig	User Interface Part Customization
	Table	xsfPartConfigHistory	History of UI Part customizations
IsRegular	(bit, 1)		
	Table	xsfMeetingAttendee	Meeting Attendee
IsRequired	(bit, 1)		
	Table	xsfComplianceTypeMap	Maps Compliance Type to Vendor and Commitments
	Table	xsfDocDateType	Date Types
ItemContainerKey	(uniqueidentifier, 16)		
	Table	xsfItemContainer Primary Key:1	Heirarchical Container
	Table	xsfNodeParentCache	Preresolved lineage

Data Dictionary - Field Index

Wednesday, June 05, 2013
2:03 PM

Field	Type	Name	Description
ItemKey	(uniqueidentifier, 16)		
	Table	xsfItemPermit AK_xsfItemPermit (Unique):2	Item Permission settings
ItemName	(varchar, 64)		
	Table	xsfPartConfig IX_xsfPartConfig:2	User Interface Part Customization Ref: xsfUIPartItem
	Table	xsfPartConfigHistory	History of UI Part customizations
	Table	xsfUIPartItem AK_xsfUIPartItem (Unique):2	User Interface Items
	Table	xsfUIPartItemHistory	History of UI Part Distributed Defaults
ItemNumber	(varchar, 32)		
	Table	xsfDocRevItem IX_xsfDocRevItem:2	Document Revision Items
	Table	xsfInclusion IX_xsfInclusion (Unique):3	Include and Exclusion Items
ItemPercent	(smallint, 5)		
	Table	xsfDocItemTask	Revenue and Expense Details for an Item
ItemPermitKey	(uniqueidentifier, 16)		
	Table	xsfItemPermit Primary Key:1	Item Permission settings
ItemQuantity	(numeric, 16)		
	Table	xsfDocItem	Document Item List
ItemRefKey	(uniqueidentifier, 16)		
	Table	xsfRoutedContent	Enumerates content of document when routed to spec
ItemSeq	(int, 10)		
	Table	xsfDocRevItem	Document Revision Items

Data Dictionary - Field Index

Wednesday, June 05, 2013
2:03 PM

Field	Type	Name	Description
ItemSource	(varchar, 8)		
	Table	xsfDocItem	Document Item List
ItemStatus	(varchar, 8)		
	Table	xsfDocItem	Document Item List
ItemSubtype	(varchar, 8)		
	Table	xsfDocItem	Document Item List
ItemTaskKey	(uniqueidentifier, 16)		
	Table	xsfDocItemTask Primary Key:1	Revenue and Expense Details for an Item
ItemText	(varchar, -1)		
	Table	xsfInclusion	Include and Exclusion Items
	Table	xsfInclusionStock	Source list of stock inclusion entries
ItemText	(varchar, 64)		
	Table	xsfDashboardMenu AK_xsfDashboardMenu (Unique):4	Spitfire Dashboard Menu
ItemType	(char, 1)		
	Table	xsfInclusion IX_xsfInclusion (Unique):2	Include and Exclusion Items
	Table	xsfInclusionStock	Source list of stock inclusion entries
	Table	xsfItemPermit	Item Permission settings
ItemType	(varchar, 8)		
	Table	xsfDocItem	Document Item List
	Table	xsfUIPartItem	User Interface Items
	Table	xsfUIPartItemHistory	History of UI Part Distributed Defaults
ItemTypes	(int, 10)		
	Table	xsfEventSubscription	Event Subscriptions

Data Dictionary - Field Index

Wednesday, June 05, 2013

2:03 PM

Field	Type	Name	Description
keyword	(varchar, 2000)		
	Table	xsfFile	Stored File
KindFlags	(int, 10)		
	Table	xsfDocWriteTx	Document Save Transaction Header
Label	(varchar, 64)		
	Table	xsfItemContainer	Heirachical Container
		AK_xsfItemContainer (Unique):2	
	Table	xsfPartConfig	User Interface Part Customization
	Table	xsfPartConfigHistory	History of UI Part customizations
LaborClass	(char, 4)		
	Table	xsfDocItemTask	Revenue and Expense Details for an Item
LastAlertWas	(datetime, 23)		
	Table	xsfCompliance	Vendor Subcontract Compliance Items
	Table	xsfDocAlert	Document Alert
LastCfgChangeWas	(bigint, 19)		
	Table	xsfCustomizationHistory	Customization History Snapshot Header
LastLogin	(datetime, 23)		
	Table	xsfUser	System Users
LastPWChange	(datetime, 23)		
	Table	xsfUser	System Users
LastReason	(varchar, 64)		
	Table	xsfCompliance	Vendor Subcontract Compliance Items
LastReleasedBy	(uniqueidentifier, 16)		
	Table	xsfCompliance	Vendor Subcontract Compliance Items
LastRouteKey	(uniqueidentifier, 16)		
	Table	xsfDocHeader	Document Header

Data Dictionary - Field Index

Wednesday, June 05, 2013

2:03 PM

Field	Type	Name	Description
LastSave	(datetime, 23)		
	Table	xsfDocSession	User Document Sessions
LastSaved	(datetime, 23)		
	Table	xsfFileMarkup	File Version Markups and Resources
LastStatusBy	(uniqueidentifier, 16)		
	Table	xsfDocHeader	Document Header
	Table	xsfDocItem	Document Item List
LastUser	(uniqueidentifier, 16)		
	Table	xsfFileMarkup See also: xsfUser.UserKey	File Version Markups and Resources
latitude	(decimal, 12)		
	Table	xsfProject	Project Information
LeadDays	(smallint, 5)		
	Table	xsfCompliance	Vendor Subcontract Compliance Items
	Table	xsfComplianceType	Compliance Type
LeadTime	(smallint, 5)		
	Table	xsfAlertSubscription	Alert Subscriptions
	Table	xsfAlertType	Alert Types
	Table	xsfDocAlert	Document Alert
	Table	xsfDocDates	Document Dates
LeafNodeKey	(uniqueidentifier, 16)		
	Table	xsfNodeParentCache Primary Key:1	Preresolved lineage
LevelNum	(smallint, 5)		
	Table	xsfNodeParentCache Primary Key:2	Preresolved lineage

Data Dictionary - Field Index

Wednesday, June 05, 2013

2:03 PM

Field	Type	Name	Description
Likeness	(uniqueidentifier, 16)		
	Table	xsfUser	System Users
LimitTo	(smallint, 5)		
	Table	xsfPartConfig	User Interface Part Customization
	Table	xsfPartConfigHistory	History of UI Part customizations
LinkedCCCKey	(uniqueidentifier, 16)		
	Table	xsfDocItemTask	Revenue and Expense Details for an Item
		IX_xsfDocItemTask_LinkedCCC:1	
LinkedDocKey	(uniqueidentifier, 16)		
	Table	xsfDocHeader	Document Header
	Table	xsfDocItem	Document Item List
		IX_xsfDocItem_LinkedDoc:1	
LinkedItemKey	(uniqueidentifier, 16)		
	Table	xsfDocItem	Document Item List
	Table	xsfFileAttach	Document Attachment List
		IX_xsfFileAttachedItem:1	
	Table	xsfMeetingAttendee	Meeting Attendee
		See also: xsfDocItem.DocItemKey	
LinkedLineKey	(uniqueidentifier, 16)		
	Table	xsfDocItemTask	Revenue and Expense Details for an Item
LinkedRFQKey	(uniqueidentifier, 16)		
	Table	xsfDocItemTask	Revenue and Expense Details for an Item
ListOK	(bit, 1)		
	Table	xsfContainerPermitCache	Preresolved Container Permissions by User
	Table	xsfItemPermit	Item Permission settings
Location	(varchar, 80)		
	Table	xsfWeatherLocation	Weather Report Locations
		AK_xsfWeatherLocation (Unique):2	

Data Dictionary - Field Index

Wednesday, June 05, 2013

2:03 PM

Field	Type	Name	Description
Location	(varchar, 130)		
	Table	xsfDocHeader	Document Header
LocationCode	(varchar, 10)		
	Table	xsfWeatherLocation	Weather Report Locations
		AK_xsfWeatherLocation (Unique):1	
Locked	(datetime, 23)		
	Table	xsfFileMarkup	File Version Markups and Resources
LockedOutUntil	(datetime, 23)		
	Table	xsfUser	System Users
LockoutReason	(varchar, 60)		
	Table	xsfUser	System Users
LockUser	(uniqueidentifier, 16)		
	Table	xsfFileMarkup	File Version Markups and Resources
		See also: xsfUser.UserKey	
LoginTime	(datetime, 23)		
	Table	xsfUserSession	User sessions
		AK_xsfUserSession (Unique):2	
Logo	(uniqueidentifier, 16)		
	Table	xsfProgram	Project Programs
LogoutTime	(datetime, 23)		
	Table	xsfUserSession	User sessions
longitude	(decimal, 12)		
	Table	xsfProject	Project Information
LongName	(varchar, 50)		
	Table	xsfWBPart	Work Breakdown Detail

Data Dictionary - Field Index

Wednesday, June 05, 2013

2:03 PM

Field	Type	Name	Description
LookupName	(varchar, 32)		
	Table	xsfPartConfig	User Interface Part Customization
	Table	xsfPartConfigHistory	History of UI Part customizations
MailRoute	(char, 1)		
	Table	xsfFileAttach	Document Attachment List
MaintenanceDocKey	(uniqueidentifier, 16)		
	Table	xsfContactCompany	Contact Company
			See also: xsfDocHeader.DocMasterKey
Manufacturer	(varchar, 40)		
	Table	xsfDocItem	Document Item List
MarkupAmount	(money, 19)		
	Table	xsfAllocation	Allocations and Markups
MarkupControl	(bit, 1)		
	Table	xsfDocItemTask	Revenue and Expense Details for an Item
MarkupName	(varchar, 80)		
	Table	xsfFileMarkup	File Version Markups and Resources
MarkupPct	(numeric, 7)		
	Table	xsfAllocation	Allocations and Markups
	Table	xsfChgMarkup	Change Order Markup
MarkupRate	(money, 19)		
	Table	xsfDocItemTask	Revenue and Expense Details for an Item
MasterSession	(char, 64)		
	Table	xsfPersistedData	Transient System Data
			IX_xsfPersistedData_BySession:1
MaxTS	(bigint, 19)		
	Table	xsfContentHistory	Detailed History of Table Content

Data Dictionary - Field Index

Wednesday, June 05, 2013
2:03 PM

Field	Type	Name	Description
MenuItemID	(int, 10)		
	Table	xsfDashboardMenu AK_xsfDashboardMenu (Unique):5	Spitfire Dashboard Menu
MenuItemKey	(uniqueidentifier, 16)		
	Table	xsfDashboardMenu Primary Key:1	Spitfire Dashboard Menu
MenuPath	(varchar, 64)		
	Table	xsfDashboardMenu AK_xsfDashboardMenu (Unique):2	Spitfire Dashboard Menu
MenuSeq	(int, 10)		
	Table	xsfDashboardMenu AK_xsfDashboardMenu (Unique):3	Spitfire Dashboard Menu
MergeWithSeq	(int, 10)		
	Table	xsfRoutedContent AK_xsfRoutedContent:4	Enumerates content of document when routed to spec
MixDesign	(varchar, 8)		
	Table	xsfDocItem	Document Item List
Mode	(char, 2)		
	Table	xsfProjectRevision	Project Revision
NestedSeq	(int, 10)		
	Table	xsfRoutedContent AK_xsfRoutedContent:6	Enumerates content of document when routed to spec
NewFromDashboard	(bit, 1)		
	Table	xsfDocType	Routable Document Types
NewPercentComplete	(int, 10)		
	Table	xsfProjectRevisionWB	Project Revision Detail

Data Dictionary - Field Index

Wednesday, June 05, 2013
2:03 PM

Field	Type	Name	Description
NextAlertAfter	(datetime, 23)		
	Table	xsfCompliance	Vendor Subcontract Compliance Items
	Table	xsfDocAlert IX_xsfDocAlert_Soon:2	Document Alert
NextSet	(varchar, 16)		
	Table	xsfDocTypeSubcodes	Type Dependant Codes
	Table	xsfDocTypeSubcodesHistory	History of Doc Type Specific Codes
NextStepKey	(uniqueidentifier, 16)		
	Table	xsfRouteStep	Document Route Steps (Stage and Sequence)
NoRepeats	(smallint, 5)		
	Table	xsfRouteList	Document Route Detail
Note	(varchar, -1)		
	Table	xsfAttribute	Document Attributes
	Table	xsfComment	Comment
	Table	xsfDocDates	Document Dates
	Table	xsfDocItemTask	Revenue and Expense Details for an Item
	Table	xsfFileAttach	Document Attachment List
	Table	xsfMeetingAttendee	Meeting Attendee
	Table	xsfRoute IX_xsfRouteToUser:0	Routed Document User Detail
Note	(varchar, 64)		
	Table	xsfStaticResource	Protected System Resources
Note	(varchar, 99)		
	Table	xsfCustomizationHistory	Customization History Snapshot Header
Note	(varchar, 1000)		
	Table	xsfWBPart	Work Breakdown Detail
NoteA	(varchar, -1)		
	Table	xsfDocRevision	Document Revision

Data Dictionary - Field Index

Wednesday, June 05, 2013

2:03 PM

Field	Type	Name	Description
NoteB	(varchar, -1)		
	Table	xsfDocRevision	Document Revision
NoteEML	(varchar, -1)		
	Table	xsfDocRevision	Document Revision
Notes	(varchar, -1)		
	Table	xsfDocRevision	Document Revision
Notes	(varchar, 176)		
	Table	xsfUCFunctionMap	Maps Capabilities to affected UI Parts
Notes	(varchar, 2048)		
	Table	xsfForecast	Forecast
NotificationDocKey	(uniqueidentifier, 16)		
	Table	xsfCompliance	Vendor Subcontract Compliance Items
NotificationType	(char, 1)		
	Table	xsfAlert	User Alerts List
Notified	(datetime, 23)		
	Table	xsfAlert	User Alerts List
NumToForward	(smallint, 5)		
	Table	xsfDocHeader	Document Header
NumToSend	(smallint, 5)		
	Table	xsfDocHeader	Document Header
ObjectID	(int, 10)		
	Table	xsfContentHistory Primary Key:2	Detailed History of Table Content
OnAdd	(bit, 1)		
	Table	xsfCodeList	Coded Choices

Data Dictionary - Field Index

Wednesday, June 05, 2013

2:03 PM

Field	Type	Name	Description
OnAdd	(bit, 1) Table	xsfCodeListHistory	History of Codes
OnDashboard	(char, 2) Table	xsfDocType	Routable Document Types
OpenDoc	(bit, 1) Table	xsfAPInfo	AP Doc Summary by Project
OpenVia	(varchar, 128) Table	xsfDocType	Routable Document Types
ORGAmount	(money, 19) Table	xsfFSnapshotByPeriod	Project Budget by Period Snapshot
OrgLevel	(int, 10) Table	xsfUser	System Users
OrigAmt	(money, 19) Table	xsfAPInfo	AP Doc Summary by Project
OriginalBudget	(money, 19) Table	xsfForecast	Forecast
OriginalEstimate	(money, 19) Table	xsfDocItem	Document Item List
OriginalQuote	(money, 19) Table	xsfDocItem	Document Item List
OriginalRevenue	(money, 19) Table	xsfForecast	Forecast
OriginalSC	(money, 19) Table	xsfForecast	Forecast

Data Dictionary - Field Index

Wednesday, June 05, 2013
2:03 PM

Field	Type	Name	Description
ParentType	(uniqueidentifier, 16)		
	Table	xsfDocType	Routable Document Types
PartConfigKey	(uniqueidentifier, 16)		
	Table	xsfPartConfig Primary Key:1	User Interface Part Customization
	Table	xsfPartConfigHistory Primary Key:2	History of UI Part customizations
PartItemKey	(uniqueidentifier, 16)		
	Table	xsfUIPartItem Primary Key:1	User Interface Items
	Table	xsfUIPartItemHistory Primary Key:2	History of UI Part Distributed Defaults
PartName	(varchar, 64)		
	Table	xsfPartConfig IX_xsfPartConfig:1	User Interface Part Customization Ref: xsfUIPartItem
	Table	xsfPartConfigHistory	History of UI Part customizations
	Table	xsfUCFunctionMap IX_xsfUCFunctionMap (Unique):1	Maps Capabilities to affected UI Parts
	Table	xsfUIPart Primary Key:1	User Interface Parts
	Table	xsfUIPartItem AK_xsfUIPartItem (Unique):1	User Interface Items Ref: xsfUIPart
	Table	xsfUIPartItemHistory	History of UI Part Distributed Defaults
Password	(varchar, 50)		
	Table	xsfUser	System Users
PayControl	(bit, 1)		
	Table	xsfComplianceType	Compliance Type
PayControl	(char, 2)		
	Table	xsfCompliance	Vendor Subcontract Compliance Items

Data Dictionary - Field Index

Wednesday, June 05, 2013
2:03 PM

Field	Type	Name	Description
PayControl	(char, 2)		
	Table	xsfDocHeader IX_DocByType:0	Document Header
PayItemNumber	(varchar, 30)		
	Table	xsfDocHeader	Document Header
PayPercent	(smallint, 5)		
	Table	xsfComplianceType	Compliance Type
PBDistribKey	(uniqueidentifier, 16)		
	Table	xsfFSnapshotByPeriod Primary Key:1	Project Budget by Period Snapshot
PBDRevKey	(uniqueidentifier, 16)		
	Table	xsfPjPeriodRevBD Primary Key:1	Project Budget by Period Revision Detail
PC_Status	(char, 1)		
	Table	xsfAPInfo	AP Doc Summary by Project
PDFData	(varbinary, -1)		
	Table	xsfFileVersion	Stored File Version
PendingBudgetRevision	(money, 19)		
	Table	xsfForecast	Forecast
PendingBudgetUnits	(numeric, 17)		
	Table	xsfForecast	Forecast
PendingCo	(money, 19)		
	Table	xsfForecast	Forecast
PendingCORevenue	(money, 19)		
	Table	xsfForecast	Forecast

Data Dictionary - Field Index

Wednesday, June 05, 2013
2:03 PM

Field	Type	Name	Description
PendingPayAmount	(money, 19)		
	Table	xsfForecast	Forecast
PendingSCO	(money, 19)		
	Table	xsfForecast	Forecast
PercentComplete	(int, 10)		
	Table	xsfProjectWBS	Project Work Breakdown
PeriodRevKey	(uniqueidentifier, 16)		
	Table	xsfPjPeriodRev Primary Key:1	Project Budget by Period Revision Header
	Table	xsfPjPeriodRevBD AK_xsfPjPeriodRevBD (Unique):1	Project Budget by Period Revision Detail Ref: xsfPjPeriodRev
PermitKey	(uniqueidentifier, 16)		
	Table	xsfUCFunctionPermit Primary Key:1	Role Permission Settings
PermitMask	(smallint, 5)		
	Table	xsfUCFunction	System Function List
PersistedDataKey	(char, 160)		
	Table	xsfPersistedData Primary Key:1	Transient System Data
Person	(varchar, 60)		
	Table	xsfDocAddr	Address
	Table	xsfProject	Project Information
PgmPjtMapKey	(uniqueidentifier, 16)		
	Table	xsfProgramProjectMap Primary Key:1	Program Project List
Phone	(varchar, 20)		
	Table	xsfDivision	Company Division List

Data Dictionary - Field Index

Wednesday, June 05, 2013

2:03 PM

Field	Type	Name	Description
Phone	(varchar, 20)		
	Table	xsfProject	Project Information
Phone	(varchar, 30)		
	Table	xsfDocAddr	Address
	Table	xsfUser	System Users
PlanRoom	(bit, 1)		
	Table	xsfDocType	Routable Document Types
PlanRoomMode	(varchar, 8)		
	Table	xsfProject	Project Information
Posted	(datetime, 23)		
	Table	xsfDocPosting	Document Posting
	Table	xsfPjPeriodRev	Project Budget by Period Revision Header
PostingType	(char, 2)		
	Table	xsfDocPosting	Document Posting
		AK_xsfDocPosting (Unique):2	
PotentialSCO	(money, 19)		
	Table	xsfForecast	Forecast
Present	(bit, 1)		
	Table	xsfMeetingAttendee	Meeting Attendee
PrimaryContactKey	(uniqueidentifier, 16)		
	Table	xsfContactCompany	Contact Company
		See also: xsfUser.UserKey	
PrintAs	(varchar, 50)		
	Table	xsfAllocation	Allocations and Markups
PriorBudgetChangeKey	(uniqueidentifier, 16)		
	Table	xsfForecast	Forecast

Data Dictionary - Field Index

Wednesday, June 05, 2013

2:03 PM

Field	Type	Name	Description
PriorChangeKey	(uniqueidentifier, 16)		
	Table	xsfForecast	Forecast
PriorFAC	(money, 19)		
	Table	xsfForecast	Forecast
PriorFACRevenue	(money, 19)		
	Table	xsfForecast	Forecast
PriorFACUnits	(money, 19)		
	Table	xsfForecast	Forecast
Priority	(smallint, 5)		
	Table	xsfDocHeader	Document Header
	Table	xsfRouteSpecial	Document Route Selection Criteria
PriorityOver	(smallint, 5)		
	Table	xsfUserNotify	User Notification Settings
Probability	(smallint, 5)		
	Table	xsfDocHeader	Document Header
Product	(char, 1)		
	Table	xsfDocType	Routable Document Types
ProductData	(varchar, 8)		
	Table	xsfDocItem	Document Item List
ProgramID	(varchar, 24)		
	Table	xsfProgram	Project Programs
		AK_xsfProgram (Unique):1	
	Table	xsfUserRole	User Role Membership
ProgramKey	(uniqueidentifier, 16)		
	Table	xsfProgram	Project Programs
		Primary Key:1	

Data Dictionary - Field Index

Wednesday, June 05, 2013
2:03 PM

Field	Type	Name	Description
ProgramKey	(uniqueidentifier, 16)		
	Table	xsfProgramProjectMap AK_xsfProgramProjectMap:1	Program Project List Ref: xsfProgram
ProgramTitle	(varchar, 60)		
	Table	xsfProgram	Project Programs
Project	(char, 16)		
	Table	xsfAlert	User Alerts List
	Table	xsfAlertSubscription	Alert Subscriptions
	Table	xsfAllocation	Allocations and Markups
	Table	xsfAPInfo Primary Key:1	AP Doc Summary by Project
	Table	xsfChgMarkup AK_Markup (Unique):1	Change Order Markup
	Table	xsfContainerPermitCache AK_xsfContainerPermitCache (Uniq	Preresolved Container Permissions by User
	Table	xsfDocHeader IX_DocList:1	Document Header
	Table	xsfEventSubscription	Event Subscriptions
	Table	xsfFile AK_xsfFile:2	Stored File
	Table	xsfPjPeriodRev AK_xsfPjPeriodRev (Unique):1	Project Budget by Period Revision Header
	Table	xsfProject AK_xsfProject (Unique):1	Project Information
	Table	xsfProjectRevision AK_xsfProjectRevision (Unique):1	Project Revision
	Table	xsfProjectWBS AK_xsfProjectWBS (Unique):1	Project Work Breakdown Ref: xsfProject
	Table	xsfRouteSpecial	Document Route Selection Criteria
	Table	xsfUserProject AK_UserProject (Unique):2	User Project Relationship
Table	xsfUserRole IX_xsfUserRole (Unique):6	User Role Membership	

Data Dictionary - Field Index

Wednesday, June 05, 2013
2:03 PM

Field	Type	Name	Description
Project	(varchar, 16)		
	Table	xsfProjectWBSegment AK_xsfProjectWBSegment (Unique)	Descriptive Titles for Project WBS Segments
ProjectDashboard	(bit, 1)		
	Table	xsfDocType	Routable Document Types
Projected	(bit, 1)		
	Table	xsfForecast IX_xsfForecast_AcctTasks (Unique)	Forecast
ProjectKey	(uniqueidentifier, 16)		
	Table	xsfProgramProjectMap AK_xsfProgramProjectMap:2	Program Project List Ref: xsfProject
	Table	xsfProject Primary Key:1	Project Information
ProjectPurchasing	(bit, 1)		
	Table	xsfContactCompany	Contact Company
ProjectReference	(char, 16)		
	Table	xsfDocItemTask IX_xsfDocItemTask_ProjectCharge:	Revenue and Expense Details for an Item
ProjectRevDetailKey	(uniqueidentifier, 16)		
	Table	xsfProjectRevisionWB Primary Key:1	Project Revision Detail
ProjectRevID	(int, 10)		
	Table	xsfPjPeriodRev	Project Budget by Period Revision Header
ProjectSubtype	(varchar, 8)		
	Table	xsfDocTemplate	Word Document Template
	Table	xsfRouteSpecial	Document Route Selection Criteria

Data Dictionary - Field Index

Wednesday, June 05, 2013
2:03 PM

Field	Type	Name	Description
ProjectType	(char, 2)		
	Table	xsfProject	Project Information
ProjectWBSKey	(uniqueidentifier, 16)		
	Table	xsfPjPeriodRevBD AK_xsfPjPeriodRevBD (Unique):2	Project Budget by Period Revision Detail Ref: xsfProjectWBS
	Table	xsfProjectWBS Primary Key:1	Project Work Breakdown
ProjectWBSSegmentKey	(varbinary, 16)		
	Table	xsfProjectWBSSegment Primary Key:1	Descriptive Titles for Project WBS Segments
ProjEntity	(char, 32)		
	Table	xsfChgMarkup AK_Markup (Unique):2	Change Order Markup
	Table	xsfDocHeader IX_DocOCD:0	Document Header
	Table	xsfDocItemTask IX_xsfDocItemTask:2	Revenue and Expense Details for an Item
	Table	xsfForecast AK_xsfForecast (Unique):2	Forecast
	Table	xsfRouteSpecial	Document Route Selection Criteria
Provider	(varchar, 80)		
	Table	xsfWeatherLocation AK_xsfWeatherLocation (Unique):4	Weather Report Locations
Purpose	(varchar, 8)		
	Table	xsfMeetingAttendee	Meeting Attendee
PWAging	(bit, 1)		
	Table	xsfUser	System Users
PWMustChange	(bit, 1)		
	Table	xsfUser	System Users

Data Dictionary - Field Index

Wednesday, June 05, 2013

2:03 PM

Field	Type	Name	Description
Recorded	(datetime, 23)		
	Table	xsfAttribute	Document Attributes
RecordedAt	(varchar, 80)		
	Table	xsfWeatherLocation AK_xsfWeatherLocation (Unique):3	Weather Report Locations
Recurs	(char, 2)		
	Table	xsfAlertSubscription	Alert Subscriptions
	Table	xsfAlertType	Alert Types
	Table	xsfCompliance	Vendor Subcontract Compliance Items
	Table	xsfComplianceType	Compliance Type
Recurs	(char, 10)		
	Table	xsfDocAlert	Document Alert
Reference	(varchar, 30)		
	Table	xsfMeetingAttendee	Meeting Attendee
ReferenceDate	(datetime, 23)		
	Table	xsfFile	Stored File
	Table	xsfFileMarkup	File Version Markups and Resources
RefNbr	(char, 10)		
	Table	xsfAPIInfo Primary Key:3	AP Doc Summary by Project
RefreshBookmarks	(bit, 1)		
	Table	xsfFile	Stored File
RegionID	(varchar, 10)		
	Table	xsfRegion AK_Region (Unique):1	Region Definition

Data Dictionary - Field Index

Wednesday, June 05, 2013

2:03 PM

Field	Type	Name	Description
RegionKey	(uniqueidentifier, 16)		
	Table	xsfRegion Primary Key:1	Region Definition
	Table	xsfRegionMap AK_RegionMap (Unique):2	Company Region Map Ref: xsfRegion
RegionMapKey	(uniqueidentifier, 16)		
	Table	xsfRegionMap Primary Key:1	Company Region Map
Released	(datetime, 23)		
	Table	xsfCompliance	Vendor Subcontract Compliance Items
RemoteNotify	(bit, 1)		
	Table	xsfAlertSubscription	Alert Subscriptions
ReplyTo	(bit, 1)		
	Table	xsfRoute	Routed Document User Detail
Reported	(datetime, 23)		
	Table	xsfWeatherReading AK_xsfWeatherReading (Unique):2	Weather Reading Data
Request	(varchar, -1)		
	Table	xsfRoute	Routed Document User Detail
Requested	(datetime, 23)		
	Table	xsfDocItem	Document Item List
RequiredBefore	(smallint, 5)		
	Table	xsfPartConfig	User Interface Part Customization
	Table	xsfPartConfigHistory	History of UI Part customizations
RequiredBy	(datetime, 23)		
	Table	xsfCompliance	Vendor Subcontract Compliance Items

Data Dictionary - Field Index

Wednesday, June 05, 2013
2:03 PM

Field	Type	Name	Description
RequiredPermit	(int, 10)		
	Table	xsfDashboardMenu	Spitfire Dashboard Menu
Resolved	(datetime, 23)		
	Table	xsfMeetingAttendee	Meeting Attendee
	Table	xsfRouteStep	Document Route Steps (Stage and Sequence)
ResourceKey	(uniqueidentifier, 16)		
	Table	xsfStaticResource	Protected System Resources
Response	(varchar, -1)		
	Table	xsfRoute	Routed Document User Detail
ResponseCode	(varchar, 8)		
	Table	xsfRoute	Routed Document User Detail
Responsibility	(uniqueidentifier, 16)		
	Table	xsfUserProject	User Project Relationship
		AK_UserProject (Unique):3	
		See also: xsfUCRole.UCRoleKey	
ResponsibleParty	(uniqueidentifier, 16)		
	Table	xsfDocHeader	Document Header
		IX_DocOCD:0	
		See also: xsfUser.UserKey	
	Table	xsfDocItem	Document Item List
	IX_xsfDocItem_Responsible:1		
Table	xsfRouteSpecial	Document Route Selection Criteria	
ResultSetName	(varchar, 16)		
	Table	xsfRuleItemValidation	Rule Item Validation
ResultType	(char, 10)		
	Table	xsfRule	Logic Rules

Data Dictionary - Field Index

Wednesday, June 05, 2013
2:03 PM

Field	Type	Name	Description
ResultType	(varchar, 32)		
	Table	xsfRuleItemValidation	Rule Item Validation See also: xsfRuleValueType.ValueTypeID
ResultValue	(varchar, 196)		
	Table	xsfRuleItem	Logic Rule Detail
	Table	xsfRuleItemHistory	History of Rule settings
RetentionAmount	(money, 19)		
	Table	xsfDocItemTask	Revenue and Expense Details for an Item
RetentionMethod	(char, 2)		
	Table	xsfDocItemTask	Revenue and Expense Details for an Item
RevenueAmount	(money, 19)		
	Table	xsfDocItemTask	Revenue and Expense Details for an Item
RevenueEntity	(char, 32)		
	Table	xsfDocItem	Document Item List
RevID	(smallint, 5)		
	Table	xsfFileAccess	File Access Log AK_xsfFileAccess_ByFile (Unique) Ref: xsfFileVersionInfo
	Table	xsfFileCheckout	File Checkout Information
	Table	xsfFileRStatus	Store File Content Recognition Status Primary Key:3
	Table	xsfFileVersionInfo	Stored File Version Attributes AK_xsfFileVersionInfo (Unique):2
Reviewed	(datetime, 23)		
	Table	xsfAttribute	Document Attributes
	Table	xsfDocItem	Document Item List
RevisionID	(int, 10)		
	Table	xsfPjPeriodRev	Project Budget by Period Revision Header AK_xsfPjPeriodRev (Unique):2

Data Dictionary - Field Index

Wednesday, June 05, 2013
2:03 PM

Field	Type	Name	Description
RevisionID	(int, 10)		
	Table	xsfProjectRevision AK_xsfProjectRevision (Unique):2	Project Revision
RevisionNumber	(varchar, 16)		
	Table	xsfDocItem	Document Item List
RevisionSource	(char, 2)		
	Table	xsfProjectRevision	Project Revision
RevisionUnits	(numeric, 17)		
	Table	xsfForecast	Forecast
RevNo	(smallint, 5)		
	Table	xsfDocRevision AK_DocRevision (Unique):2	Document Revision
RevSource	(char, 1)		
	Table	xsfPjPeriodRev	Project Budget by Period Revision Header
RIVVEnumKey	(uniqueidentifier, 16)		
	Table	xsfRuleValueEnum Primary Key:1	Rule Value Enumeration for Type
RIsed	(bit, 1)		
	Table	xsfAPInfo	AP Doc Summary by Project
Role	(varchar, 50)		
	Table	xsfUser	System Users
RoleDescription	(varchar, 64)		
	Table	xsfUserProject	User Project Relationship
RoleName	(varchar, 50)		
	Table	xsfUCRole AK_xsfUCRole (Unique):1	User Role Definitions

Data Dictionary - Field Index

Wednesday, June 05, 2013
2:03 PM

Field	Type	Name	Description
RoleUserKey	(uniqueidentifier, 16)		
	Table	xsfUserRole Primary Key:1	User Role Membership
Rollup	(char, 10)		
	Table	xsfDocReference	Document Catagorical Reference
	Table	xsfReference	CSI and/or Unifomat
RouteContentKey	(uniqueidentifier, 16)		
	Table	xsfRouteContentPending AK_xsfRouteContentPending:3	Catalog content to be updated for routing Ref: xsfRoutedContent
	Table	xsfRoutedContent Primary Key:1	Enumerates content of document when routed to spec
RoutedContent	(bit, 1)		
	Table	xsfFile	Stored File
RouteeProxy	(uniqueidentifier, 16)		
	Table	xsfUser See also: xsfUCRole.UCRoleKey	System Users
RouteFlags	(int, 10)		
	Table	xsfDocHeader	Document Header
RouteID	(uniqueidentifier, 16)		
	Table	xsfRoute Primary Key:1	Routed Document User Detail
	Table	xsfRoutedContent AK_xsfRoutedContent:2	Enumerates content of document when routed to spec Ref: xsfRoute
	Table	xsfRouteTransmittal Primary Key:1	Extends a Route Entry with a Transmittal Ref: xsfRoute
RouteKey	(uniqueidentifier, 16)		
	Table	xsfRouteList	Document Route Detail

Data Dictionary - Field Index

Wednesday, June 05, 2013
2:03 PM

Field	Type	Name	Description
RouteKey	(uniqueidentifier, 16)		
	Table	xSfRouteListMaster Primary Key:1	Document Route List
	Table	xsfRouteSpecial	Document Route Selection Criteria
RouteListKey	(uniqueidentifier, 16)		
	Table	xsfRouteList Primary Key:1	Document Route Detail
RouteName	(varchar, 50)		
	Table	xSfRouteListMaster IX_xSfRouteListMaster (Unique):1	Document Route List
RouteSpecialKey	(uniqueidentifier, 16)		
	Table	xsfRouteSpecial Primary Key:1	Document Route Selection Criteria
RouteStepKey	(uniqueidentifier, 16)		
	Table	xsfRoutedContent AK_xsfRoutedContent:1	Enumerates content of document when routed to spec
	Table	xsfRouteStep Primary Key:1	Document Route Steps (Stage and Sequence)
RouteVia	(char, 1)		
	Table	xsfRoute	Routed Document User Detail
	Table	xsfUser	System Users
	Table	xsfUserNotify	User Notification Settings
Rows	(int, 10)		
	Table	xsfContentHistory	Detailed History of Table Content
RowType	(char, 1)		
	Table	xsfForecast	Forecast

Data Dictionary - Field Index

Wednesday, June 05, 2013
2:03 PM

Field	Type	Name	Description
RSysName	(varchar, 64)		
	Table	xsfFileRStatus Primary Key:1	Store File Content Recognition Status
RuleItemKey	(uniqueidentifier, 16)		
	Table	xsfRuleItem Primary Key:1	Logic Rule Detail
	Table	xsfRuleItemHistory Primary Key:2	History of Rule settings
RuleItemValidationKey	(uniqueidentifier, 16)		
	Table	xsfRuleItemValidation Primary Key:1	Rule Item Validation
RuleKey	(uniqueidentifier, 16)		
	Table	xsfRule Primary Key:1	Logic Rules
	Table	xsfRuleItem AK_xsfRuleItem (Unique):1	Logic Rule Detail Ref: xsfRule
	Table	xsfRuleItemHistory AK_xsfRuleItemHistory (Unique):1	History of Rule settings Ref: xsfRule
	Table	xsfRuleItemValidation AK_xsfRuleItemValidation (Unique)	Rule Item Validation
RuleName	(varchar, 50)		
	Table	xsfRule AK_xsfRule (Unique):1	Logic Rules
RuleVVTKey	(uniqueidentifier, 16)		
	Table	xsfRuleValueType Primary Key:1	Rule Value Type
Salutation	(varchar, 50)		
	Table	xsfUser	System Users

Data Dictionary - Field Index

Wednesday, June 05, 2013

2:03 PM

Field	Type	Name	Description
Samples	(varchar, 8)		
	Table	xsfDocItem	Document Item List
SCBudgetMode	(varchar, 8)		
	Table	xsfProject	Project Information
SchedFinish	(datetime, 23)		
	Table	xsfDocDates	Document Dates
	Table	xsfProjectWBS	Project Work Breakdown
SchedStart	(datetime, 23)		
	Table	xsfDocDates	Document Dates
	Table	xsfProjectWBS	Project Work Breakdown
Schedule	(varchar, 8)		
	Table	xsfDocItem	Document Item List
SCPayReqPaid	(money, 19)		
	Table	xsfForecast	Forecast
SCPayReqRetention	(money, 19)		
	Table	xsfForecast	Forecast
SCPayReqTotal	(money, 19)		
	Table	xsfForecast	Forecast
SCPPRRetention	(money, 19)		
	Table	xsfForecast	Forecast
SCRemainingPay	(money, 19)		
	Table	xsfForecast	Forecast
Section	(char, 16)		
	Table	xsfDocHeader	Document Header

Data Dictionary - Field Index

Wednesday, June 05, 2013

2:03 PM

Field	Type	Name	Description
SegBreakFlag	(char, 1)		
	Table	xsfFlexKeySegments	Flex Key Segment Definition
SegLen	(smallint, 5)		
	Table	xsfFlexKeySegments	Flex Key Segment Definition
SegLookup	(varchar, 32)		
	Table	xsfFlexKeySegments	Flex Key Segment Definition
SegMaskType	(char, 1)		
	Table	xsfFlexKeySegments	Flex Key Segment Definition
Segment	(varchar, 8)		
	Table	xsfDocRevision	Document Revision
SegName	(varchar, 16)		
	Table	xsfFlexKeySegments	Flex Key Segment Definition
SegNumber	(smallint, 5)		
	Table	xsfFlexKeySegments	Flex Key Segment Definition
		AK_xsfFlexKeySegments (Unique):2	
	Table	xsfProjectWBSSegment	Descriptive Titles for Project WBS Segments
		AK_xsfProjectWBSSegment (Unique)	
SegRollupFlag	(char, 1)		
	Table	xsfFlexKeySegments	Flex Key Segment Definition
SegValue	(varchar, 32)		
	Table	xsfProjectWBSSegment	Descriptive Titles for Project WBS Segments
		AK_xsfProjectWBSSegment (Unique)	
SegValueDescription	(varchar, 60)		
	Table	xsfProjectWBSSegment	Descriptive Titles for Project WBS Segments
SegValues	(varchar, 128)		
	Table	xsfFlexKeySegments	Flex Key Segment Definition

Data Dictionary - Field Index

Wednesday, June 05, 2013
2:03 PM

Field	Type	Name	Description
SendAlerts	(bit, 1)		
	Table	xsfRoute	Routed Document User Detail
	Table	xsfRouteList	Document Route Detail
SeqData	(smallint, 5)		
	Table	xsfPartConfig	User Interface Part Customization
	Table	xsfPartConfigHistory	History of UI Part customizations
SeqNo	(smallint, 5)		
	Table	xsfRouteList	Document Route Detail
Sequence	(smallint, 5)		
	Table	xsfAlertType IX_xsfAlertType:1	Alert Types
	Table	xsfAllocation	Allocations and Markups
	Table	xsfDocDateType	Date Types
	Table	xsfDocWorkflow AK_xsfDocWorkflow:4	Document Workflow Events
	Table	xsfDocWriteTxFact	Document Save Facts
	Table	xsfRoute AK_xsfRouteDetail (Unique):3	Routed Document User Detail
	Table	xsfRouteStep AK_xsfRouteStep (Unique):3	Document Route Steps (Stage and Sequence)
	Table	xsfWBPart	Work Breakdown Detail
	SessionEnd	(datetime, 23)	
Table		xsfDocSession	User Document Sessions
SessionStart	(datetime, 23)		
	Table	xsfDocSession AK_xsfDocSession (Unique):2	User Document Sessions
SetEmailFrom	(bit, 1)		
	Table	xsfRouteList	Document Route Detail

Data Dictionary - Field Index

Wednesday, June 05, 2013

2:03 PM

Field	Type	Name	Description
SetName	(varchar, 16)		
	Table	xsfCodeList AK_CodeList (Unique):1	Coded Choices
	Table	xsfCodeListHistory	History of Codes
	Table	xsfCodeSet IX_xsfCodeSet (Unique):1	Code Sets
	Table	xsfCodeSetHistory	History of Code Sets
	Table	xsfDocTypeSubcodes AK_xsfDocSubtype (Unique):2	Type Dependant Codes
	Table	xsfDocTypeSubcodesHistory	History of Doc Type Specific Codes
	SetType	(varchar, 24)	
Table		xsfCodeSet	Code Sets
Table		xsfCodeSetHistory	History of Code Sets
SetupDocKey	(uniqueidentifier, 16)		
	Table	xsfProject	Project Information
sfGenerated	(bit, 1)		
	Table	xsfFile	Stored File
sfUser	(bit, 1)		
	Table	xsfUser	System Users
sfVersion	(smallmoney, 10)		
	Table	xsfDocRevision	Document Revision
sfVersion	(varchar, 32)		
	Table	xsfCustomizationHistory	Customization History Snapshot Header
Shop	(varchar, 8)		
	Table	xsfDocItem	Document Item List
ShowDate	(bit, 1)		
	Table	xsfAlertType	Alert Types

Data Dictionary - Field Index

Wednesday, June 05, 2013
2:03 PM

Field	Type	Name	Description
ShowName	(varchar, 24)		
	Table	xsfCodeSet	Code Sets
	Table	xsfCodeSetHistory	History of Code Sets
ShowNewProjects	(bit, 1)		
	Table	xsfUser	System Users
ShowPhone	(smallint, 5)		
	Table	xsfUser	System Users
Signature	(uniqueidentifier, 16)		
	Table	xsfUser	System Users
Signoff	(datetime, 23)		
	Table	xsfDocHeader	Document Header
SiteActive	(bit, 1)		
	Table	xsfDashboardMenu	Spitfire Dashboard Menu
	Table	xsfDocType	Routable Document Types
SiteAddrKey	(uniqueidentifier, 16)		
	Table	xsfProject	Project Information
SiteName	(varchar, 50)		
	Table	xsfDocType	Routable Document Types
SlidingExpiration	(bit, 1)		
	Table	xsfUser	System Users
SMRetention	(money, 19)		
	Table	xsfDocItem	Document Item List
	Table	xsfDocRevision	Document Revision
SMRetentionAmount	(money, 19)		
	Table	xsfDocItemTask	Revenue and Expense Details for an Item

Data Dictionary - Field Index

Wednesday, June 05, 2013

2:03 PM

Field	Type	Name	Description
SolomonUser	(bit, 1)		
	Table	xsfUser	System Users
SortName	(varchar, 40)		
	Table	xsfUser	System Users
Source	(char, 2)		
	Table	xsfItemContainer	Heirachical Container
Source	(varchar, 8)		
	Table	xsfDocHeader	Document Header
Source	(varchar, 30)		
	Table	xsfAlert	User Alerts List
SourceAcctCategory	(char, 16)		
	Table	xsfAllocation	Allocations and Markups
SourceBatchNo	(varchar, 16)		
	Table	xsfFile	Stored File
SourceContact	(uniqueidentifier, 16)		
	Table	xsfDocHeader	Document Header
		IX_DocByType:0	
	Table	xsfFile	Stored File
		AK_xsfFile:3	
	Table	xsfRouteSpecial	Document Route Selection Criteria
SourceDate	(datetime, 23)		
	Table	xsfDocHeader	Document Header
SourceDocNo	(varchar, 30)		
	Table	xsfDocHeader	Document Header
		IX_DocSourceNo:1	
	Table	xsfFile	Stored File

Data Dictionary - Field Index

Wednesday, June 05, 2013
2:03 PM

Field	Type	Name	Description
SourceDocRevKey	(uniqueidentifier, 16)		
	Table	xsfProjectRevision IX_xsfProjectRevision_Source:1	Project Revision
SourceID	(varchar, 16)		
	Table	xsfDocTemplate	Word Document Template
SourceInitialNumber	(varchar, 30)		
	Table	xsfDocItem	Document Item List
SourceItemNumber	(varchar, 30)		
	Table	xsfDocItem	Document Item List
SourceKey	(varchar, 50)		
	Table	xsfAlert	User Alerts List
SourceProjEntity	(char, 32)		
	Table	xsfAllocation	Allocations and Markups
SourceRevision	(varchar, 16)		
	Table	xsfFileVersionInfo	Stored File Version Attributes
SourceType	(char, 1)		
	Table	xsfDocAddr	Address
SOVItemNumber	(char, 6)		
	Table	xsfDocHeader	Document Header
SOVLine	(varchar, 32)		
	Table	xsfProjectWBS	Project Work Breakdown
SOVLineNumber	(varchar, 32)		
	Table	xsfDocItem	Document Item List
SOVMaterials	(money, 19)		
	Table	xsfDocItemTask	Revenue and Expense Details for an Item

Data Dictionary - Field Index

Wednesday, June 05, 2013
2:03 PM

Field	Type	Name	Description
SOVWork	(money, 19)		
	Table	xsfDocItemTask	Revenue and Expense Details for an Item
Specification	(varchar, 16)		
	Table	xsfAttribute	Document Attributes
	Table	xsfDocItem	Document Item List
Stage	(smallint, 5)		
	Table	xsfComment	Comment
	Table	xsfDocItem	Document Item List
	Table	xsfRoute	Routed Document User Detail
	Table	AK_xsfRouteDetail (Unique):2	
Started	(datetime, 23)		
	Table	xsfDocItem	Document Item List
Starting	(datetime, 23)		
	Table	xsfProjectRevisionWB	Project Revision Detail
State	(char, 1)		
	Table	xsfFileRStatus	Store File Content Recognition Status
State	(char, 2)		
	Table	xsfDivision	Company Division List
	Table	xsfDocAddr	Address
	Table	xsfProject	Project Information
	Table	xsfUser	System Users
Status	(char, 1)		
	Table	xsfAlert	User Alerts List
		IX_xsfAlert:2	

Data Dictionary - Field Index

Wednesday, June 05, 2013
2:03 PM

Field	Type	Name	Description
Status	(char, 1)		
	Table	xsfFileCheckout	File Checkout Information
	Table	xsfRoute IX_xsfRouteToUser:5	Routed Document User Detail
Status	(char, 2)		
	Table	xsfDocHeader IX_DocSourceContact:0	Document Header
	Table	xsfProjectRevision	Project Revision
Status		xsfRouteSpecial	Document Route Selection Criteria
Status	(varchar, 8)		
	Table	xsfProjectWBS	Project Work Breakdown
StoredAmount	(money, 19)		
	Table	xsfDocItemTask	Revenue and Expense Details for an Item
SubAcct	(char, 24)		
	Table	xsfAPInfo	AP Doc Summary by Project
SubChangeOrder	(char, 10)		
	Table	xsfDocItemTask	Revenue and Expense Details for an Item
SubContract	(char, 16)		
	Table	xsfDocHeader IX_DocOCD:0	Document Header
	Table	xsfDocItemTask IX_xsfDocItemTask:4	Revenue and Expense Details for an Item
Submitted	(datetime, 23)		
	Table	xsfDocItem	Document Item List
SubRoleKey	(uniqueidentifier, 16)		
	Table	xsfUCSubRole Primary Key:1	Sub Role

Data Dictionary - Field Index

Wednesday, June 05, 2013

2:03 PM

Field	Type	Name	Description
SubscriptionKey	(uniqueidentifier, 16)		
	Table	xsfEventSubscription Primary Key:1	Event Subscriptions
Subsegment	(varchar, 8)		
	Table	xsfDocRevision	Document Revision
Subtype	(varchar, 8)		
	Table	xsfDocHeader IX_DocByType:0	Document Header
	Table	xsfDocTemplate	Word Document Template
	Table	xsfRouteSpecial	Document Route Selection Criteria
Subtype	(varchar, 16)		
	Table	xsfFileMarkup	File Version Markups and Resources
SubUCRoleKey	(uniqueidentifier, 16)		
	Table	xsfUCSubRole AK_xsfUCSubRole (Unique):2 See also: xsfUCRole.UCRoleKey	Sub Role
SuffixSeparator	(varchar, 4)		
	Table	xsfRuleItemValidation	Rule Item Validation
SuffixSetName	(varchar, 16)		
	Table	xsfRuleItemValidation	Rule Item Validation
Supplier	(varchar, 40)		
	Table	xsfDocItem	Document Item List
SuppressNotifyUntil	(datetime, 23)		
	Table	xsfUser	System Users
Suspend	(bit, 1)		
	Table	xsfAlertSubscription	Alert Subscriptions

Data Dictionary - Field Index

Wednesday, June 05, 2013
2:03 PM

Field	Type	Name	Description
SynchCheck	(int, 10)		
	Table	xsfUser	System Users
TakenBy	(uniqueidentifier, 16)		
	Table	xsfCustomizationHistory	Customization History Snapshot Header
TargetAcctCategory	(char, 16)		
	Table	xsfAllocation	Allocations and Markups
TargetProjEntity	(char, 32)		
	Table	xsfAllocation	Allocations and Markups
TaxHandling	(varchar, 8)		
	Table	xsfDocRevision	Document Revision
TaxID	(char, 10)		
	Table	xsfDocRevision	Document Revision
	Table	xsfTaxRate	Tax Rate Definitions
		AK_xsfTaxRate (Unique):1	
TaxRate	(decimal, 9)		
	Table	xsfDocRevision	Document Revision
	Table	xsfTaxRate	Tax Rate Definitions
TaxRateKey	(uniqueidentifier, 16)		
	Table	xsfTaxRate	Tax Rate Definitions
		Primary Key:1	
TaxType	(varchar, 8)		
	Table	xsfTaxRate	Tax Rate Definitions
TeamList	(bit, 1)		
	Table	xsfUserProject	User Project Relationship
Temperature	(smallint, 5)		
	Table	xsfWeatherReading	Weather Reading Data

Data Dictionary - Field Index

Wednesday, June 05, 2013
2:03 PM

Field	Type	Name	Description
TemplateKey	(uniqueidentifier, 16)		
	Table	xsfDocTemplate Primary Key:1	Word Document Template
TemplateName	(varchar, 80)		
	Table	xsfDocTemplate AK_xsfDocTemplateByType (Unique)	Word Document Template
TemplateType	(char, 2)		
	Table	xsfDocTemplate	Word Document Template
TestReport	(varchar, 8)		
	Table	xsfDocItem	Document Item List
TestValue	(varchar, 40)		
	Table	xsfRuleItem AK_xsfRuleItem (Unique):2	Logic Rule Detail
	Table	xsfRuleItemHistory AK_xsfRuleItemHistory (Unique):3	History of Rule settings
TestValueLike	(varchar, 48)		
	Table	xsfRuleItemValidation AK_xsfRuleItemValidation (Unique)	Rule Item Validation
Threshold	(smallint, 5)		
	Table	xsfForecast IX_xsfForecast_AcctTasks (Unique)	Forecast
ThresholdAmount	(money, 19)		
	Table	xsfAllocation	Allocations and Markups
TimeZone	(char, 3)		
	Table	xsfUser	System Users
TipText	(varchar, 64)		
	Table	xsfDashboardMenu	Spitfire Dashboard Menu

Data Dictionary - Field Index

Wednesday, June 05, 2013
2:03 PM

Field	Type	Name	Description
TipText	(varchar, 100)		
	Table	xsfPartConfig	User Interface Part Customization
	Table	xsfPartConfigHistory	History of UI Part customizations
Title	(varchar, 60)		
	Table	xsfDocHeader IX_DocOCD:0	Document Header
	Table	xsfUser	System Users
TopicKey	(uniqueidentifier, 16)		
	Table	xsfComment IX_xsfDocContent (Unique):1	Comment
TotalIMS	(int, 10)		
	Table	xsfDocWriteTx	Document Save Transaction Header
	Table	xsfUserSession	User sessions
TotalRequests	(int, 10)		
	Table	xsfUserSession	User sessions
TrackingNotes	(varchar, 2048)		
	Table	xsfForecast	Forecast
TransNumber	(int, 10)		
	Table	xsfRouteTransmittal AK_xsfRouteTransmittal (Unique):	Extends a Route Entry with a Transmittal
TransStatus	(char, 2)		
	Table	xsfRouteTransmittal	Extends a Route Entry with a Transmittal
TriggerWhen	(smallint, 5)		
	Table	xsfDocWorkflow AK_xsfDocWorkflow:2	Document Workflow Events
TxtData	(varchar, -1)		
	Table	xsfFileMarkup	File Version Markups and Resources

Data Dictionary - Field Index

Wednesday, June 05, 2013

2:03 PM

Field	Type	Name	Description
TxtData	(varchar, -1)		
	Table	xsfFileVersionInfo	Stored File Version Attributes
UCFunction	(varchar, 50)		
	Table	xsfDashboardMenu	Spitfire Dashboard Menu
UCFunctionKey	(uniqueidentifier, 16)		
	Table	xsfPartConfig	User Interface Part Customization
	Table	xsfPartConfigHistory	History of UI Part customizations
	Table	xsfUCFunction	System Function List
		Primary Key:1	
	Table	xsfUCFunctionMap	Maps Capabilities to affected UI Parts
		IX_xsfUCFunctionMap (Unique):2	Ref: xsfUCFunction
Table	xsfUCFunctionPermit	Role Permission Settings	
	AK_xsfUCFunctionPermit (Unique):	Ref: xsfUCFunction	
UCModule	(char, 4)		
	Table	xsfDashboardMenu	Spitfire Dashboard Menu
	Table	xsfUCFunction	System Function List
		AK_xsfUCFunction_Name (Unique):1	
UCName	(varchar, 50)		
	Table	xsfUCFunction	System Function List
		AK_xsfUCFunction_Name (Unique):2	
UCPartMapKey	(uniqueidentifier, 16)		
	Table	xsfUCFunctionMap	Maps Capabilities to affected UI Parts
		Primary Key:1	
UCRoleKey	(uniqueidentifier, 16)		
	Table	xsfAlertSubscription	Alert Subscriptions
	Table	xsfEventSubscription	Event Subscriptions
	Table	xsfItemPermit	Item Permission settings
		AK_xsfItemPermit (Unique):1	Ref: xsfUCRole
Table	xsfRouteList	Document Route Detail	

Data Dictionary - Field Index

Wednesday, June 05, 2013
2:03 PM

Field	Type	Name	Description
UCRoleKey	(uniqueidentifier, 16)		
	Table	xsfUCFunctionPermit AK_xsfUCFunctionPermit (Unique):	Role Permission Settings Ref: xsfUCRole
	Table	xsfUCRole Primary Key:1	User Role Definitions
	Table	xsfUCSubRole AK_xsfUCSubRole (Unique):1	Sub Role Ref: xsfUCRole
	Table	xsfUserRole IX_xsfUserRole (Unique):2	User Role Membership Ref: xsfUCRole
UIFlags	(int, 10)		
	Table	xsfUIPart	User Interface Parts
	Table	xsfUIPartItem	User Interface Items
	Table	xsfUIPartItemHistory	History of UI Part Distributed Defaults
UnchangedAsOf	(datetime, 23)		
	Table	xsfCustomizationHistory	Customization History Snapshot Header
UnionCode	(varchar, 8)		
	Table	xsfContactCompany	Contact Company
UniReferenceKey	(uniqueidentifier, 16)		
	Table	xsfDocHeader IX_DocOCD:0	Document Header Ref: xsfReference
	Table	xsfDocItem	Document Item List
	Table	xsfReference Primary Key:1	CSI and/or Unifomat
	Table	xsfRouteSpecial	Document Route Selection Criteria
UOM	(char, 4)		
	Table	xsfDocItemTask	Revenue and Expense Details for an Item
	Table	xsfProjectWBS	Project Work Breakdown
UOM	(char, 30)		
	Table	xsfForecast	Forecast

Data Dictionary - Field Index

Wednesday, June 05, 2013

2:03 PM

Field	Type	Name	Description
Updated	(datetime, 23)		
	Table	xsfDocTemplate	Word Document Template
UpdateMask	(int, 10)		
	Table	xsfDocHeader	Document Header
	Table	xsfPjPeriodRev	Project Budget by Period Revision Header
	Table	xsfProjectRevision	Project Revision
		IX_xsfProjectRevision_Source:0	
UpdateTS	(timestamp, 8)		
	Table	xsfAlert	User Alerts List
	Table	xsfAlertSubscription	Alert Subscriptions
	Table	xsfAlertType	Alert Types
	Table	xsfAllocation	Allocations and Markups
	Table	xsfAPInfo	AP Doc Summary by Project
	Table	xsfArchiveDB	Archive Databases for static catalog content
	Table	xsfAttribute	Document Attributes
	Table	xsfCodeList	Coded Choices
	Table	xsfCodeListHistory	History of Codes
	Table	xsfCodeSet	Code Sets
	Table	xsfCodeSetHistory	History of Code Sets
	Table	xsfComment	Comment
	Table	xsfCompanyCSIMap	Company CSI Map
	Table	xsfCompliance	Vendor Subcontract Compliance Items
	Table	xsfComplianceType	Compliance Type
	Table	xsfComplianceTypeMap	Maps Compliance Type to Vendor and Commitments
	Table	xsfContactCompany	Contact Company
	Table	xsfContentHistoryList	Index of Content History Snapshots
	Table	xsfCSI	CSI Definition
	Table	xsfCustomizationHistory	Customization History Snapshot Header
	Table	xsfDashboardMenu	Spitfire Dashboard Menu
	Table	xsfDivision	Company Division List
	Table	xsfDocAddr	Address
	Table	xsfDocAlert	Document Alert
	Table	xsfDocDates	Document Dates
	Table	xsfDocDateType	Date Types

Field	Type	Name	Description
UpdateTS	(timestamp, 8)		
	Table	xsfDocHeader IX_DocByType:0	Document Header
	Table	xsfDocItem	Document Item List
	Table	xsfDocItemTask	Revenue and Expense Details for an Item
	Table	xsfDocPosting	Document Posting
	Table	xsfDocReference	Document Catagorical Reference
	Table	xsfDocRevision	Document Revision
	Table	xsfDocRevItem	Document Revision Items
	Table	xsfDocSession	User Document Sessions
	Table	xsfDocSingleUser	Document Exclusive User Reservation
	Table	xsfDocTemplate	Word Document Template
	Table	xsfDocType	Routable Document Types
	Table	xsfDocTypeSubcodes	Type Dependant Codes
	Table	xsfDocTypeSubcodesHistory	History of Doc Type Specific Codes
	Table	xsfDocWorkflow	Document Workflow Events
	Table	xsfDocWriteTx	Document Save Transaction Header
	Table	xsfDocWriteTxFact	Document Save Facts
	Table	xsfEventAgent	Event Notification Consumer Agents
	Table	xsfEventSubscription	Event Subscriptions
	Table	xsfFile	Stored File
	Table	xsfFileAccess	File Access Log
	Table	xsfFileAttach	Document Attachment List
	Table	xsfFileCheckout	File Checkout Information
	Table	xsfFileMarkup	File Version Markups and Resources
	Table	xsfFileRStatus	Store File Content Recognition Status
	Table	xsfFileVersion	Stored File Version
	Table	xsfFileVersionInfo	Stored File Version Attributes
	Table	xsfFlexKeySegments	Flex Key Segment Definition
	Table	xsfForecast IX_xsfForecast_AcctTasks (Unique	Forecast
	Table	xsfFSnapshotByPeriod	Project Budget by Period Snapshot
	Table	xsfInclusion	Include and Exclusion Items
	Table	xsfInclusionStock	Source list of stock inclusion entries
	Table	xsfItemContainer	Heirachical Container
	Table	xsfItemPermit	Item Permission settings
	Table	xsfMeetingAttendee	Meeting Attendee

Field	Type	Name	Description
UpdateTS	(timestamp, 8)		
	Table	xsfPartConfig	User Interface Part Customization
	Table	xsfPartConfigHistory	History of UI Part customizations
	Table	xsfPersistedData	Transient System Data
	Table	xsfPjPeriodRev	Project Budget by Period Revision Header
	Table	xsfPjPeriodRevBD	Project Budget by Period Revision Detail
	Table	xsfProgram	Project Programs
	Table	xsfProgramProjectMap	Program Project List
	Table	xsfProject	Project Information
	Table	xsfProjectRevision	Project Revision
	Table	xsfProjectRevisionWB	Project Revision Detail
	Table	xsfProjectWBS	Project Work Breakdown
	Table	xsfProjectWBSegment	Descriptive Titles for Project WBS Segments
	Table	xsfReference	CSI and/or Unifomat
	Table	xsfRegion	Region Definition
	Table	xsfRegionMap	Company Region Map
	Table	xsfRoute	Routed Document User Detail
	Table	xsfRouteContentPending	Catalog content to be updated for routing
	Table	xsfRoutedContent	Enumerates content of document when routed to spec
	Table	xsfRouteList	Document Route Detail
	Table	xSfRouteListMaster	Document Route List
	Table	xsfRouteSpecial	Document Route Selection Criteria
	Table	xsfRouteStep	Document Route Steps (Stage and Sequence)
	Table	xsfRouteTransmittal	Extends a Route Entry with a Transmittal
	Table	xsfRuleItem	Logic Rule Detail
	Table	xsfRuleItemHistory	History of Rule settings
	Table	xsfRuleItemValidation	Rule Item Validation
	Table	xsfRuleValueEnum	Rule Value Enumeration for Type
	Table	xsfRuleValueType	Rule Value Type
	Table	xsfStaticResource	Protected System Resources
	Table	xsfTaxRate	Tax Rate Definitions
	Table	xsfUCFunctionMap	Maps Capabilities to affected UI Parts
	Table	xsfUCFunctionPermit	Role Permission Settings
	Table	xsfUCRole	User Role Definitions
	Table	xsfUIPart	User Interface Parts
	Table	xsfUIPartItem	User Interface Items
	Table	xsfUIPartItemHistory	History of UI Part Distributed Defaults

Data Dictionary - Field Index

Wednesday, June 05, 2013

2:03 PM

Field	Type	Name	Description
UpdateTS	(timestamp, 8)		
	Table	xsfUser	System Users
	Table	xsfUserNotify	User Notification Settings
	Table	xsfUserProject	User Project Relationship
	Table	xsfUserRole	User Role Membership
	Table	xsfUserSession	User sessions
	Table	xsfWBPart	Work Breakdown Detail
	Table	xsfWorkflowLib	Workflow Script Library
UpdOk	(bit, 1)		
	Table	xsfItemPermit	Item Permission settings
	Table	xsfUCFunctionPermit	Role Permission Settings
UseCompanyAddr	(bit, 1)		
	Table	xsfUser	System Users
UserDocEdit	(bit, 1)		
	Table	xsfRoute	Routed Document User Detail
UserKey	(uniqueidentifier, 16)		
	Table	xsfAlert	User Alerts List
		IX_xsfAlert:1	Ref: xsfUser
	Table	xsfAlertSubscription	Alert Subscriptions
	Table	xsfContainerPermitCache	Preresolved Container Permissions by User
		AK_xsfContainerPermitCache (Uniq	
	Table	xsfDocAddr	Address
	Table	xsfDocPosting	Document Posting
	Table	xsfDocSingleUser	Document Exclusive User Reservation
		IX_xsfDocSingleUser_User:1	Ref: xsfUser
	Table	xsfEventSubscription	Event Subscriptions
	Table	xsfFileAccess	File Access Log
		IX_xsfFileAccess_byUser:1	Ref: xsfUser
	Table	xsfFileCheckout	File Checkout Information
	Table	xsfMeetingAttendee	Meeting Attendee
	Table	xsfPersistedData	Transient System Data
		IX_xsfPersistedData_ByUser:1	

Data Dictionary - Field Index

Wednesday, June 05, 2013

2:03 PM

Field	Type	Name	Description
UserKey	(uniqueidentifier, 16)		
	Table	xsfRoute	Routed Document User Detail
		AK_xsfRouteDetail (Unique):4	Ref: xsfUser
	Table	xsfRouteList	Document Route Detail
	Table	xsfUser	System Users
		Primary Key:1	
	Table	xsfUserNotify	User Notification Settings
	Table	xsfUserProject	User Project Relationship
		AK_UserProject (Unique):1	Ref: xsfUser
Table	xsfUserRole	User Role Membership	
	IX_xsfUserRole (Unique):1	Ref: xsfUser	
Table	xsfUserSession	User sessions	
	AK_xsfUserSession (Unique):1	Ref: xsfUser	
UserList	(bit, 1)		
	Table	xsfUserProject	User Project Relationship
UserLogin	(varchar, 47)		
	Table	xsfUser	System Users
		AK_xsfUser_login (Unique):1	
UserName	(varchar, 60)		
	Table	xsfUser	System Users
UserNotifyKey	(uniqueidentifier, 16)		
	Table	xsfUserNotify	User Notification Settings
		Primary Key:1	
UserProjectKey	(uniqueidentifier, 16)		
	Table	xsfUserProject	User Project Relationship
		Primary Key:1	
UserSelectable	(bit, 1)		
	Table	xsfEventAgent	Event Notification Consumer Agents

Data Dictionary - Field Index

Wednesday, June 05, 2013
2:03 PM

Field	Type	Name	Description
UserSessionKey	(uniqueidentifier, 16)		
	Table	xsfDocSession AK_xsfDocSession (Unique):3	User Document Sessions Ref: xsfUserSession
	Table	xsfDocSingleUser IX_xsfDocSingleUser_UserSession:	Document Exclusive User Reservation Ref: xsfUserSession
	Table	xsfUserSession Primary Key:1	User sessions
UseTransmittal	(bit, 1)		
	Table	xsfRouteList	Document Route Detail
ValidationLayer	(smallint, 5)		
	Table	xsfRuleItemValidation	Rule Item Validation
ValidationSequence	(smallint, 5)		
	Table	xsfRuleItemValidation	Rule Item Validation
ValidationType	(char, 1)		
	Table	xsfRuleItemValidation	Rule Item Validation
ValidValueLike	(varchar, 128)		
	Table	xsfRuleValueEnum AK_xsfRuleValueEnum (Unique):2	Rule Value Enumeration for Type
Value	(money, 19)		
	Table	xsfAttribute	Document Attributes
ValueTypeID	(varchar, 32)		
	Table	xsfRuleValueEnum AK_xsfRuleValueEnum (Unique):1	Rule Value Enumeration for Type
	Table	xsfRuleValueType AK_xsfRuleValueType (Unique):1	Rule Value Type
Vendor	(char, 16)		
	Table	xsfDocItemTask	Revenue and Expense Details for an Item

Data Dictionary - Field Index

Wednesday, June 05, 2013
2:03 PM

Field	Type	Name	Description
VendorID	(char, 16)		
	Table	xsfTaxRate	Tax Rate Definitions
	Table	xsfUser IX_VendorContact (Unique):2	System Users
VendorName	(varchar, 60)		
	Table	xsfForecast	Forecast
VerbalCO	(money, 19)		
	Table	xsfForecast	Forecast
ViaUI	(bit, 1)		
	Table	xsfUIPart	User Interface Parts
	Table	xsfUIPartItem	User Interface Items
	Table	xsfUIPartItemHistory	History of UI Part Distributed Defaults
Viewed	(datetime, 23)		
	Table	xsfAlert	User Alerts List
	Table	xsfRoute IX_xsfRouteToUser:4	Routed Document User Detail
Visibility	(smallint, 5)		
	Table	xsfWeatherReading	Weather Reading Data
Visible	(bit, 1)		
	Table	xsfPartConfig	User Interface Part Customization
	Table	xsfPartConfigHistory	History of UI Part customizations
WantsExclusive	(bit, 1)		
	Table	xsfDocSession	User Document Sessions
WBClass	(char, 2)		
	Table	xsfWBPart	Work Breakdown Detail

Data Dictionary - Field Index

Wednesday, June 05, 2013
2:03 PM

Field	Type	Name	Description
WBCode	(char, 32)		
	Table	xsfProjectRevisionWB IX_xsfProjectRevisionWB (Unique)	Project Revision Detail
	Table	xsfProjectWBS AK_xsfProjectWBS (Unique):2	Project Work Breakdown
WBPart	(char, 16)		
	Table	xsfPjPeriodRevBD AK_xsfPjPeriodRevBD (Unique):3	Project Budget by Period Revision Detail
	Table	xsfProjectRevisionWB IX_xsfProjectRevisionWB (Unique)	Project Revision Detail
	Table	xsfWBPart AK_xsfWBPart (Unique):1	Work Breakdown Detail
WBPartKey	(uniqueidentifier, 16)		
	Table	xsfWBPart Primary Key:1	Work Breakdown Detail
WBType	(char, 2)		
	Table	xsfWBPart	Work Breakdown Detail
WeatherInfoKey	(uniqueidentifier, 16)		
	Table	xsfWeatherReading Primary Key:1	Weather Reading Data
WeatherLocationKey	(uniqueidentifier, 16)		
	Table	xsfWeatherLocation Primary Key:1	Weather Report Locations
	Table	xsfWeatherReading AK_xsfWeatherReading (Unique):1	Weather Reading Data Ref: xsfWeatherLocation
WebCamURL	(varchar, 200)		
	Table	xsfProject	Project Information
Website	(varchar, 196)		
	Table	xsfDivision	Company Division List

Data Dictionary - Field Index

Wednesday, June 05, 2013

2:03 PM

Field	Type	Name	Description
WebURL	(varchar, 200)		
	Table	xsfUser	System Users
WhenTaken	(datetime, 23)		
	Table	xsfCustomizationHistory	Customization History Snapshot Header
Wind	(smallint, 5)		
	Table	xsfWeatherReading	Weather Reading Data
WindDirection	(char, 6)		
	Table	xsfWeatherReading	Weather Reading Data
WorkAmount	(money, 19)		
	Table	xsfDocItemTask	Revenue and Expense Details for an Item
WorkflowScript	(varchar, -1)		
	Table	xsfAlertType	Alert Types
	Table	xsfComplianceType	Compliance Type
	Table	xsfRoute	Routed Document User Detail
	Table	xsfRouteList	Document Route Detail
	Table	xsfWorkflowLib	Workflow Script Library
WorkflowScriptKey	(uniqueidentifier, 16)		
	Table	xsfDocWorkflow	Document Workflow Events
	Table	xsfWorkflowLib	Workflow Script Library
		Primary Key:1	
WorkflowScriptName	(varchar, 50)		
	Table	xsfWorkflowLib	Workflow Script Library
		AK_xsfWorkflowLib:1	
Zip	(char, 10)		
	Table	xsfDivision	Company Division List
	Table	xsfDocAddr	Address
	Table	xsfProject	Project Information

Data Dictionary - Field Index

Wednesday, June 05, 2013
2:03 PM

Field	Type	Name	Description
zip	(varchar, 10)		
	Table	xsfUser	System Users

SYS

xsfAuditData**Audit Trail**

Each row details a change to a data element

ChangeKey	Guid Default(newid())	Primary Key:1
TableID	Smallint(5)	In Index audit_by_record:1
ColID	Smallint(5)	In Index audit_by_record:4
KeyValue	Guid	In Index audit_by_when:2
UserKey	Guid NULL	In Index audit_by_user:1
ChangeWhen	Datetime(23,3) Default(getdate())	In Index audit_by_when:1
PriorValue	Sql_variant(0) NULL	
NewValue	Sql_variant(0) NULL	

Fields: 8

SYS

xsfConfig**Configuration Settings**

Each row stores a configuration value

CfgIDKey	Guid Default(newid())	Primary Key:1
CompanyID	Char(10) Default('[ALL]')	In Index AK_xSfConfig (Unique):1
Key	Varchar(64)	In Index AK_xSfConfig (Unique):2
ValueType	Char(1) NULL Default('C')	
ValueLength	Smallint(5) Default((0))	
Value	Varchar(80)	
UpdateTS	Timestamp(8)	

Fields: 7

SYS

xsfEventLog**Event Log**

Information about system events

EventID	Int(10) Identity	In Index PK_xsfEventLog (Unique):3
UserName	Varchar(64)	When available, the Spitfire User; otherwise the SQL user
HostWS	Varchar(32)	When available, the remote host; normally the SQL server name
EventType	Char(2)	In Index PK_xsfEventLog (Unique):2
EventStart	Datetime(23,3) Default(getdate())	This date is always set to the time when the row was added In Index PK_xsfEventLog (Unique):1
EventEnd	Datetime(23,3) NULL	
EventCode	Int(10) NULL	
EventText	Varchar(4000) NULL	

Fields: 8

SYS

xsfFiscalMonth**Fiscal Months**

Each row defines a valid month in a fiscal year

FMonth	Char(2)	Primary Key:1
--------	---------	---------------

Fields: 1

SYS

xsfFiscalYear

Fiscal Years

Each row defines a valid fiscal year

Field Name	Field Type	Field Properties
FYear	Char(4)	Primary Key:1
StartPeriod	Char(2) Default('01')	
LastPeriod	Char(2) Default('12')	
UpdateTS	Timestamp(8)	

Fields: 4

SYS

xsfLookup

Lookup

Defines a lookup

Field Name	Field Type	Field Properties
LookupKey	Guid Default(newid())	Primary Key:1
LookupName	Varchar(32)	In Index IX_xsfLookupName (Unique):1
Product	Char(3) Default('SPM')	
TargetDS	Varchar(16) Default('')	
LookupResultField	Guid NULL	
LookupResultKey	Guid NULL	In Index IX_xsfLookupAlternates:1 References xsfLookupResult.LookupResultKey
OfferSequence	Smallint(5) Default(0)	In Index IX_xsfLookupAlternates:2
Caption	Varchar(60)	In Index IX_xsfLookupAlternates:3
DataQuery	Varchar(4000)	
PreLoad	Bit(1) Default(1)	
Active	Bit(1) Default(1)	
UpdateTS	Timestamp(8) NULL	

Fields: 12

SYS

xsflLookupField

Lookup Fields

Defines the fields in various lookups

LookupKey	Guid	In Index IX_xsflLookupFieldSeq (Unique):1 References xsflLookup.LookupKey
LookupFieldKey	Guid Default(newid())	Primary Key:1
LookupResultKey	Guid NULL	References xsflLookupResult.LookupResultKey
FieldSequence	Smallint(5)	In Index IX_xsflLookupFieldSeq (Unique):2
FieldQuery	Varchar(128)	
FieldAlias	Varchar(60) Default("")	In Index IX_xsflLookupFieldSeq (Unique):3
Label	Varchar(50)	Column Label
ShowField	Char(1) Default('P')	Primary, Secondary, Hidden Check (charindex([ShowField], 'PSH') > (0))
GridColumnClass	Varchar(50) Default("")	
DisplayFormat	Varchar(50) Default("")	
WParamName	Varchar(40) Default("")	
WParamLabel	Varchar(50) NULL	Filter Label
WPredicate	Varchar(250) NULL	
WOperatorType	Char(1) Default('L')	
WDefault	Char(5) Default("")	
PredicateMode	Char(1) Default('N')	Dynamic, Input, Required, or No Check (charindex([PredicateMode], 'PDIRN') > (0))
OrderByMode	Char(1) Default('N')	Check (charindex([OrderByMode], 'ABCDEFN') > (0))
IsInputOnly	Bit(1) Default((0))	
Active	Bit(1) Default((1))	
UpdateTS	Timestamp(8) NULL	

Fields: 20

SYS

xsflLookupResult

Lookup Result

Defines the set of results that various lookups can output

LookupResultKey	Guid Default(newid())	Primary Key:1
Product	Char(3) Default('SPM')	In Index IX_xsflLookupResultName (Unique):
LookupResultName	Varchar(32)	In Index IX_xsflLookupResultName (Unique):
TargetDS	Varchar(16) Default("")	
TestQuery	Varchar(4000) Default("")	
PVType	Varchar(32) NULL	When set to GUID, engine verifies test value is a UniquelIdentifier and assumes is invalid if fails
Active	Bit(1) Default(1)	
UpdateTS	Timestamp(8) NULL	

Fields: 8

SYS

xsfSysCatalog**System Catalog**

Enumerates tables and provides extended description and relationship information

TableID	Int(10) Identity	Primary Key:1
Owner	Varchar(32)	
TableName	Varchar(64)	In Index IX_Catalog_TableName (Unique):1
LongName	Varchar(64) NULL	
TableSeq	Int(10) NULL	
TableType	Char(1) NULL	
RootTable	Int(10) NULL	
ParentID	Int(10) NULL	
ParentJoin	Varchar(64) NULL	
TableDescr	Varchar(128) NULL	
Product	Char(3) NULL	
TargetDB	Char(1) NULL	

Fields: 12

SYS

xsfSysColumn**System Column Catalog**

Enumerates columns

TableID	Int(10)	Primary Key:1
colname	Varchar(128)	Primary Key:2
columnid	Smallint(5) NULL	In Index xsfSysColumns:2
base_t_id	Smallint(5) NULL	
base_c_id	Smallint(5) NULL	
comment	Varchar(128) NULL	
InternalNote	Varchar(256) NULL	

Fields: 7

Summary of Changes

The pages that follow enumerate changes to the database schema over time

- *Changes are listed in reverse chronological order (beginning with the most recent)*
- *Potentially breaking changes such as fields renamed or removed are shown in red*

Revision Number(s)	120
Start Date:	OCT 2012
Actual End Date:	SR 120:DEC 2012:
Comment	sfDocSys, from Version 4.2 to 4.3

Revision 120

- xsfAlertSubscription
 - Added subtype VC(8)
- xsfContactCompany
 - Added IsPreliminary BIT
- xsfDocItemTask
 - Added csAmount Money
 - Added csCheck BIT
 - Added csDate DateTime
 - Added csString016 VC(16)
 - Added csString030 VC(30)
 - Added csString060 VC(60)
 - Added SOVWork Money
 - Added SOVMaterials Money
 - Added WorkAmount Money
- xsfProject
 - Added WebCamURL VC(200)
- New Tables
 - xsfFileAccess

Revision Number(s)	115
Start Date:	May 2011
Actual End Date:	SR115: DEC 2011
Comment	sfDocSys, from Version 4.1 to 4.2

Revision 116

- Minor indexing tweaks

Revision 115

- xsf DocRevision
 - Added sfVersion SmallMoney (eg 4.1)
 - Added csAmount Money
 - Added csCheck BIT
 - Added csDate DateTime
 - Added csString016 VC(16)
 - Added csString030 VC(30)
 - Added csString060 VC(60)
 - Added EmailSubject VC(80)
 - **Removed** BinData (upgrade moves files to catalog for full version control)
 - **Removed** TxtData
 - **Removed** BinType
- xsfDocRevItem
 - Added ItemSeq INT
- xsfDocTemplate
 - Added DefaultInclude C(1)
 - Added ProjectSubtype VC(8)
 - Added HasBookmarks BIT
- xsfFile
 - Added RefreshBookmarks BIT
 - Added RoutedContent BIT
- xsfFileAttach
 - Added AttachSeq SmallInt
- xsfFileVersionInfo
 - Added xsfFileBinKey UniqueIdentifier

- xsfFileVersion
 - **Removed:** DocKey
 - **Removed:** RevId
 - **Renamed:** FileVerKey → FileBinKey

- xsfForecast
 - Added ActualPY Money
 - Added ActualPP Money
 - Added ActualCY Money
 - Added ActualCP Money
 - Added ActualUnitsPY Money
 - Added ActualUnitsPP Money
 - Added ActualUnitsCY Money
 - Added ActualUnitsCP Money
 - Added czUDSAmt1 Money
 - Added czUDSAmt2 Money
 - Added czUDSAmt3 Money
 - Added czUDSText1 VC(255)
 - Added czUDSText2 VC(255)
 - Added VendorName VC(60)...the vendor name or 'Multiple'

- xsfInclusion
 - Increased Paragraph to VC(30)
 - Added csAmount Money
 - Added csCheck BIT
 - Added csDate DateTime
 - Added csString016 VC(16)
 - Added csString030 VC(30)
 - Added csString060 VC(60)
 -

- xsfMeetingAttendee
 - Added csAmount Money
 - Added csCheck BIT
 - Added csDate DateTime
 - Added csString016 VC(16)
 - Added csString030 VC(30)
 - Added csString060 VC(60)

- xsfProgram
 - Increased ProgramID to VC(24)

- xsfProject
 - Added County VC(40)
 - Added PlanRoomMode VC(8)

- xsfRoute
 - Added ResponseCode VC(8)
 - Added Downloaded DateTime

- xsfRouteList
 - Added DefaultVia C(1)
 - Added DueInDays SmallMoney
 - Added NoRepeats BIT
 - Added SetEmailFrom BIT

- xsfRouteSpecial
 - Added ProjectSubtype VC(8)

- xsfRuleItem
 - Added Immutable BIT

- xsfDocType
 - **Renamed** IsPublic → PlanRoom
- xsfUserRole
 - Increased ProgramID to VC(24)
- xsfUserSession
 - Added AgentInfo VC(32)

- vsf_Subcontract
 - **Renamed** Subcontract_Desc → SubcontractDesc (word template compatibility)
 - **Renamed** Specialty_CD → ReferenceDesc (accuracy and word compatibility)

- New Tables

<ul style="list-style-type: none"> ○ xsfCodListHistory ○ xsfCodeSetHistory ○ xsfDocTypeSubcodesHistory ○ xsfInclusionStock ○ xsfPartConfigHistory ○ xsfRouteStep 	<ul style="list-style-type: none"> ○ xsfRoutedContent ○ xsfRoutedContentPending ○ xsfRuleItemHistory ○ xsfUIPartItemHistory ○
------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------	----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------

Revision Number(s)	110-111
Start Date:	Feb 12 th 2010
Actual End Date:	SR110: 2011-09-20 SR111.... 2011-11-19
Comment	sfDocSys, from Version 4.0 to 4.1

Revision 111

- Minor indexing tweaks

Revision 110

- xsfCompany renamed table to xsfDivision
 - **Renamed** CompanyKey → [DivisionKey]
 - **Renamed** CompanyID → [DivisionID]
 - **Renamed** CompanyName → [DivisionName]
 - Company ID -> Division ID **renamed** across tables
 - xsfAlertSubscription
 - xsfDocTemplate
 - xsfFile
 - xsfRouteSpecial
 - xsfUserRole
- xsfAlertSubscription
 - **Renamed:** CompanyID → DivisionID
 - Added Suspend bit
- xsf DocHeader
 - **Renamed** IsSubcontractor → DocFlag
 - Added LastRouteKey GUID
 - Added ContractType varchar(8) with code set
 - **Renamed** RejectCode → [Reason]
 - Added RouteFlags [int] (future routing features)
 - **Renamed** Company → DivisionID
 - **Renamed** BudgetRevID → BudgetRevFlag
- xsf DocRevision
 - Added Bond Money
 - Added BondRate Dec(9,6)

- xsfDocType
 - **Renamed** PushPJSubmit → CheckCompliance
 - Added IsPublic

- xsfFile
 - Keywords increased to VC(2000)
 - **Renamed** CompanyID -> DivisionID
 - Added GeoLat and GeoLng Dec(9,6)

- xsfFileVersion
 - **Removed:** [SourceRevision] (already in xsfFileVersionInfo)
 - Moved [FromUser] → xsfFileVersionInfo
 - Moved [TxtData] → xsfFileVersionInfo
 - Changed [BinData] to varbinary(max)
 - Moved [DataHash] → xsfFileVersionInfo

- xsfFileVersionInfo
 - Added [DataHash] [char](32) (moving from xsfFileVersion)
 - Added: [FromUser] GUID (moving from xsfFileVersion)
 - Added [ArchiveDBKey] GUID
 - Changed [TxtData] to [varchar](max)

- xsfFlexKeySegments
 - Added SegBreakFlag – C(1)
 - Added SegRollupFlag --C(1)
 - Added AllowTitles BIT

- xsfForecast
 - Added OriginalRevenue MONEY
 - Added SCRemainingPay
 - Added TrackingNotes VC(2048)
 - **Removed** ChangeBudgetRevenue and PendingBudgetRevenue
 - ProjectFBDetail (materialized projection of a snapshot)
 - The column formerly named VerbalCOREvenue will now be properly named **ApprovedCOREvenue**
 - The column formerly named PendingFACAmount will now be properly named **PriorFACRevenue**
 - The column OriginalRevenue has been added immediately after BudgetRevenue
 - The column TaskRowKey has been added immediately after ForecastRowKey

- xsfPartConfig
 - Added Container
 - Added Filter
 - Added LookupName (Migrated out of AuxData)
 - Added DisplayFormat (Migrated out of AuxData)
 - Added RequiredWhen (bit flag)
 - Added IsDistributed

- xsfProjectRevision
 - **Renamed** ProjectRevHdrKey → BudgetRevisionKey
 - Changed RevisionSource to C(2)
 - Added ExternalID
 - Added SourceDocRevKey
 - Added HitsCost
 - Added HitsRevenue

- xsfProjectRevisionWB
 - **Renamed** ProjectRevHdrKey → BudgetRevisionKey

- xsfUCRole
 - Added: AllowUnconditional bit
- xsfUser
 - Added Country char(3) with code set
 - Added County varchar(40)
 - Added [Signature] GUID
 - Added [Likeness] GUID
 - **Removed** IsContact
 - Added [SlidingExpiration] [bit]
 - Added [PWMustChange] [bit] NOT NULL,
 - Added [PWAgging] [bit] NOT NULL,
 - **Renamed** SolCompany → [DivisionID]
 - Added [LockoutReason] [varchar](60) NULL,
 - Added [FailedLoginRun] [money] NOT NULL,
 - Added [LockedOutUntil] [datetime] NULL,
 - Added [Expiration] [datetime] NULL,

- xsfUserProject
 - Added: RoleDescription
 - Added Starting
 - Added Ending

- xsfUserRole
 - Added ProgramID
 - **Renamed:** CompanyID to DivisionID

➤ New Tables

- xsfArchiveDB
- xsfDocPosting
- xsfDocSession
- xsfDocSingleUser
- xsfDocWorkflow
- xsfDocWriteTx
- xsfDocWriteTxFact
- xsfProgram
-
- xsfProgramProjectMap
- xsfProjectWBSSegment
- xsfUserSession
- xsfUIPart
- xsfUIPartItem
- xsfWorkflowLib
-

➤ Blob data types update

- Table [xsfAttribute] . [Note]
- Table [xsfPersistedData] . [BinData]
- Table [xsfFileRStatus] . [Details]
- Table [xsfComment] . [Note]
- Table [xsfProject] . [Description]
- Table [xsfRouteTransmittal] . [BinData]
- Table [xsfMeetingAttendee] . [Note]
- Table [xsfDocItem] . [Description]
- Table [xsfDocTemplate] . [binData]
- Table [xsfInclusion] . [ItemText]
- Table [xsfRouteList] . [WorkflowScript]
- Table [xsfAlertType] . [WorkflowScript]
- Table [xsfDocItemTask] . [Note]
- Table [xsfDocDates] . [Note]
- Table [xsfFileVersionInfo] . [TxtData]
- Table [xsfComplianceType] . [WorkflowScript]
- Table [xsfFileAttach] . [Note]
- Table [xsfFileVersion] , with columns also being removed
- Table [xsfFileMarkup]
- Table [xsfDocRevision], columns:Notes, NoteA, NoteB, NoteEmI, TxtData, BinData
- Table [xsfRoute], columns: Note, Request, Response, WorkflowScript

(Inside back cover)

